Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires January 31, 2004

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

JAN 20 2012 MDA 701-02-0014 6 If Indian, Allottee or Tribe Name

		,	Far	mington Field (Offigicarilla A	pache	Nation	
SUBMIT IN TRIPLICATE - Other instructions on revers				u on Land Ivialia	99. Wellin or	CA/Ag	reement, Name and/or No	
l Type of Well					Joint Van	tura An	raamant	
Oil Well Gas Well Other					Joint Venture Agreement 8. Well Name and No			
2 Name of Operator					Apache JVA 3C			
Jicarilla Apache Energy Corp (JAECO)				9. API Well No.				
Ba Address	3b. Phone No. (include area code)			30-039-31099				
P.O. Box 710 Dulce, New Mexic	575-759-3224			10 Field and Pool, or Exploratory Area				
Location of Well (Footage, Sec., T, R., M., or Survey Description)						Blanco Mesa Verde 11. County or Parish, State		
1515' FNL & 2100' FWL, Sec 21, T27N, R2W, NMPM					11. County o	or Parish	i, State	
						Rio Arriba County, New Mexico		
12. CHECK APP	PROPRIATE BOX(ES) TO	INDICATE	NATURE C	F NOTICE, RI	EPORT, OR	OTH	ER DATA	
TYPE OF SUBMISSION TYPE OF ACT								
	Acidıze	Deepen		Production (Start	/Resume)	□ w.	ater Shut-Off	
Notice of Intent	Alter Casing	Fracture Tre	at 🔲	Reclamation		□ w	ell Integrity	
Subsequent Report	Casing Repair	✓ New Constr	uction 🔲	Recomplete		Ot	her	
- BY	Change Plans	Plug and Ab	andon 🔲	Temporarily Abandon				
☐ Final Abandonment Notice	Convert to Injection	Plug Back		Water Disposal		_		
determined that the site is ready in the site is ready in the subject well and the subject well are a subject. STC: Sawtooth Collar, 2 jts of sing: 10 bbls pre flush + 6 cu yd: (a) 1:00 pm, 1/11/2012, checked for subject the state of the subject to the subject	@ 9:30 am, 1/10/2012. Mo-Tecsg, insert float, 13 jts esg for a s, 162 cf, Type 1-2 14.7ppg recloat - held Circ 6 bbls cement to 700 psi for 30 minutes - held	: Surface Rig 21 a total of 316' ca di-mix cement t	2 air drilled a using, set at 3 collowed by v	a 12 1/4" hole to 15' GL with inservood wiper plug,	321' GL. 1/1 rt float at 274 21 bbls fresh	1/2012 ' GL. M. water. tst weldment jo	Mo-Te ran 9 5/8" 36# Mo-Te cemented casing Bumped plug to 250 psi	
 I hereby certify that the foregoing Name (PrintedlTyped) 	g is true and correct							
Charles Neeley		-	Fitle PE/agei	nt				
Signature	when		Dăte 1/19/20	12		·		
rana maranara (La silanda de Sandalda)	THIS SPACE FO	OR FEDERAL	OR STATE	OFFICE USE	ere (glore) (ref. esegue)			
Approved by (Signature)			Name (Printed/T	vned)	Title			
Conditions of approval, if any, are attached. Approval of this notice does not warrant or				<u> </u>	L,		Date	
conditions of approval, if any, are adacticed. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			ease					

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious of fraudulent statements of representations as to any inatter within its jurisdiction.