District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W Grand Ave , Artesia, NM 88210 District III 1000 Rio Brazos Rd , Aztec, NM 87410

District IV

1220 S St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008 For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the

appropriate NMOCD District Office. Pit Closed-Loon System Relow-Grade Tank or

Proposed Alternative Method Permit or Closure Plan Application
Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method X Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
Modification to an existing permit
Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,
below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of hability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499
Facility or well name: SCOTT 7B
API Number: 30-045-34952 OCD Permit Number:
U/L or Qtr/Qtr: C(NE/NW) Section: 3 Township: 31N Range: 10W County: San Juan Center of Proposed Design: Latitude: 36.93273 °N Longitude: 107.87292 °W NAD: 1927 X 1983
Center of Proposed Design: Latitude: 36.93273 °N Longitude: 107.87292 °W NAD: 1927 X 1983 Surface Owner: X Federal State Private Tribal Trust or Indian Allotment
X Pit: Subsection F or G of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency X Cavitation P&A (Pre-set)
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions L x W x D
3
Closed-loop System: Subsection H of 19.15.17 11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or
notice of intent)
Drying Pad Above Ground Steel Tanks Haul-off Bins Other
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVD Other
Liner Seams Welded Factory Other RECENTER
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Oil CONS. DIV. DIST 3 Tank Construction material:
Tank Construction material:
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Visible sidewalls and liner Visible sidewalls only Other
Liner Type: Thicknessmil HDPE PVC Other
5 Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of app	roval.	
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks)	Yes NA	□No	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	🗀		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐Yes ☐NA	No	
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	Yes	No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No	
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No	
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No	
Within a 100-year floodplain - FEMA map	Yes	No	

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions. Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15 17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17 11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan
Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
14
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15 4 W. F. J.
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Soft Backfird and Cover Design Specifications - based upon the appropriate requirements of Subsection 11 of 17:13:17:13 NWAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

16			
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.	ים		
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI Disposal Facility Permit #: NM-01-0011 / NM-01-	0010B		
Disposal Facility Name: Basin Disposal Facility Disposal Facility Permit #: NM-01-005			
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nbe used for future Yes (If yes, please provide the information No	e service and		
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 N Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17 13 NMAC	NMAC		
17			
Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC Instructions Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the soffice for consideration of approval Justifications and/or demonstrations of equivalency are required Please refer to 19 15 17.10 NMAC for guidance			
Ground water is less than 50 feet below the bottom of the buried waste.	Yes No		
- NM Office of the State Engineer - IWATERS database search; USGS. Data obtained from nearby wells	N/A		
Ground water is between 50 and 100 feet below the bottom of the buried waste	Yes No		
- NM Office of the State Engineer - IWATERS database search, USGS; Data obtained from nearby wells	N/A		
Ground water is more than 100 feet below the bottom of the buried waste.	Yes No		
- NM Office of the State Engineer - iWATERS database search; USGS, Data obtained from nearby wells			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark)	Yes No		
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site, Aerial photo, satellite image	Yes No		
	Yes No		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application. - NM Office of the State Engineer - iWATERS database, Visual inspection (certification) of the proposed site			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	Yes No		
Within 500 feet of a wetland	Yes No		
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site			
Within the area overlying a subsurface mine.	Yes No		
- Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division			
Within an unstable area	∐Yes ∐No		
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society, Topographic map 			
Within a 100-year floodplain FEMA map	Yes No		
18			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must bee attached to the close by a check mark in the box, that the documents are attached.	sure plan. Please indicate,		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19 15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NM	IAC		
X Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standard	ds cannot be achieved)		
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC			

Form C-144

19	
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accura	ite and complete to the best of my knowledge and belief.
	mia.
Signature:	Date:
e-mail address:	Telephone:
20	
OCD Approval: Permit Application (including closure plan),	Closure Plan (only) OCD Conditions (see attachment)
OCD Representative Signature:	1/2/1/2010
OCD Representative Signature.	Y-h114 Approval Date: 2/06/2012
Title: Consolique Office	OCD Permit Number:
The Complete Control	OOD GETIME (Validate)
21	
Closure Report (required within 60 days of closure completion): Subs	ONLOW V 0610 16 17 12 NIMAC
	implementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the completion	
approved closure plan has been obtained and the closure activities have been con	npleted.
	Closure Completion Date: 8/14/2009
22	
Closure Method:	
Waste Excavation and Removal On-site Closure Method	X Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain	
23	The A Heller A. L. C. C. L. C.
Closure Report Regarding Waste Removal Closure For Closed-loop Systems	ng fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.	ng finius and arm canings were aisposed. Ose anachment if more man two facilities
Disposal Facility Name	Disposal Facility Permit Number:
Disposal Facility Name.	Disposal Facility Pennit Number:
Were the closed-loop system operations and associated activities performed or	
Yes (If yes, please demonstrate compliane to the items below)	No
Required for impacted areas which will not be used for future service and ope Site Reclamation (Photo Documentation)	erations:
Soil Backfilling and Cover Installation	
l '넊	
Re-vegetation Application Rates and Seeding Technique	
24	
	owing items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.	
Proof of Closure Notice (surface owner and division)	
Proof of Deed Notice (required for on-site closure)	
Plot Plan (for on-site closures and temporary pits)	
Confirmation Sampling Analytical Results (if applicable)	
Waste Material Sampling Analytical Results (if applicable)	
Disposal Facility Name and Permit Number	· ·
Soil Backfilling and Cover Installation	
Re-vegetation Application Rates and Seeding Technique	
I ≒=	
Site Reclamation (Photo Documentation)	1
On-site Closure Location: Latitude:	Longitude:NAD19271983
25	
Operator Closure Certification:	
	report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and donditions spe	cified in the approved closure plan
Name (Print): \\ \\ \Amagin E. \\ Jaragrifilo \/	/// Title: Staff Regulatory Technician
Walle (Fill)	Ol + Ol 1
Signature:	Date:
e-mail address: marie e.jaramillo@conocophi/lips.com	Telephone: \(\frac{1}{5}05-326-9865\)

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	ND
TPH	EPA SW-846 418.1	2500	21.0
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	15

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.

SCOTT 7B API# 30-045-34952 PERMIT# 6918 RESULTS/SAMPLES

Scott 7B

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

 The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components ³	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA:SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50:	ND .
TPH'	EPA SW-846 418.1	2500	21.0
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	15

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location:
- 2. In the event/the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B).
- Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations:



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics **Total Petroleum Hydrocarbons**

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Pre-set Cuttings	Date Reported:	08-18-09
Laboratory Number:	51302	Date Sampled:	08-14-09
Chain of Custody No:	6740	Date Received:	08-14-09
Sample Matrix:	Soil	Date Extracted:	08-17-09
Preservative:	Cool	Date Analyzed:	08-17-09
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Scott 7B



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	08-17-09 QA/QC	Date Reported:	08-18-09
Laboratory Number:	51117	Date Sampled.	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-17-09
Condition:	N/A	Analysis Requested:	TPH

	160ei Date	I-CeliRF	C-Cal RF	% Difference	Accept Range
Gasoline Range C5 - C10	05-07-07	1.0534E+003	1.0538E+003	0.04%	0 - 15%
Diesel Range C10 - C28	05-07-07	1.0808E+003	1.0812E+003	0.04%	0 - 15%

Blank Corre (mg/L s mg/Kg)	Concentration	Detection Limit
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

Duplicate Cont. (mg/Kg)	Sample	Bioplicate	% Difference	Accept Range
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%
Diesel Range C10 - C28	ND	ND	0.0%	0 - 30%

Spike Conc. (mg/Kg)	Simple	Splke Added	Spike Result	% Recovery	Accept Range
Gasoline Range C5 - C10	ND	250	243	97.2%	75 - 125%
Diesel Range C10 - C28	ND	250	255	102%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 51117 - 51121, 51230 - 51233, and 51302.

Analyst

Christian Weller Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Pre-set Cuttings	Date Reported:	08-18-09
Laboratory Number:	51302	Date Sampled:	08-14-09
Chain of Custody:	6740	Date Received:	08-14-09
Sample Matrix:	Soil	Date Analyzed:	08-17-09
Preservative:	Cool	Date Extracted:	08-17-09
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	ND	1.0
Ethylbenzene	ND	1.0
p,m-Xylene	ND	1.2
o-Xylene	ND	0.9
Total BTEX	ND	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Scott 7B

Analyst

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

, , , , , , , , , , , , , , , , , , , ,		
N/A	Project #:	N/A
08-17-BT QA/QC	Date Reported:	08-18-09
51117	Date Sampled:	N/A
Şoil	Date Received:	N/A
N/A	Date Analyzed	08-17-09
N/A	Analysis [.]	BTEX
	08-17-BT QA/QC 51117 Soil N/A	08-17-BT QA/QC Date Reported: 51117 Date Sampled: Soil Date Received: N/A Date Analyzed

Calibration and Detection Limits (uglls)	I-Cal RF	G-Ca⊩RF: ≗ Accept Ran	%Diff: 1 je 0 - 15%	Blank Gone	i Deteci Limit
Benzene	1.2834E+006	1 2859E+006	0.2%	ND	0.1
Toluene	8.1793E+005	8.1957E+005	0.2%	ND	0.1
Ethylbenzene	6.4366E+005	6 4495E+005	0.2%	ND	0.1
p,m-Xylene	1 5142E+006	1 5172E+006	0.2%	ND	0.1
o-Xylene	5.9106E+005	5.9224E+005	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample Du	plicate	76Diff.	Accept Range	Detect/Limit
Benzene	ND	ND	0.0%	0 - 30%	0.9
Toluene	ND	ND	0.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	ND	ND	0.0%	0 - 30%	1.2
o-Xylene	ND	ND	0.0%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample Amo	unt Spiked: Spik	ed Sample	%/Recovery	/Accept Range
Benzene	ND	50.0	48.9	97.8%	39 - 150
Toluene	ND	50.0	47.8	95.6%	46 - 148
Ethylbenzene	ND	50.0	46.8	93.6%	32 - 160
p,m-Xylene	ND	100	97.9	97.9%	46 - 148
o-Xylene	ND	50.0	47.5	95.0%	46 - 148

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996

Comments:

QA/QC for Samples 51117 - 51121, 51230 - 51233, and 51302.

Analyst



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Pre-set Cuttings	Date Reported:	08-18-09
Laboratory Number:	51302	Date Sampled:	08-14-09
Chain of Custody No:	6740	Date Received:	08-14-09
Sample Matrix:	Soil	Date Extracted:	08-17-09
Preservative:	Cool	Date Analyzed:	08-17-09
Condition:	Intact	Analysis Needed:	TPH-418.1

7.3.2.4.3		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

21.0

16.5

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Scott 7B.

Analyst

Review



EPA METHOD 418.1 TOTAL PETROLEUM HYROCARBONS QUALITY ASSURANCE REPORT

Client:

QA/QC

Project #:

N/A

Sample ID:

QA/QC

Date Reported:

08-17-09

Laboratory Number:

08-17-TPH.QA/QC 51201

Date Sampled:

N/A

TPH

Sample Matrix:

Freon-113

Date Analyzed:

08-17-09

Preservative: Condition:

N/A N/A Date Extracted: Analysis Needed: 08-17-09

Calibration

I-Cal Date

C-Cal Date

I-Cal RF:

C-Cal RF:

% Difference

Accept. Range

08-03-09

08-17-09

1,380

1,250

9.4%

+/- 10%

Blank Conc. (mg/Kg)

TPH

Concentration ND

Detection Limit

16.5

Duplicate Conc. (mg/Kg)

TPH

Sample 359

Duplicate 386

% Difference 7.7%

Accept. Range +/- 30%

Spike Conc. (mg/Kg)

TPH

Sample 359

Spike Added Spike Result % Recovery 2,000

2,370

100%

Accept Range 80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 51201 - 51204, 51273 - 51276, 51300 and 51302.

Analyst

Mister Muceters



Chloride

Client: ConocoPhillips Project #: 96052-0026 Date Reported: 08-18-09 Sample ID: **Pre-set Cuttings** 08-14-09 Lab ID#: 51302 Date Sampled: Sample Matrix: Soil Date Received: 08-14-09 Date Analyzed: 08-17-09 Preservative: Cool 6740 Condition: Intact Chain of Custody:

Parameter

Concentration (mg/Kg)

Total Chloride

15

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Scott 7B.

Analyst 7

Review

OIL CONS. DIV.

DIST. 3

DATE: 2/01/12

WELL NAME: SCOTT 7B

API# 30-045-34952 PERMIT #: 6918

MISSING DATA: COPY OF CLOSURE NOTIFICATION – NOT NEEDED CL