

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

~Amended~ Form C-103
Revised August 1, 2011

WELL API NO.	30-043-21117
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. LG-3925	
7. Lease Name or Unit Agreement Name Lybrook H36-2307	
8. Well Number 01H	
9. OGRID Number 282327	
10. Pool name or Wildcat Lybrook Gallup	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Encana Oil & Gas (USA) Inc.

3. Address of Operator
370 17th Street, Suite 1700 Denver, CO 80202

4. Well Location

SHL: Unit Letter: H 1550 feet from the NORTH line and 280 feet from the EAST line

BHL: Unit Letter: E 1550 feet from the NORTH line and 330 feet from the WEST line

Section 36 Township 23N Range 7W NMPM Sandoval County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
7265 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

This sundry includes supplemental data to the intermediate casing string and cement sundry submitted on 12/21/11.

Intermediate hole from surface to 4829' TVD/MD. Intermediate casing string set between 0 and 4810' TVD/MD.

Casing and BOP tested on 12/20/11. BOP pressure held at 1500 psi for 60 minutes and casing pressure held at 600 psi for 60 minutes. No pressure drop.

RCVD FEB 17 '12
OIL CONS. DIV.

Spud Date: 12/08/11

Rig Release Date:

DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Brenda R. Linster TITLE Regulatory Advisor
Type or print name: Brenda R. Linster Email address: brenda.linster@encana.com

DATE 02/15/12
PHONE: 720-876-3989

For State Use Only

APPROVED BY: Bel Bell TITLE Deputy Oil & Gas Inspector,
Conditions of Approval (if any): District #3 DATE 2-22-12

rv