

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

**RECEIVED****FEB 09 2012**Farmington Field Office  
Bureau of Land Management1. Type of Well  
GAS

2. Name of Operator

**ConocoPhillips**

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit E (SW/NW), 2480' FNL &amp; 945' FWL, Section 23, T26N, R6W, NMPM

5. Lease Number  
SF-079296

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
FEDERAL 12P

9. API Well No.  
  
30-039-30757

10. Field and Pool  
BLANCO MV / BASIN DK

11. County and State  
Rio Arriba, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - ☐ Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☒ Final Abandonment☐ Altering Casing☐ Conversion to Injection**RCVD FEB 13 '12  
OIL CONS. DIV.****13. Describe Proposed or Completed Operations****DIST. 3**

01/19/12 MIRU AWS 673. NU BOPE. PT csg. to 600#/30min @ 15:15hrs on 01/21/12 Test - OK. PU & TIH w/ 8 3/4" bit. Tagged @ 310' & DO cmt to 356'. Drilled ahead to 3380' - Inter TD reached 01/24/12. Circ. hole & RIH w/ 80jts, 7", 20#, J-55 ST & C csg set @ 3370'. 1st Stage: Pre-flushed w/ 10bbls FW, 10bbls GW, 10bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 357sx(760cf-135bbls=2.13yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 81sx(112cf-20bbls=1.38yld) Type III cmt w/ 1% CaCl, .025 pps celloflake, & 0.2% FL-52. Dropped plug & displaced w/ 135bbls FW. Shut down. Bumped plug @ 14:37hrs 01/25/12. Circ. 50bbls cmt to surface. WOC.

PT 7" csg to 1500#/30min @ 22:45hrs on 01/25/12. Test - OK. Drilled w/ 6 1/4", tagged @ 3320' & DO cmt to 3380'. TD reached @ 7675' on 01/30/12. Circ. hole & RIH w/ 182jts, 4 1/2", 11 6#, L-80, LT&C csg set @ 7674'. RU to cmt. Pre-flushed w/ 140bbls mud w/ 35% N2, 10bbls of GW w/ 35% N2, 10bbls of FW. Pumped scavenger 9sx(28cf-5bbls=3.10yld) Premium lite HS FM, 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, & 1% FL-52. Tail w/ 300sx(594cf-106bbls=1.98yld) Premium lite HS FM, 0.25 pps celloflake. 0.3% CD-32, 6.25pps LCM-1 & 1% FL-52. Dropped plug & displaced w/ 119bbls FW. Bumped plug. Plug down @ 11:56hrs on 02/01/12. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 04:00hrs on 02/02/11. A

PT will be conducted by Completion Rig. Results &amp; TOC will appear on next report

**14. I hereby certify that the foregoing is true and correct.**

Signed

Marie E. Jaramillo

Title Staff Regulatory Tech.

Date 02/08/12

(This space for Federal or State Office use)

APPROVED BY

Title

**ACCEPTED FOR RECORD**

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

**FEB 10 2012****NMOC**

**FARMINGTON FIELD OFFICE**  
BY 

PC