

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Jun 19, 2008

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-045-22588
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-11125-34 / E-5317
7. Lease Name or Unit Agreement Name State Com
8. Well Number 42
9. OGRID Number 217817
10. Pool name or Wildcat Blanco Pictured Cliffs

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
P.O. Box 4289, Farmington, NM 87499-4289

4. Well Location
 Unit Letter **G** : **1660** feet from the **North** line and **1540** feet from the **East** line
 Section **32** Township **31N** Range **9W** NMPM **San Juan County**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
 6389' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The subject well was P&A'd on 1/20/2012 per the attached report.

Approved for plugging of wellbore only.
 Liability under bond is retained pending.
 Receipt of C-103 (Subsequent Report of Well Plugging) which may be found @ OCD web page under forms
www.emnrd.state.us/ocd

RCVD FEB 23 '12
 OIL CONS. DIV.
 DIST. 3

Spud Date: 3/27/1978 2/1978

PNR ONLY

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Crystal Tafoya TITLE Staff Regulatory Technician DATE 2/22/2012

Type or print name Crystal Tafoya E-mail address: crystal.tafoya@conocophillips.com PHONE: 505-326-9837

For State Use Only

APPROVED BY: Red Bell TITLE Deputy Oil & Gas Inspector, District #3 DATE 2/23/12
 Conditions of Approval (if any):

AV

A-PLUS WELL SERVICE, INC.

P.O. BOX 1979
Farmington, New Mexico 87499
505-325-2627 *fax: 505-325-1211

Conoco Phillips
State Com #42

January 20, 2012
Page 1 of 1

1660' FNL and 1540' FEL, Section 32, T-31-N, R-9-W
San Juan County, NM
Lease Number: B-11125-34 / E-5317
API #30-045-22588

Plug and Abandonment Report
Notified NMOCD and BLM on 1/17/12

Plug and Abandonment Summary:

Plug #1 with CIBP at 3106' mix and pump 17 sxs (20.06 cf) class B cement inside casing from 3106' to 2695' to cover the Picture Cliffs interval and Fruitland top.

Plug #2 mix and pump 13 sxs (15.34 cf) class B cement inside casing from 2010' to 1696' to cover the Kirtland and Ojo Alamo tops.

Plug #3 with CR at 527' mix and pump 31 sxs (36.58 cf) class B cement, 24 sxs (28.32 cf) in annulus, 2 sxs (2.36 cf), below cement retainer, 15 sxs (5.9 cf) above cement retainer TOC at 407' to cover the Nacimiento top.

Plug #4 mix and pump 63 sxs(74.34 cf) class B cement down casing and out annulus.

Plug #5 mix and pump 21 sxs(24.78 cf) class B cement and install P&A marker.

- 1/18/12 Rode rig and equipment to location. Check well pressures; tubing 0#, casing 100# and bradenhead 0#. Perform LO/TO. Blow tubing and casing down. SI well. SDFD.
- 1/19/12 Check well pressures: tubing 100#, casing 100# and bradenhead 0#. Attempt to blow well down, unable to. Pump 30 bbls fresh water down tubing to kill well. ND wellhead. Strip on wellhead and BOP, test. TOOH and tally 47 stands 1-1/4" EUE tubing with FN nipple and one tail joint. Round trip 2.80" gauge ring to 3120'. PU 3.5" wireline set CIBP and RIH; set at 3106'. Pressure test 3 1/2" casing to 800#. SI well. SDFD.
- 1/20/12 Open up well; no pressures. Test BOP. Establish circulation. Spot Plug #1 and #2. Perforate 3 squeeze holes at 562'. Establish rate into squeeze holes. PU 3.5" wireline set CR and RIH; set at 527'. Spot Plug #3. Perforate 3 squeeze holes at 221'. Establish circulation. ND BOP and dig out wellhead. Perform Hot Work Permit. Cut off wellhead. Install P & A. RD. MOL. SDFD.

Jimmy Morris, MVCI representative was on location.
John Durham, NMOCD representative was on location.