Office	State of I	New Mex	aco]	Form C-103
<u>District I</u> – (575) 393-6161	Energy, Minerals	and Natur	al Resources		August 1, 2011
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.			
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION			15-35315		
	11 S. First St., Ariesia, NM 88210 1220 South St. Francis Dr.		5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410	Rio Brazos Rd., Aztec, NM 87410		STATE FEE		
<u>District IV</u> – (505) 476-3460	Santa Fe	, NM 87:	505	6. State Oil & Gas Lease No.	
1220 S. St Francis Dr., Santa Fe, NM 87505				V-1509	
	CES AND REPORTS ON	IWEIIS		7. Lease Name or Unit Agree	ment Name
(DO NOT USE THIS FORM FOR PROPOS			G BACK TO A	Good Times P32-2410	ment Name
DIFFERENT RESERVOIR USE "APPLIC	CATION FOR PERMIT" (FORM	M C-101) FOI	R SUCH		
PROPOSALS.)	_	•		8. Well Number	
<u> </u>	Gas Well Other			01H	
2. Name of Operator				9. OGRID Number	
Encana Oil & Gas (USA) Inc.	·			282327	
3. Address of Operator				10. Pool name or Wildcat	
370 17 th Street, Suite 1700 Der	ver, CO 80202			South Bisti-Gallup	1
4. Well Location		•			
SHL: Unit Letter P: 990 feet	from the \underline{S} line and $\underline{330}$	feet from	the $\underline{\mathbf{E}}$ line		
BHL: Unit Letter M: 990 fee	et from the S line and 33	0 feet from	n the W line		
Section 32 Township 24N Ra	-		-		
Section 32 Township 2414 Ra	11. Elevation (Show wh				
	11. Elevation (Show wh	6615 GF	,		
12 Check	Appropriate Box to In			anort or Other Date	
12. Check	Appropriate Box to III	uicaie iva	ture of Notice, K	eport of Other Data	
NOTICE OF IN	TENTION TO:	1	SUB	SEQUENT REPORT OF	: •
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR					
TEMPORARILY ABANDON	CHANGE PLANS	Ħ l	COMMENCE DRI	<u>—</u>	
PULL OR ALTER CASING	MULTIPLE COMPL	H	CASING/CEMENT		
DOWNHOLE COMMINGLE	MOETH LE COMI L		CASINO/CEMEN		
OTHER:			OTHER:		
13. Describe proposed or comp	eted operations (Clearly			l give portinent detec including	agtimated data
13. Describe proposed of comp	leted operations. (Clearly	state an pe	ertinient detans, and	i give pertinent dates, including	esumated date
of starting any proposed we	-LA CEE DIHE 10 15 7	14 NIMAC	For Multiple Con	anlatiana. Attach wallhara diac	rmam of
of starting any proposed wo		14 NMAC.	For Multiple Con	npletions: Attach wellbore diag	gram of
of starting any proposed wo proposed completion or reco		14 NMAC.	For Multiple Con	npletions: Attach wellbore diag	gram of
proposed completion or reco	ompletion.		-		gram of
	ompletion.		-		gram of
proposed completion or reco	ompletion.	string on 02	2/17/12 and 02/18/	12. Gelled freshwater system.	
proposed completion or reconstruction. Set intermediate casing string on 02/ Hole diameter: 12.250", casing diameter.	ompletion. 17/12 and cement casing seter: 9.625", casing weigh	string on 02	2/17/12 and 02/18/ e <u>40# K55</u> STC. D	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2	<u>3763'</u>
proposed completion or reconstruction. Set intermediate casing string on 02/ Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the control of the co	ompletion. 17/12 and cement casing seter: 9.625", casing weigh	string on 02	2/17/12 and 02/18/ e <u>40# K55</u> STC. D	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2	<u>3763'</u>
proposed completion or reconstruction. Set intermediate casing string on 02/ Hole diameter: 12.250", casing diameter.	ompletion. 17/12 and cement casing seter: 9.625", casing weigh	string on 02	2/17/12 and 02/18/ e <u>40# K55</u> STC. D	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2	<u>3763'</u>
proposed completion or reconstruction. Set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from and BOC @ 3763'.	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD	string on 02 nt and grade /MD. Stage	2/17/12 and 02/18/ e <u>40# K55</u> STC. D e tool @ 1724' and	12. Gelled freshwater system. epth of 12.250" hole from 0 to 3 top of float collar @ 3704'. To	3763' OC @ surface
proposed completion or reconstruction of reconstruction of the set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the set of	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD	string on 02 at and grade /MD. Stage	2/17/12 and 02/18/e <u>40# K55</u> STC. De tool @ 1724' and	12. Gelled freshwater system. epth of 12.250" hole from 0 to 3 top of float collar @ 3704'. To	3763' OC @ surface 5 lb/sk LCM-1
proposed completion or reconstruction. Set intermediate casing string on 02/. Hole diameter: 12.250", casing diametry TVD/MD. Intermediate casing set from and BOC @ 3763'. Stage 1 pumped on 02/17/12: Lead: 3 + 8% bentonite + 0.4% sodium metas.	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD/ 390 sks Premiuim Lite FM silicate + 0.4% FL-52A.	string on 02 at and grade MD. Stage 1 Cement + Vield 2.13	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 1	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c	3763' DC @ surface 5 lb/sk LCM-1 tement + 1%
proposed completion or reconstruction of reconstruction of the set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the set of	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD/ 390 sks Premiuim Lite FM silicate + 0.4% FL-52A.	string on 02 at and grade MD. Stage 1 Cement + Vield 2.13	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 1	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c	3763' DC @ surface 5 lb/sk LCM-1 tement + 1%
proposed completion or reconstruction. Set intermediate casing string on 02/2. Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the diameter of th	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD/ 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Y flake + 0.2% FL-52A. Y	string on 02 at and grade/MD. Stage 1 Cement + 7 ield 2.13 c iield 1.38 c	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 uft/sk. Mixed at 14	12. Gelled freshwater system. epth of 12.250" hole from 0 to 3 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours.
proposed completion or reconstruction. Set intermediate casing string on 02/. Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the analysis of the set o	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD, 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Y flake + 0.2% FL-52A. Y	string on 02 at and grade/MD. Stage I Cement + Yield 2.13 c ield 1.38 c ent + 3% C	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 1/2 uft/sk. Mixed at 1/2 calcium Chloride +	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells 6.6ppg. 145 sks circ to surface. V	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours.
proposed completion or reconstruction. Set intermediate casing string on 02/2. Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the diameter of th	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD, 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Y flake + 0.2% FL-52A. Y	string on 02 at and grade/MD. Stage I Cement + Yield 2.13 c ield 1.38 c ent + 3% C	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 1/2 uft/sk. Mixed at 1/2 calcium Chloride +	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells 6.6ppg. 145 sks circ to surface. V	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours.
proposed completion or reconstruction. Set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the diameter of the d	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD, 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Y flake + 0.2% FL-52A. Y se Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2	at and grade/MD. Stage 1 Cement + 7 ield 2.13 c ield 1.38 c ent + 3% C	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and 3% Calcium Chlocuft/sk. Mixed at 19 uft/sk. Mixed at 14 Calcium Chloride + 15. Mixed at 12.1 pp	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c 4.6ppg. 145 sks circ to surface. V 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours.
proposed completion or reconstruction. Set intermediate casing string on 02/. Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the analysis of the set o	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD, 390 sks Premiuim Lite FM, silicate + 0.4% FL-52A. Yeld as Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2 on 02/19/12.Casing and	at and grade/MD. Stage 1 Cement + (ield 2.13 cield 1.38 cient + 3% Co.13 cuft/sk	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and 3% Calcium Chlocuft/sk. Mixed at 19 uft/sk. Mixed at 14 Calcium Chloride + 15. Mixed at 12.1 pp	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells 6.6ppg. 145 sks circ to surface. V 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
proposed completion or reconstruction. Set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the diameter of the d	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD, 390 sks Premiuim Lite FM, silicate + 0.4% FL-52A. Yeld as Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2 on 02/19/12.Casing and	at and grade/MD. Stage 1 Cement + (ield 2.13 cield 1.38 cient + 3% Co.13 cuft/sk	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and 3% Calcium Chlocuft/sk. Mixed at 19 uft/sk. Mixed at 14 Calcium Chloride + 15. Mixed at 12.1 pp	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c 4.6ppg. 145 sks circ to surface. V 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC	3763' DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
proposed completion or reconstruction. Set intermediate casing string on 02/Hole diameter: 12.250", casing diameter TVD/MD. Intermediate casing set from the diameter of the d	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD, 390 sks Premiuim Lite FM, silicate + 0.4% FL-52A. Yeld as Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2 on 02/19/12.Casing and	at and grade/MD. Stage 1 Cement + (ield 2.13 cield 1.38 cient + 3% Co.13 cuft/sk	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 uft/sk. Mixed at 14. Mixed at 12.1 ppd on 02/19/12. BO	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To pride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells. 6.6ppg. 145 sks circ to surface. Vel. 6ppg. 145 sks circ to surface. Vel. 87 sks circ to surface. WOC P pressure and casing pressure COLL MOR.	3763' DC @ surface 5 lb/sk LCM-1 ement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 1717
proposed completion or reconstruction. Set intermediate casing string on 02/2. Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the and BOC @ 3763". Stage 1 pumped on 02/17/12: Lead: 2 + 8% bentonite + 0.4% sodium meta: Calcium Chloride + 0.25 lbs/sk cellor Stage 2 pumped on 02/18/12: 358 sk bentonite + 0.4% sodium metasilicate. Started drilling out stage tool at 1724 psi for 30 minutes and 250 psi for 5 m. Spud Date: 02/09/12	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD/ 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Yellow flake + 0.2% FL-52A. Yellow flake + 0.4% FL-52A. Yield 2 on 02/19/12. Casing and minutes. No pressure drop	at and grade/MD. Stage If Cement + (ield 2.13 cield 1.38 cield 1.38 cient + 3% Cient +	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and 3% Calcium Chlocuft/sk. Mixed at 14 uft/sk. Mixed at 14 alcium Chloride + 15. Mixed at 12.1 ppd on 02/19/12. BO	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c. 6,6ppg. 145 sks circ to surface. V. 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure PCIII HORS. DIST. 2	3763.2 DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
proposed completion or reconstruction of the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter of the diameter: 12.250", casing diameter and BOC @ 3763". Stage 1 pumped on 02/17/12: Lead: 2+8% bentonite + 0.4% sodium metas: Calcium Chloride + 0.25 lbs/sk cello Stage 2 pumped on 02/18/12: 358 sk bentonite + 0.4% sodium metasilicate of the diameter o	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Yelake + 0.2% FL-52A. Yelake + 0.4% FL-52A. Yield 2 on 02/19/12. Casing and minutes. No pressure drop	of tand grade of the string on 02 and and grade of the string on 02 and	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date:	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells flake + 1.6 ppg. 145 sks circ to surface. WOC 9.87 sks circ to surface. WOC P pressure and casing pressure Pressure and casing pressure DIST. Colling Casing reports with	3763.2 DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
proposed completion or reconstruction. Set intermediate casing string on 02/2. Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the and BOC @ 3763". Stage 1 pumped on 02/17/12: Lead: 2 + 8% bentonite + 0.4% sodium meta: Calcium Chloride + 0.25 lbs/sk cellor Stage 2 pumped on 02/18/12: 358 sk bentonite + 0.4% sodium metasilicate. Started drilling out stage tool at 1724 psi for 30 minutes and 250 psi for 5 m. Spud Date: 02/09/12	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Yelake + 0.2% FL-52A. Yelake + 0.4% FL-52A. Yield 2 on 02/19/12. Casing and minutes. No pressure drop	of tand grade of the string on 02 and and grade of the string on 02 and	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date:	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells flake + 1.6 ppg. 145 sks circ to surface. WOC 9.87 sks circ to surface. WOC P pressure and casing pressure Pressure and casing pressure DIST. Colling Casing reports with	3763.2 DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
proposed completion or reconstruction of the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the diameter of the diameter: 12.250", casing diameter and BOC @ 3763". Stage 1 pumped on 02/17/12: Lead: 2+8% bentonite + 0.4% sodium metas: Calcium Chloride + 0.25 lbs/sk cello Stage 2 pumped on 02/18/12: 358 sk bentonite + 0.4% sodium metasilicate of the diameter o	ompletion. 17/12 and cement casing seter: 9.625", casing weighom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Yelake + 0.2% FL-52A. Yelake + 0.4% FL-52A. Yield 2 on 02/19/12. Casing and minutes. No pressure drop	of tand grade of the string on 02 and and grade of the string on 02 and	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date:	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III cells flake + 1.6 ppg. 145 sks circ to surface. WOC 9.87 sks circ to surface. WOC P pressure and casing pressure Pressure and casing pressure DIST. Colling Casing reports with	3763.2 DC @ surface 5 lb/sk LCM-1 tement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500
Proposed completion or reconstruction of reconstruction of the complete casing string on 02/14 Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter casing set from the casing set fr	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD/ 390 sks Premiuim Lite FM silicate + 0.4% FL-52A. Y flake + 0.2% FL-52A. Y flake + 0.4% FL-52A. Yield 2 on 02/19/12. Casing and minutes. No pressure drop	of tring on 02 Int and grade MD. Stage I Cement + Yield 2.13 of the distance of the distan	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlouft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date:	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c 6.6ppg. 145 sks circ to surface. V 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure PCLID HORS 1 DIST. 3 Ciling Casing reports with e and belief.	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of reconstruction of the complete casing string on 02/14 Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter casing set from the casing set from the casing set from the set of the casing set from the casing set from the casing set from the casing set from the case of the case o	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2. on 02/19/12.Casing and minutes. No pressure drop. 15.7.14 D which above is true and complete.	at and grade/MD. Stage If Cement + Cield 2.13 Cield 1.38 c ent + 3% C 2.13 cuft/sk BOP teste Rig Relea requires e to the bes LE Regular	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 Calcium Chloride +	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. TO oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III collection. See the collection of the collection. O.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure of the collection of the co	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of reconstruction of the complete casing string on 02/14 Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter casing set from the casing set fr	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2. on 02/19/12.Casing and minutes. No pressure drop. 15.7.14 D which above is true and complete.	at and grade/MD. Stage If Cement + Cield 2.13 Cield 1.38 c ent + 3% C 2.13 cuft/sk BOP teste Rig Relea requires e to the bes LE Regular	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlouft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date:	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III c 6.6ppg. 145 sks circ to surface. V 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure PCLID HORS 1 DIST. 3 Ciling Casing reports with e and belief.	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of the set intermediate casing string on 02/Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the set of	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2. on 02/19/12.Casing and minutes. No pressure drop. 15.7.14 D which above is true and complete.	at and grade/MD. Stage If Cement + Cield 2.13 Cield 1.38 c ent + 3% C 2.13 cuft/sk BOP teste Rig Relea requires e to the bes LE Regular	2/17/12 and 02/18/e 40# K55 STC. De tool @ 1724' and -3% Calcium Chlocuft/sk. Mixed at 14 Calcium Chloride +	12. Gelled freshwater system. epth of 12.250" hole from 0 to 2 top of float collar @ 3704'. TO oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III collection. See the collection of the collection. O.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure of the collection of the co	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of reconstruction of the complete casing string on 02/14 Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the casing set from the diameter casing set from the casing set from the casing set from the set of the casing set from the casing set from the casing set from the casing set from the case of the case o	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2. on 02/19/12.Casing and minutes. No pressure drop. 15.7.14 D which above is true and complete.	at and grade/MD. Stage If Cement + Cield 2.13 Cield 1.38 c ent + 3% C 2.13 cuft/sk BOP teste Rig Relea Fequires to the bes E Regular brenda.lin	2/17/12 and 02/18/ e 40# K55 STC. De tool @ 1724' and - 3% Calcium Chloruft/sk. Mixed at 14 Calcium Chloride + Calcium Chloride	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To oride + 0.25 lbs/sk cello flake + 2.1 ppg. Tail:100 sks Type III collection. 6.6ppg. 145 sks circ to surface. 0.25 lbs/sk cello flake + 5lb/sk g. 87 sks circ to surface. WOC P pressure and casing pressure PCLICHOS. DIST. 3 Casing reports with and belief. DATE 03/05/1 PHONE: 720-876-3989	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of reconstruction of the complete casing string on 02/14 Hole diameter: 12.250", casing diamed TVD/MD. Intermediate casing set from the diameter: 12.250", casing diamed TVD/MD. Intermediate casing set from the diameter: 12.250", casing diamed TVD/MD. Intermediate casing set from the diameter of	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2 c on 02/19/12.Casing and minutes. No pressure drop 15.7.14 D which above is true and complete.	of tand grade MD. Stage MCement + Gield 2.13 cield 1.38 cent + 3%	2/17/12 and 02/18/ e 40# K55 STC. De tool @ 1724' and - 3% Calcium Chloruft/sk. Mixed at 12 uft/sk. Mixed at 14 Calcium Chloride + t. Mixed at 12.1 pp d on 02/19/12. BO ase Date: tory Advisor ster@encana.com	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To 1 top of flo	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117
Proposed completion or reconstruction of the set intermediate casing string on 02/Hole diameter: 12.250", casing diam TVD/MD. Intermediate casing set from the set of	ompletion. 17/12 and cement casing seter: 9.625", casing weightom surface to 3763' TVD. 390 sks Premiuim Lite FM. silicate + 0.4% FL-52A. Y. flake + 0.2% FL-52A. Y. s Premiuim Lite FM Ceme + 0.4% FL-52A. Yield 2. on 02/19/12.Casing and minutes. No pressure drop. 15.7.14 D which above is true and complete.	of tand grade MD. Stage MCement + Gield 2.13 cield 1.38 cent + 3%	2/17/12 and 02/18/ e 40# K55 STC. De tool @ 1724' and - 3% Calcium Chloruft/sk. Mixed at 14 Calcium Chloride + Calcium Chloride	12. Gelled freshwater system. epth of 12.250" hole from 0 to 1 top of float collar @ 3704'. To 1 top of flo	3763' DC @ surface 5 lb/sk LCM-1 sement + 1% WOC 4 hours. LCM-1 + 8% 18.5 hours. held at 1500 3117