Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMD No. 1004-0135 Expires July 31, 1996

5.	Lease	Sefial	No.

NMSF/- (079366
----------	--------

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name		
	ICATE – Other instruct	ions on revers) side	ĺ	A/Agreement, Name and/or Note NMNM 78406C	0.
1. Type of Well				0 Well Name	and No.	
Oil Well X Gas Well Other 2. Name of Operator			8. Well Name and No. Rincon Unit #403			
•	flike Pippin LLC (Agent)	-	777	9. API Well N		
3a. Address	Phóne Nó (include	Phóne Nó. (include area code) 30-039-27814				
		05/327-4573/10 I		10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		1/n 1/2 1/2 2 60		Blanco Mesaverde & Basin Dakota		
350' FSL 475' FEL (P) Sec. 21 T27N R06W				11. County or Parish, State Rio Arriba County, New Mexico		
12. CHECK APPROPRIATE BOX	K(ES) TO INDICATE NATUR	E OF NOTICE, RE	PORT, OR OT	HER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Acidize	Deepen Fracture Treat	Reclamation		Water Shut-Off Well Integrity	
X Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily		Other SPUD & SURFACE & INTER	₹
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Water Dispo		CASINGS	
Cemented sg w/90 sx (flocele, &-2% econolite in 0.25#/sx flocele nixed (100 psi in 5 min 2 Drilled 8-3/4" hold to 27/2 PRB Type II; cmt w/2% (12.5 gps & yield of 2.24	2 12:00 PM on 3/31/05. [2 163 cf) PRB Type 11 cm mixed @ 13.5 ppg w/yield [2 15.6 ppg & yield of 1.1 26'. TIH w/7" 20# J-55 L Calseal, 2% Econolite, 6% cf/sx. Tail w/135 sx (244 c, 0.25#/sx Flocele mixed	Drilled to 427'. To tw/6% salt, 0.3°d of 1.81 cuft/sx 8 cf/sx. Circ. 20°C Csg & set 6°C Salt, 0.3% Verify PRB Type I	"IH w/9-5/8" 3 % Versaset, 2 . Tail w/100) bbls cmt to) 2726' on 4/5 rsaset, 5#/sx I cmt w/2% 0	32.3# H-40 L 2% Calseal, sx (118 cf) s pit. Pressur 3/05. Ceme gilsonite, 0.: Calseal, 2%	T&C csg & set @ 41 5#/sx gilsonite, 0.25# standard cmt w/2% Ca e test csg to 500 psi. ented csg w/350 sx (73 25#/sx Flocele mixed Econolite, 6% Salt, 0.	t/sx acl2, Lost 84 cf)
14. I hereby certify that the foregoing	is true and correct		 		***	
Name (Printed/Typed) Mike	**		r. Engr. (Age	ent)		
Signature Date			April 5, 2005			
11(1)(1)	THIS SPACE	FOR FEDERAL OR			PIED FUR RECURD	ly.
Approved by	I.IIO OF AUE	Title		Date		
				1 1	ਪੁਰਤ 1 3 2005	<u> </u>
Conditions of approval, if any, are attached. Approval of this notice does not warrancertify that the applicant holds legal or equitable title to those rights in the subject I which would entitle the applicant to conduct operations thereon.				FARA	ningium field office	
Title 18 U.S.C. Section 1001, makes it fraudulent statements or representations			any department or	r agency of the U	nited States any false, fictitious	s or

(Instructions on reverse)