This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

| Operator BR | | | | | Lease | Name H | ANKS | | | Well No14E |
|--------------------------------------|-------------------------|-------------------------|----------|------------------------|---|------------|-------------------------|----------------------------|--------------------------------------|----------------------------|
| Location of We | ll: Unit | Letter | 0 : | Sec | 12 | Twp02 | 27N | Rge | 010W API | # 30-045-24479 |
| | Name of Reservoir or Po | | | ol Type of Prod | | | | Method of Prod | | Prod Medium |
| Upper Completion | PC | | | | Gas | | | Artific | ial Lift | Tubing |
| Lower Completion | DK | | | | Gas | | | Flow | | Tubing |
| | | | | Pre | -Flow S | hut-In Pre | ssure | Data | | |
| Upper Completion | | | | | Length of Time Shut-In 96 hours | | | SI Pres | ss. PSIG | Stabilized?(Yes or No) Yes |
| Lower Hour, Date, Shut-In Completion | | | | Length of Time Shut-In | | | SI Pres | ss. PSIG | Stabilized?(Yes or No) | |
| 5/10/2012 | | | | 200 hours | | | | 16.7 Yes | | |
| | | | | | Flo | w Test No | . 1 | | | |
| Commenced a | at: | 5 | /14/2012 | | | Zone | Produ | ucing (Uppe | r or Lower): UP | PER |
| Time (date/time) | | Lapsed Time Since* Uppe | | PRES er zone | | | Prod Zone emperature | Remarks | | |
| 5/15/2012 8.00.00 AM | | | 32 | | 25 | 16 7 | | 65 | producing upper zone with compressor | |
| 5/16/2012 8:00:00 AM | | | 56 | | 15 | 17 | | 60 | comp. running, flow rate @45mcf/d | |
| 5/17/2012 8:00·00 AM | | | 80 | | 12 | 17 | | 60 | comp running , py = 40mcf | |
| 5/18/2012 8:00:00 AM 104 | | 104 | | 10 | 17 | | 60 | comp. running , py 37mcf/d | | |
| Production rate | during | test | | | | | | , | | |
| Oil: | BPOD | Based or | n: | Bbls | s. In | F | irs | | Grav. | GOR |
| Gas | | MCF | PD; Test | thru (Orif | ice or M | leter) | | | | |
| | | | | nn:- | i_Tact S | hut-In Dro | eeuro | Data | | |
| Upper Completion | Hour, Date, Shut-In | | | IAIIC | lid-Test Shut-In Pressure Dat Length of Time Shut-In | | | | ss. PSIG | Stabilized?(Yes or No) |
| Lower Completion | Hour, Date, Shut-In | | | | Length of Time Shut-In | | | SI Pres | ss PSIG | Stabilized?(Yes or No) |

(Continue on reverse side)

RCVD JUN 5 '12 OIL CONS. DIV. DIST. 3

Page 2

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

| Commenced at: | | | Zone Pro | oducing (Uppe | r or Lower) | | | | |
|-------------------------|----------------------------------|------------------|--------------|--|---------------------|------------|--|--|--|
| Time | Lapsed Time Since* | | SURE | Prod Zone | | Remarks | | | |
| (date/time) | Since | Upper zone | Lower zone | Temperature | | Remarks | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | , | | | | | | | | |
| Dil:BPOD |) Based on: | Bbls. In | Hrs. | | Grav. | GOR | | | |
| ∋as | MCFPD; Test th | ru (Orifice or M | eter) | | • | | | | |
| | | | | | | , | | | |
| Remarks: | | | | | | | | | |
| | | | | | | | | | |
| | | | | AATTOO AA | | | | | |
| hereby certify that the | e information herein co | ontained is true | and complete | to the best of | my knowledge |) . | | | |
| Approved: | 6/7 | 20 /2 | Opera | tor: BR | | | | | |
| New Mexico Oil Co | nservation Division | | Ву: | Russell Elliot | t | | | | |
| By: Ball | M | | Title: | Title: Multi-Skilled Operator | | | | | |
| Depui | ty Oil & Gas Insp District #3 | ector, | Date: | Date: Monday, June 04, 2012 | | | | | |
| | | | | | - ·, · - | | | | |

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- $6 \qquad Flow \ Test \ No \ 2 \ shall \ be \ conducted \ even though \ no \ leak \ was \ indicated \ during \ Flow \ Test \ No \ 1 \ Procedure for \ Flow \ Test \ No \ 2 \ is to be the same as for Flow \ Test \ No \ 1 \ except that the previously produced \ zone \ shall \ remain \ shut-in \ while the \ zone \ which \ was \ previously \ shut-in \ is \ produced$
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-inmute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

5 Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3 above