

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR MAY 02 20 2

FORM APPROVED

OWR No	1004-0137
Expires: J	uly 31, 2010

BUREAU OF LAND MANAGEMENT Farmington Field			Expires: July 31, 2010					
Bureau of Land Man			5'llease Scrial No Agente: SF-079296					
			6 If Indian, Allottee or Tribe Name					
	this form for proposals t			,	, manan, money or manager			
	well. Use Form 3160-3 (A							
SU	IBMIT IN TRIPLICATE - Other ins	tructions c	on page 2		7 If Unit of CA/Agreement, Name and/or No			
1 Type of Well								
Oil Well	X Gas Well Other				8. Well Name and No			
2 Name of Operator		FEDERAL 11M 9 API Well No.						
ConocoPhillips Company		30-039-30673						
3a. Address 3b Phone No. (include area code)		10 Field and Pool or Exploratory Area						
PO Box 4289, Farmington, NM 87499 (505) 326-9700			Blanco MV/Basin Mancos/Basin DK					
4. Location of Well (Footage, Sec., T, R		-I Coo	22 TOOM DOW	,	11. Country or Parish, State	Maria	Navios	
Surface Unit I (N	IESE), 2445' FSL & 785' FE	EL, Sec.	23, 120W, ROW	1	Rio Arriba ,	MeM	Mexico	
12 CHECK 3	THE APPROPRIATE BOX(ES)	TO IND	CATE NATURE (OF NO	TICE REPORT OR OTHE	R DATA		
	1.27.1.1.1.0.1.1.1.1.2.207.(20)							
	YPE OF SUBMISSION TYPE OF AC							
Notice of Intent	Acidize	Deep			roduction (Start/Resume)	=	Shut-Off	
F	Alter Casing		ure Treat		eclamation		ntegrity	
X Subsequent Report	Casing Repair	<u></u> .	Construction	=	lecomplete	X Other	Casing Report	
	Change Plans Convert to Injection		and Abandon	=	emporarily Abandon			
Final Abandonment Notice 13. Describe Proposed or Completed Op		Plug			Vater Disposal		6	
following completion of the involv	ork will be performed or provide the I ed operations. If the operation results Abandonment Notices must be filed or final inspection.)	in a multip	le completion or recon	npletion	in a new interval, a Form 3160-4	must be file	d once	
				RCVD MAY 14'12				
PLEASE SEE ATTACHED.			OIL CONS. DIV.					
				1	DIST. 3			
					!	له ۱۱ ساله ۱۲		
PT will be conducted by	y Completion Rig. Results 8	& TOC v	vill appear on ne	xt rep	ort. ACCEPTE	ED FOR	RECORD	
					MA	Y 0 7 2	012	
					FARMINGT BY S G	ron fiel	D OFFICE	
		**	·					
14 I hereby certify that the foregoing is	true and correct. Name (Printed/Typ	ed)						
	DENISE JOURNEY		Title REGULAT		EGULATORY TECHNICIAN	LATORY TECHNICIAN		
Signature Mill	owney		5/1/2012 Date					
	THIS SPACE FO	R FEDI	ERAL OR STAT	E OFI	ICE USE			
Approved by								
			The state of the s	la.		Data		
Conditions of approval, if any, are attac	hed Approval of this notice does not	warrant or	certify	16		Date		
that the applicant holds legal or equitable entitle the applicant to conduct operation	le title to those rights in the subject leans thereon	ase which v	vould Of	fice				
Title 18 U S C Section 1001 and Title	43 U.S.C. Section 1212, make it a crip	ne for any p	erson knowingly and	willfully	to make to any department or age	ncy of the U	nited States any	

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

FEDERAL 11M 30-039-30673 ConocoPhillips Blanco MV/Basin Mancos/Basin DK

4/14/12 MIRU AWS 711.

4/15/12 PT 9 5/8" casing to 600#/30 min. Test OK. TIH w/ 8 3/4" bit, tag cmt @ 320' & DO. Drilled ahead with 8 3/4" bit to 4,584' – Inter TD reached 4/18/12. **4/19/12** Circ. hole. TIH w/ 107 jts (29 jts 23# LT&C & 78 jts 20# ST&C) 7", J-55 casing, set @ 4,560'.

4/21/12 RU to cmt. Pre-flush w/ 10 bbls FW & 10 bbls GW spacer. Pumped scavenger 19 sx (57cf-10bbls=3.02 yld) Prem Lite w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Lead w/ 529 sx (1127cf-200bbls=2.13 yld) Prem Lite w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Tail w/ 107 sx (148cf-26bbls=1.38 yld) Type III cmt., w/ 1% CACL2, .25 pps cello-flake, & 0.2% FL-52. Drop plug & displaced w/ 183 bbls FW. Bump plug. Circ. 62 bbls cmt to surface. RD cmt. WOC.

4/22/12 PT 7" casing to 1500#/30 min. Test OK. TIH w/ 6_½" bit, tag cmt @ 4515' & DO. Drilled ahead w/ 6 ½" bit to 7,318' (TD) – TD reached 4/26/12.

4/27/12 TIH w/ 175 jts., 4½", 11.6#, L-80 casing, set @ 7,315'. RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger, 9 sx (27cf-5bbls=3.02 yld) Prem Lite w/ 0.3% CD-32, .25 pps cello-flake, 1% FL-52, & 6.25 pps LCM-1. Tail w/ 196 sx (388cf-69bbls=1.98 yld) Prem Lite w/ 0.3% CD-32, .25 pps cello-flake, 1% FL-52, & 6.25 pps LCM-1. Drop plug & displaced w/ 113 bbls FW (1st 10 bbls with sugar water). Bump plug w/ 1330#. Plug down @ 13:34 hrs on 4/28/12. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 06:00 hrs on 4/29/12.

