## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO 1004-0135 Expires: July 31, 2010

Lease Serial No NMSF078156A

SUNDRY N	IOTICES AN	D REPORTS	ON WELLS
Do not use this	form for proj	posals to drill	or to re-enter an

6. If Indian, Allottee or Tribe Name

	030 form 0.00 0 (Al D)	101 00011 )	or oposurs.					
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No NMNM89374			
1. Type of Well					8. Well Name and No.			
☐ Oil Well ☐ Gas Well ☐ Other					CISCO COM 9	<del></del>		
2. Name of Operator Contact: ALIPH REENA DUGAN PRODUCTION CORPORATION all: aliph.reena@duganproduction.com					9 API Well No. 30-045-28805-00-S1			
3a. Address 3b Phone No. Ph. 505-32			o. (include area code)		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL			
FARMINGTON, NM 87499			23-1021		BASIN FROI	ILAND C	OAL	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, and State			
Sec 34 T26N R13W SWSW ( 36.439484 N Lat, 108.211990			SAN JUAN COUNTY, NM					
12. CHECK APP	ROPRIATE BOX(ES) TO	NDICATE	E NATURE OF N	IOTICE, RE	PORT, OR OTH	HER DAT	ГΑ	
TYPE OF SUBMISSION			. TYPE OF					
Notice of Intent	☐ Acidize	Dec 🗖 Dec	pen cture Treat	Production	on (Start/Resume)	. o n	Vater Shut-Off	
· · · · · · · · · · · · · · · · · · ·	☐ Alter Casing	□ Frac	cture Treat	☐ Reclamat	ion	🖸 W	Vell Integrity	
☐ Subsequent Report	Casing Repair		v Construction	_	ete	_O	ther	
Final Abandonment Notice	Change Plans	🛛 Plug	g and Abandon		rily Abandon	•		
	Convert to Injection	· D Plug	g Back	□ Water Di	sposal			
testing has been completed Final Al determined that the site is ready for for the Operator plans to plug the we 1) Set 4-1/2" bridge plug @ +	inal inspection.) Il as described.		, 17	ing reclamation	RCVD OIL (	ed; and the JUN 4: JUNS. D JST. 3	12	
Spot and balance inside p	lug with 25 sks Class B nea	t cement (S	910'-1210')	•				
<ol> <li>Spot and balance inside p</li> </ol>	l <del>ug with 25 sks Class B ne</del> a	t-cement-(2	<del>?70'-574</del> ')			4	Cas in	
4) Perforate @ 170'. Circulat	ı	Pluz f where	<del>270'-574</del> ') irom 242' - Su Cement is 1	or praso	de dourside ar.	ru v	· · · · · · · · · · · · · · · · · · ·	
5) Cut wellhead. Install dry h	iole marker as required.							
	(1)* ( )		`					
14. I hereby certify that the foregoing is	true and approat							
Cou	Electronic Submission #13 For DUGAN PRODUCT mmitted to AFMSS for proces	ION CORP	DRÁTION, sent to	the Farmington	oń			
Name (Printed/Typed) ALIPH RE	•	g 2, 0		CTION ENGI	•			
Signature (Electronic S			Date 05/25/20		(1)			
	THIS SPACE FOR	FEDERA	L OR STATE C	FFICE USI	<b>E</b>			
Approved By STEPHEN MASON			TitlePETROLEU	JM ENGINEE	i <i>a</i>	- ;	Date 06/01/2012	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Farmington	. · . on				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE

6251 COLLEGE BLVD. FARMINGTON, NEW MEXICO 87402

Attachment to notice of Intention to Abandon:

Re: Permanent Abandonment

Well: 91 Cisco Com

## **CONDITIONS OF APPROVAL**

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 564-7750.
- 3. The following modifications to your plugging program are to be made:
- a) Place the Kirtland/Ojo Alamo/Surface plug from 242' to surface inside and outside the 4 ½" casing where cement is not present.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.