# RECEIVED

Form 3160-5

## UNITED STATES NTERIOR

JUN 15 2012

FORM APPROVED OMB No 1004-0137 Expires. July 31, 2010

	Olill ED Billing
igust 2007)	DEPARTMENT OF THE IN
	DIMPATIONI AND MANIA

BUREAU OF LAND MANAGEMEN Farmington Field Office 5. Lease Serial No. 187 NOTICES AND REPORTS BUTGEL LAND Management 189-IND-58

Do not use this form for propos abandoned well. Use Form 3160-	6. If Indian, Allottee or Tribe Name NAVAJO	
SUBMIT IN TRIPLICATE -	7. If Unit of CA/Agreement, Name and/or No.	
1. Type of Well  Oil Well  Gas Well  Other  2. Name of Operator VALLECITO GAS CO, LLC		8 Well Name and No. NAVAJO 18#3 9. API Well No. 30-045-202990
3a. Address C/O TIFFANY GAS CO, LLC PO BOX 50, FARMINGTON, NM 87499-0050	3b. Phone No (include area code) 505-325-1701	10. Field and Pool or Exploratory Area HOGBACK DAKOTA
4. Location of Well (Footage, Sec., T, R, M., or Survey Descr 1155' FNL & 2475' FEL, SECTION 18, T29N-16W	iption)	11. Country or Parish, State SAN JUAN COUNTY, NEW MEXICO

TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
	Change Plans	Plug and Abandon	Temporarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	

the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

VALLECITO GAS, LLC PLUGGED AND ABANDONED SUBJECT WELL PER THE ATTACHED:

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

RCVD JUN 20'12 OIL CONS. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) JIM HICKS Titl	e CONTRACTED BY TIFFANY GAS	CO, AGENT FOR VALLECITO GAS
Signature Dat	e 06/08/2012	
THIS SPACE FOR FEDERA	L OR STATE OFFICE USE	ASSEPTED FOR RECORD
Approved by	Title	Date JUN 1 8 2012
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon	Office	PAPERAGION PIELDOFFICE

(Instructions on page 2)

## A-PLUS WELL SERVICE, INC.

P.O. BOX 1979 Farmington, New Mexico 87499 505-325-2627 \*fax: 505-325-1211

Vallecito Gas Co., LLC Navajo 18 #3

May 10, 2012 Page 1 of 1

1155' FNL and 2475' FEL, Section 18, T-29-N, R-16-W San Juan County, NM Lease Number: I-89-IND-58 API #30-045-202990

Plug and Abandonment Report Notified NMOCD and BLM

### Plug and Abandonment Summary:

Plug #1 pump 78 sxs (92.04 cf) Class B cement inside casing from 824' to 150' to cover the Dakota interval.

Plug #2 pump 28 sxs (34.22 cf) Class B cement inside casing from 100' to surface.

#### Plugging Work Details:

- 5/9/12 MOL. RU cement equipment. Open up well; no pressures. RU pump and load 4 ½" casing with .5 bbls. Establish rate of 1.5 bbls at 1100 psi. Spot Plug #1. PUH and WOC. Well was flowing gray water out 4.5" casing. RU A-Plus Wireline with 1 1/8" weight bar. TIH and attempt to tag cement. Shut in casing back in wait on orders. V. Ventillie, NNBLM, approved procedure change. Displace cement back down to 150' with fresh water. SI well and WOC overnight. SDFD.
- 5/10/12 Travel to location. Open up well. TIH and tag cement at 114'. POH and wait on orders. V. Ventillie, NN BLM, approved tag and procedure change. Perforate 3 bi-wire squeeze holes at 114'. RU pump to casing and load with ½ bbl water. Pressure up to 1500 psi then bled down to 750 psi. Unable to establish rate. V. Ventillie, NN BLM and B. Powell, NMOCD, approved procedure change. Perforate 3 bi-wire squeeze holes at 50'. RU pump to casing and pump 25 bbls at 3.5 bbl bpm at 250 psi; no circulation. PU poly pipe and RIH to 100'. Spot Plug #2. Install P&A marker. RD & MOL.

Jim Hicks, Hicks Oil & Gas representative, was on location. Valjean Ventillie, NN BLM representative, was on location.