Form 3160-5 (March 2012)

UNITED STATES DEPARTMENT OF THE INTERIOR

RECEIVEL

FORM APPROVED OMB No 1004-0137

uu oa **20**12

Expires October 31, 2014

BUR	EAU OF LAND MAN	IAGEMENT	JOL	00 20.	5. Lease Serial No NMSF078875		
SUNDRY N	NOTICES AND REPO	ORTS ON WEL	_E s rmingt	on Field (6. If Indian, Allotte	e or Tribe N	Vame
abandoned well.	Use Form 3160-3 (A	(PD) for such	proposal	s.	,		•
SUBMIT IN TRIPLICATE – Other instructions on page 2.					7 If Unit of CA/Agreement, Name and/or No. Canyon Largo Unit		
1. Type of Well Oil Well Gas Well Other					8 Well Name and No. Canyon Largo Unit #506		
2 Name of Operator Huntington Energy, L.L.C.					9. API Well No 30-039-31098		
3a Address 908 N W. 71st St Oklahoma City, OK 73116	3b Phone No (inc	lude area cod	lude area code) 10. Field and Pool or Explora Basın Dakota			ory Area	
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec. 33, T2SN-R6W, NWNW 718' FNL & 976' FWL 36 361690 N Lat, 107 477950 W Lon					11 County or Parish, State Rio Arriba Co., NM		
- 12 CHEC	CK THE APPROPRIATE BO	X(ES) TO INDICA	TE NATURE	OF NOTIC	E, REPORT OR OT	HER DAT	A
TYPE OF SUBMISSION TYPE OF ACT					ION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture T	`reat	_	ection (Start/Resume)	□ v	Vater Shut-Off Vell Integrity
✓ Subsequent Report	Casing Repair Change Plans	New Cons Plug and A		_	nplete orarily Abandon	☑ c	Other Completion
Final Abandonment Notice	Convert to Injection	Plug Back		☐ Water	er Disposal		
Completion Detail for the above refe	renced well is attached.					OIL CO	UL 12'12 NS. DIV. ST. 3
					20000	UL 1 0	2012
14 I hereby certify that the foregoing is tr Catherine Smith	ue and correct Name (Printed		e Regulator	·			
Signature Catherine	Smil		e 06/28/201			·	
	THIS SPACE I	OR FEDERAL	OR STA	TE OFF	CE USE		
Approved by	2						
Conditions of approval, if any, are attached that the applicant holds legal or equitable trentitle the applicant to conduct operations to	tle to those rights in the subject		Title Office		· · · · · · · · · · · · · · · · · · ·	Date	
Title 18 U.S C Section 1001 and Title 43 t	J.S C Section 1212, make it a	crime for any person l	knowingly and	willfully to	make to any departme	nt or agency	of the United States any false

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Huntington Energy, L.L.C.

908 NW 71st Street
Oklahoma City, OK 73116
(405) 840-9876 & Fax # (405) 840-2011

Canyon Largo Unit #506 Rio Arriba Co., New Mexico API: 3003931098

COMPLETION SUNDRY:

6/14/12: NU FRAC VALVE AND FRAC Y. PRESSURE TEST CSG AND FRAC EQUIPMENT TO 5000 PSI FOR 30 MINS. HELD.

6/15/12: MOVE IN BASIN AND RIG UP. PERF WELL 7022-7034', 7012-7016', 6982-6992', 6946-6952', 6870-6882'. 4 SHOTS PERF FOOT, TOTAL OF 176 HOLES. SHUT WELL IN AND RIG DOWN BASIN.✓

6/19/12: MOVE IN HALLIBURTON AND RIG UP FRAC EQUIPMENT. PRESSURE LINES TO 5000 PSI. SAFETY MEETING. PUMP 2500 GALS OF 15% HCL ACID. PUMPED 1614 MCF FOR COOL DOWN. PUMPED 29,870 GALS OF 15 CP DELTA 200 AT AN AVG RATE OF 13.2 BPM AND AVG WHTP OF 4,689 PSI. PUMP 68.736 GALS OF 70Q 15 CP DELTA 200 AT AN AVG RATE OF 33.4 BPM AND AN AVG QUALITY OF 67%. PUMP 605.4 SACKS OF 20/40 PR AND 500.2 SACKS CRC PER WT SLIPS W/ A MAX BH SAND CONCENTRATION OF 4.6 LB/GAL. A 25% PAD WAS PUMPED. MAX PSI REACHED WAS 4858 PSI. FRAC GRADIENT AT END WAS .80 PSI/FT. ISIP – 4095 PSI, 5 MINS – 3328 PSI, 10 MIN – 3290 PSI, 15 MIN – 3259 PSI. RIG UP FLOW BACK LINES TO FLOW BACK TANK. WELL ON 20/64" CHOKE AT 6PM. SHUT WELL IN.

6/25/12: MOVE IN RIG UP. CSG 2300 PSI. BLEED DOWN WELL. KILL WELL W/20 BBLS OF 2% KCL WATER. NIPPLE DOWN FRAC STACK. NU BOP. KILL WELL W/ 20 BBLS. PICK UP 2 3/8" TBG. KILL TBG 4 TIMES W/10 BBLS EACH TIME. PICK UP TOTAL OF 129 JTS. SHUT WELL IN FOR NIGHT.

6/26/12: CSG AND TBG 1300 PSI. BLEED WELL DOWN. PICK UP 2 3/8" TAG @ 7010'. CLEAN OUT TO 7100'. 66' OF RAT HOLE, CIRC HOLE CLEAN. LAY DOWN 7 JTS. TBG NC, SN, 213 JTS 2 3/8", LAND TBG @ 6879'. ND BOP AND NU WH. RIG UP SWAB EQUIPMENT. MADE 2 RUNS AND TBG STARTED FLOWING. FLOWING @ 200 PSI ON 20/64" CHOKE. CSG 40 PSI. TURN WELL OVER TO FLOWBACK HANDS. FLOWBACK WELL. ✓

* Include Tubing weight a grade on all Future Surdrijs