RECEIVED

Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR**JUL 05 2012**BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

Farmington Field Office SUNDRY NOTICES AND REPORTS @Naw EULand Managemen		5. Lease Serial No SF-078771
Do not use this form for proposals to drill or to re-enter an		6. If Indian, Allottee or Tribe Name
abandoned well. Use Form 3160-3 (APD) for such proposals.		
SUBMIT IN TRIPLICATE – Other instructions on page 2.		7. If Unit of CA/Agreement, Name and/or No. Rosa Unit
1. Type of Well		
Oil Well Gas Well Other		8. Well Name and No. Rosa Unit #215A
2 Name of Operator WPX Energy Production, LLC		9. API Well No. 30-039-27422
3a. Address 3b. Phone No. (include area code) PO Box 640 Aztec, NM 87410 505-333-1806		10. Field and Pool or Exploratory Area Basin Fruitland Coal
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SHL 2631' FNL & 1150' FWL SEC 26 31N 6W BHL: 625' FSL & 2532' FEL SEC 23 31N 6W		11. Country or Parish, State Rio Arriba
12 CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACTION		
Notice of Intent Acidize Deepen Alter Casing Fracture Treat	Production (Sta	wrt/Resume) Water Shut-Off Well Integrity
Subsequent Report Casing Repair New Construc Change Plans Plug and Abar		Other
Final Abandonment Notice Convert to Plug Back 13. Describe Proposed or Completed Operation Clearly state all pertinent deta	Water Disposal	
duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) RCUD JUL 18 *12		
5/17/12- MIRU HWS #12 FOR SIDETRACK PREP		OIL CONS. DIV.
<u>5/20/12-</u> RIH AND SET RBP @ 2711' RDMOL		DIST. 3
<u>6/1/12-</u> MIRU AWS #980		
<u>6/2/12</u> - TEST BOP PIPE & BLIND RAMS, MUD CROSS VALVES, CHOKE MANIFOLD VALVES, UPPER KELLY VALVE, FLOOR VALVE @ 250# LOW 5 MIN AND 1500# HIGH 10 MIN EACH TEST 7" CSG @ 1500# 30 MIN ALL TEST GOOD		
6/3/12- RIH AND SET WHIPSTOCK MILL WINDOW 2687'- 2695'		
14 I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Ben Mitchell	Title Regulatory Spec.	
Signature 2 1/5/20/2		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE		
Approved by		
	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

NMOCD A

JUL 17 2012



6/4/12-6/6/12 DRILL 6-1/4" CURVE 2695'- 3594'

6/7/12-6/10/12 - DRILL 6-1/4" LATERAL 3594'-6483'. TD 6-1/4" LATERAL @ 6601' (3258' TVD)

6/11/12- RAN 85 JTS , 4-1/2", 11.6#, J-55, LT&C PERFERATED CASING (28, 0 50" HOLES P/FT) AND 10 JTS 4-1/2", 11.6#, J-55, LT&C NON PERFERATED CASING SET @ 6599', TOL @ 2706'. TOP PERFS @ 3153' AND BOTTOM @ 6596'

6/12/12- RDMO AWS #980

6/19/12- MIRU HWS #12 TO C/O LATERAL, RUN RODS AND LAND TUBING.

6/20/12-6/30/12- C/O LATERAL

7/1/12- POOH WITH WHIPSTOCK. RETRIEVE RBP

 $\frac{7/2/12}{1}$ LAND PRODUCTION TBG 2 7/8", 104 JTS TOTAL, EUE 8RD J-55 6.5# AS FOLLOWS TOP DOWN:TBG HANGER 1 JT, 102 JTS ,SN,1 JT MA WITH 1/2 MULE SHOE SN @ 3271', EOT@ 3303'. WITH 2800' STAINLESS STEEL CAP STRING.

RUN PUMP AND RODS AS FOLLOWS: one 2.5"x 1 25"x 7'x 11' RHAC Instert Pump w/ 1"x 6' Gas Anchor, 3 Norris 1.25" SB's, 127 Grade D Unguided Rods, one 2'x .75" Pony Rod, and one 1.25"x 16' PR w/ 1.5" PR Liner. RWAC SAND PRO HBR PUMP