Form 3160-5 (August 2007)

UNITED STATES RECEIVED DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT 26 2012 SUNDRY NOTICES AND REPORTS ON WELLS

5 Lease Serial No NM NM 86080

6 If Indian, Allottee or Tribe Name

FORM APPROVED

OMB No 1004-0137

Expires July 31, 2010

Do not use this form for proposals to drift on to re-enter affice

abandoned well.	Use Form 3160-3 (A	(PD)(forsúch)pi	oposalsme	<u> </u>	
SUBMIT IN TRIPLICATE – Other instructions on page 2.				7 If Unit of CA/Agreement, Name and/or No RCVD AUG 14'12	
1. Type of Well ☐ Gas Well ☐ Other				8 Well Name and No	OIL CONS. DIV.
2. Name of Operator Encana Oil & Gas (USA) Inc.				9 API Well No. 30-045-35341	DIST. 3
3a Address 370 17th Street, Suite 1700 Denver, CO 80202	3b Phone No. (included 720-876-3437	Bb Phone No. (include area code)		10 Field and Pool or Exploratory Area Gallegos - Gallup	
4. Location of Well (Footage, Sec., T, R, M, or Survey Description) SHL: 2183' FNL and 475' FEL Section 9, T25N, R10W BHL: 2181' FNL and 343' FWL Section 9, T25N, R10W				11. Country or Parish, State San Juan, New Mexico	
12. CHEC	CK THE APPROPRIATE BO	OX(ES) TO INDICATI	E NATURE OF NOTION	CE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION TYPE OF ACT				ΓΙΟΝ	
Notice of Intent	Acidize Alter Casing	Deepen Fracture Tre	rat Recl	duction (Start/Resume)	Water Shut-Off Well Integrity ✓ Other Casing Job
Subsequent Report BP	Casing Repair Change Plans	New Constr	andon Tem	omplete porarily Abandon	AMENDED
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Wate	er Disposal	
testing has been completed. Final determined that the site is ready for Utilized synthetic oil-based mud syproduction liner 06/28/12 - 06/29/12. Lateral hole diameter: 8.5", product Float shoe set at 9760' MD and float Set 18 external swellable casing part (7) 8119', (8) 7885, (9) 7653', (10) Rig released 06/30/12.	or final inspection.) stem, kicked off 3662' late 2. tion string diameter: 5.5", late collar set at 9747' MD. Fackers for isolation of prod	ral at 5018' TVD/MD production string weighted to the set from the se	KOP on 06/20/12. To ght and grade: 17ppf from 4623' to 9760'.	D reached 06/27/12. T SB80 LTC. Depth of 8	TD at 9760' MD/5585' TVD. Set 8.5" hole from 4836' to 9760' MD. 51', (4) 8820', (5) 8587', (6) 8353',
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Amanda Cavoto		Title	Title Engineering Technologist		
Signature /manda (ando	Date	07/25/12		
	THIS SPACE	FOR FEDERAL	OR STATE OF	FICE USE	WHITEHOM RECORD
Approved by					AUS 0 2 2012
Conditions of approval, if any, are attached that the applicant holds legal or equitable entitle the applicant to conduct operation	title to those rights in the subj		Office		PRINCION FIGURE OFFICE:

(Instructions on page 2)

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Title 18 U S C Section 1001 and Title 43 U.S C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,