

Form 3160-5 (August 2007)

SEP 2 0 2012 **UNITED STATES** DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0137 Expires. July 31, 2010

2741							_ = = 1 11 1
BUR	EAU OF LAND MAN	AGEMENT	gion Field Oillo	ment ce	5. Lease Serial No SF-078860	R	CUD SEP 24 12
SUNDRY N Do not use this t	NOTICES AND REPO form for proposals to Use Form 3160-3 (A	ORTS ON WE o drill or to r	LLS e-enter an		6. If Indian, Allottee or		Numerons. DIV.
SUBMIT IN TRIPLICATE – Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.		
Type of Well					8. Well Name and No.		
☑ Oil Well ☐ Gas Well ☐ Other					Escrito I24-2409 01H		
2 Name of Onerator Encana Oil & Gas (USA) Inc.					9. API Well No. 30-045-35322		
Ba. Address 170 17th Street, Suite 1700 Janver, CO 80202		3b. Phone No. (in 720-876-3437	iclude area code)		 Field and Pool or E Bisti - Lower Gallup 	xplora	ltory Area
4. Location of Well <i>(Footage, Sec., T.,</i> 3HL, 1935 FSL, 205 FEL Section 24, T24N, R 3HL 1935 FSL, 330 FWL Section 24, T24N, R	11. Country or Parish, State San Juan County, NM						
12 CHEC	CK THE APPROPRIATE BO	X(ES) TO INDIC	ATE NATURE OF	NOTIC	E, REPORT OR OTH	ER DA	TA
TYPE OF SUBMISSION		······································	ТҮРЕ О	F ACTI	ON		
Notice of Intent	Acidize	Deepen		Produ	ction (Start/Resume)		Water Shut-Off
	Alter Casing	Fracture		=	mation		Well Integrity
Subsequent Report	Casing Repair		nstruction		nplete	√	Other Casing/Cement Job
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Plug Ba	J Abandon ck		oranly Abandon Disposal		
13 Describe Proposed or Completed C the proposal is to deepen direction Attach the Bond under which the following completion of the invol- testing has been completed. Final determined that the site is ready for Set intermediate casing string and of	work will be performed or proved operations. If the operation Abandonnient Notices must be final inspection.)	ovide the Bond No on results in a mul- be filed only after a	on file with BLM/ tiple completion or all requirements, and	BIA. Recompt	equired subsequent repletion in a new interval	orts m , a Fon	ust be filed within 30 days in 3160-4 must be filed once
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for the following completed is ready for the following completed. Final determined that the site is ready for the following completed. Final determined that the site is ready for the following complete is ready for the following complete in the following complete is the following complete in the following complete i	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the er: 7". Casing weight and g MD. Top of float collar at 55 cmium Lite FM + 3% Cacl2 ent + 1% Cacl2 + 0.25#/sk (c. Lite FM + 3% Cacl2 + 0.25	ovide the Bond No on results in a mul- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellol Celloflake + 0.2%	on file with BLM/ tiple completion or all requirements, and restern. TC. Depth of 8.5" surface and BOC at the surface and BCC at the surface at the sur	/BIA. Rerecomple cluding in the frost of the	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	ediate Sodium 2 hou	ust be filed within 30 days in 3160-4 must be filed once eted and the operator has casing set from surface to in Metasilicate + 0.4% irs.
the proposal is to deepen direction. Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for the strength of	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the error, Casing weight and gMD. Top of float collar at 55 cmium Lite FM + 3% Cacl2 ent + 1% Cacl2 + 0.25#/sk (a. Lite FM + 3% Cacl2 + 0.25	ovide the Bond No on results in a mul- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellol Celloflake + 0.2%	on file with BLM/ tiple completion or all requirements, and restern. TC. Depth of 8.5" surface and BOC at the surface and BCC at the surface at the sur	/BIA. Rerecomple cluding in the frost of the	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	, a Fon comple ediate Godium 2 Phou A. Circ	ust be filed within 30 days in 3160-4 must be filed once eted and the operator has casing set from surface to in Metasilicate + 0.4% irs. ulated 2 bbls cement to surface drop.
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for Set intermediate casing string and thole diameter: 8.5°, Casing diameter 5605'MD. Stage tool at 1809'TVD/M Stage 1 Cement: Lead 229 sks Pre FL-52A. Tail 165 sks Type III Cemes Stage 2 Cement: 167 sks Premium surface. WOC 8 hours. Started drilling out stage tool at 179 Started drilling out stage tool at 179 Name (Printed/Typed)	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the error, Casing weight and gMD. Top of float collar at 55 cmium Lite FM + 3% Cacl2 ent + 1% Cacl2 + 0.25#/sk (a. Lite FM + 3% Cacl2 + 0.25	ovide the Bond No on results in a mul- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellof Celloflake + 0.2% 5#/sk Celloflake	on file with BLM/ tiple completion or all requirements, and stem. TC. Depth of 8.5" surface and BOC at the surface at the surfac	HA. Rerecomple cluding in the front of the f	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	, a Fon comple ediate Godium 2 Phou A. Circ	ust be filed within 30 days in 3160-4 must be filed once eted and the operator has casing set from surface to in Metasilicate + 0.4% irs. ulated 2 bbls cement to surface drop.
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for Set intermediate casing string and thole diameter: 8.5°, Casing diameters and the site is ready for the string of the set of	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the error of float collar at 55 amium Lite FM + 3% Cacl2 and + 1% Cacl2 + 0.25#/sk (Cacl2	ovide the Bond No on results in a mul- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellof Celloflake + 0.2% 5#/sk Celloflake	on file with BLM/ tiple completion or all requirements, and restern. TC. Depth of 8.5" surface and BOC at the surface and BCC at the surface at the sur	HA. Rerecomple cluding in the front of the f	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	ediate ediate ediate A. Circ	ust be filed within 30 days in 3160-4 must be filed once etcd and the operator has casing set from surface to in Metasilicate + 0.4% irs. Metasilicate + 0.4% irs. Lilated 2 bbls cement to surface drop. ACCEPTED FOR RECURED SEP 2 1 2012
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for Set intermediate casing string and thole diameter: 8.5°, Casing diameter 5605'MD. Stage tool at 1809'TVD/M Stage 1 Cement: Lead 229 sks Pre FL-52A. Tail 165 sks Type III Cemes Stage 2 Cement: 167 sks Premium surface. WOC 8 hours. Started drilling out stage tool at 179 Started drilling out stage tool at 179 Name (Printed/Typed)	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the final inspection. cemented 9/7/12. Gelled from the final inspection. cer; 7", Casing weight and gold. Top of float collar at 55 cmium Lite FM + 3% Cacl2 and + 1% Cacl2 + 0.25#/sk to Lite FM + 3% Cacl2 + 0.25#/sk to Lite FM + 3% Cacl2 + 0.25*/sk to Lite F	povide the Bond No on results in a multi- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellor Celloflake + 0.2% 5#/sk Celloflake	on file with BLM/ tiple completion or all requirements, and restar. TC. Depth of 8.5" surface and BOC at the surface at	hole fro at 5605 1-1 + 8% ted 30 t ted 30 t Techno	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	ediate ediate ediate A. Circ	ust be filed within 30 days in 3160-4 must be filed once etcd and the operator has casing set from surface to in Metasilicate + 0.4% irs. ACCEPTED FOR RECURE SEP 2 1 2012
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for Set intermediate casing string and thole diameter: 8.5°, Casing diameters and the site is ready for the string of the set of	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the error of float collar at 55 amium Lite FM + 3% Cacl2 and + 1% Cacl2 + 0.25#/sk (Cacl2	povide the Bond No on results in a multi- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellor Celloflake + 0.2% 5#/sk Celloflake	on file with BLM/ tiple completion or all requirements, and restar. TC. Depth of 8.5" surface and BOC at the surface at	hole fro at 5605 1-1 + 8% ted 30 t ted 30 t Techno	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	ediate ediate ediate A. Circ	ust be filed within 30 days in 3160-4 must be filed once etcd and the operator has casing set from surface to in Metasilicate + 0.4% irs. ACCEPTED FOR RECURE SEP 2 1 2012
the proposal is to deepen direction Attach the Bond under which the following completion of the involvesting has been completed. Final determined that the site is ready for Set intermediate casing string and thole diameter: 8.5", Casing diameter 5605'MD. Stage fool at 1809'TVD/M Stage 1 Cement: Lead 229 sks Pre FL-52A. Tail 165 sks Type III Cemes Stage 2 Cement: 167 sks Premium surface. WOC 8 hours. Started drilling out stage tool at 179 Started drilling out stage tool at 179 Name (Printed/Typed) Amanda Cavoto	work will be performed or proved operations. If the operation Abandonment Notices must be final inspection.) cemented 9/7/12. Gelled from the final inspection. cemented 9/7/12. Gelled from the final inspection. cer; 7", Casing weight and gold. Top of float collar at 55 cmium Lite FM + 3% Cacl2 and + 1% Cacl2 + 0.25#/sk to Lite FM + 3% Cacl2 + 0.25#/sk to Lite FM + 3% Cacl2 + 0.25*/sk to Lite F	povide the Bond No on results in a multi- be filed only after a eshwater mud sy grade: 26# J55 L 193'MD. TOC at s + 0.25#/sk Cellor Celloflake + 0.2% 5#/sk Celloflake	on file with BLM/ tiple completion or all requirements, and restar. TC. Depth of 8.5" surface and BOC at the surface at	hole fro at 5605 1-1 + 8% ted 30 t ted 30 t Techno	equired subsequent repetion in a new interval reclamation, have been on 0 to 5695'. Intermediate the control of	ediate ediate ediate A. Circ	ust be filed within 30 days in 3160-4 must be filed once etcd and the operator has casing set from surface to in Metasilicate + 0.4% irs. ACCEPTED FOR RECURED SEP 2 1 2012

(Instructions on page 2)