District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W Grand Ave , Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008 For temporary pits, closed-loop sytems, and below-grade

Form C-144

tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe

District		
1220 S St	Francis Dr., Santa Fe, NM	1
n	}	p
17	-	
100/	Type of act	i
10.		

District IV 1220 S St. Francis Dr., Santa Fe, NM 87505	Environmental Bureau office and provide a copy to the appropriate NMOCD District Office
Pit, Closed-Loop System,	Below-Grade Tank, or
Proposed Alternative Method Po	ermit or Closure Plan Application
Type of action: Permit of a pit, closed-loop syste	em, below-grade tank, or proposed alternative method
X Closure of a pit, closed-loop syst	tem, below-grade tank, or proposed alternative method
Modification to an existing perm	nit
	an existing permitted or non-permitted pit, closed-loop system,
below-grade tank, or proposed a Instructions: Please submit one application (Form C-144) per individu	
Please be advised that approval of this request does not relieve the operator of liabil environment. Nor does approval relieve the operator of its responsibility to comply with	ity should operations result in pollution of surface water, ground water or the
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: HUERFANITO UNIT 82N	
API Number: 30-045-35310	OCD Permit Number:
U/L or Qtr/Qtr: M(SW/SW) Section: 25 Township: 27N	Range: 9W County: SAN JUAN
Center of Proposed Design: Latitude: 36.53936 °N Surface Owner: Federal State Private X Tri	Longitude: 107.74617 °W NAD: 1927 X 1983 bal Trust or Indian Allotment
2 X Pit: Subsection F or G of 19 15.17.11 NMAC	RCVD NOV 14'12
Temporary: Drilling Workover	
Permanent Emergency X Cavitation P&A (Pre-set)	OIL CONS. DIV.
Lined Unlined Liner type: Thickness mil	LLDPE HDPE PVC Other DIST. 3
String-Reinforced	
Liner Seams: Welded Factory Other	Volume:bbl Dimensions Lx Wx D
Closed-loop System: Subsection H of 19.15.17.11 NMAC	
	Drilling (Applies to activities which require prior approval of a permit or nt)
Drying Pad Above Ground Steel Tanks Haul-off Bins	Other
Lined Unlined Liner type: Thicknessmil	LLDPE HDPE PVD Other
Liner Seams: Welded Factory Other	
4 Below-grade tank: Subsection Lof 19 15 17 11 NMAC	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	; 6-inch lift and automatic overflow shut-off
Below-grade tank: Subsection I of 19.15.17.11 NMAC	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Form C-144

Alternative Method:

Oil Conservation Division

Page 1 of 5

Fencing: Subsection D of 19.15.17 11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19.15 17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of app	roval.	
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No	
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes NA	No	
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No	
 NM Office of the State Engineer - IWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes	□No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	☐Yes ☐Yes	□No	
 Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 	Yes	No	
Society; Topographic map Within a 100-year floodplain - FEMA map	Yes	No	

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design) API or Permit			
12			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15.17.9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17 9			
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17.12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15 17 13 NMAC			
Previously Approved Design (attach copy of design) API			
Previously Approved Operating and Maintenance Plan API			
Permanent Pits Permit Application Checklist: Subsection B of 19 15.17.9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Climatological Factors Assessment			
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC			
Dike Protection and Structural Integrity Design. based upon the appropriate requirements of 19.15.17.11 NMAC			
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC			
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC			
Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
Nuisance or Hazardous Odors, including H2S, Prevention Plan			
Emergency Response Plan			
Oil Field Waste Stream Characterization			
Monitoring and Inspection Plan			
Erosion Control Plan			
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
14			
Proposed Closure: 19 15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System			
Alternative			
Proposed Closure Method. Waste Excavation and Removal			
Waste Removal (Closed-loop systems only)			
On-site Closure Method (only for temporary pits and closed-loop systems)			
In-place Burial On-site Trench			
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
15			
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.			
Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Book fill and Cover Design Specifications, based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Ste Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15 17.13 NMAC			

Form C-144 Oil Conservation Division Page 3 of 5

16			
Waste Removal Closure For Closed-loop Systems That Utilize Above Groun Instructions Please identify the facility or facilities for the disposal of liquids, d	nd Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC)		
facilities are required	inning futus and arm cultings. Ose attachment y more than two	,	
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-	0010B	
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005		
Will any of the proposed closed-loop system operations and associated Yes (If yes, please provide the information No	activities occur on or in areas that will nbe used for future	e service and	
Required for impacted areas which will not be used for future service and opera	ntions.		
Soil Backfill and Cover Design Specification - based upon the a	• •	NMAC	
Re-vegetation Plan - based upon the appropriate requirements of S			
Site Reclamation Plan - based upon the appropriate requirements of	of Subsection G of 19 15.17 13 NMAC		
17 Siting Criteria (Regarding on-site closure methods only: 19 15 17 10 1) Instructions Each string criteria requires a demonstration of compliance in the closure plicertain string criteria may require administrative approval from the appropriate district of office for consideration of approval. Justifications and/or demonstrations of equivalency of the consideration of approval.	an Recommendations of acceptable source material are provided belo ffice or may be considered an exception which must be submitted to the		
	1000		
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - 1WATERS database search; USGS: Database State Engineer - 1WATERS database search - 1WATERS data		Yes No	
- 1444 Office of the State Engineer - 1444 ENS database seatch, USGS. Da	ad obtained non-hearby wens		
Ground water is between 50 and 100 feet below the bottom of the burie		Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Da	ta obtained from nearby wells	∐N/A	
Ground water is more than 100 feet below the bottom of the buried was	ste.	Yes No	
- NM Office of the State Engineer - (WATERS database search; USGS; Da	ta obtained from nearby wells	N/A □	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other (measured from the ordinary high-water mark).	significant watercourse or lakebed, sinkhole, or playa lake	Yes No	
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or chu - Visual inspection (certification) of the proposed site, Aerial photo; satellite	••	Yes No	
The second continuous of the proposed site, 1101at proof, outcome	· ·······g··	☐Yes ☐No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that le purposes, or within 1000 horizontal fee of any other fresh water well or spring, i - NM Office of the State Engineer - iWATERS database, Visual inspection	in existence at the time of the initial application.		
Within incorporated municipal boundaries or within a defined municipal fresh was pursuant to NMSA 1978, Section 3-27-3, as amended	atter well field covered under a municipal ordinance adopted	Yes No	
 Written confirmation or verification from the municipality, Written approx Within 500 feet of a wetland 	val obtained from the municipality		
- US Fish and Wildlife Wetland Identification map, Topographic map, Visu	ual inspection (certification) of the proposed site	Yes No	
Within the area overlying a subsurface mine.		Yes No	
- Written confirantion or verification or map from the NM EMNRD-Mining	g and Mineral Division		
Within an unstable area.		Yes No	
- Engineering measures incorporated into the design, NM Bureau of Geolog	y & Mineral Resources; USGS, NM Geological Society,		
Topographic map Withın a 100-year floodplain FEMA map		Yes No	
18			
On-Site Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: by a check mark in the box, that the documents are attached,	Each of the following items must bee attached to the cl	osure plan. Please indicate,	
Siting Criteria Compliance Demonstrations - based upon the app	propriate requirements of 19.15.17.10 NMAC		
Proof of Surface Owner Notice - based upon the appropriate requ	· ·		
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
X Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements	s or Subsection G of 19.15.17.13 NMAC	l	

Page 4 of 5

Form C-144 Oil Conservation Division

19 Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief
Name (Print): Title:
Signature. Date: e-mail address: Telephone:
C-man address.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 19/2612 Title: OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 6/20/2012
22
Closure Method: Waste Excavation and Removal On-site Closure Method X Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized. Disposal Facility Name Disposal Facility Permit Number Disposal Facility Name Disposal Facility Permit Number
Disposal Facility Name: Disposal Facility Permit Number: Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?
Yes (If yes, please demonstrate complilane to the items below)
Required for impacted areas which will not be used for future service and operations. Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (if applicable) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)
On-site Closure Location: Latitude: Longitude: NAD 1927 1983
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan Name (Print): Jamie Goodwin Title: Regulatory Technician
Signature Date: 11917
e-mail address. <u>jamie.l.goodwin@conocophillips.com</u> Telephone: 505-326-9784

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	381
TPH	EPA SW-846 418.1	2500	111
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	30

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.

Huerfanito Unit 82N 30-045-35310 Permit # 10009 (Pre Set)

The Huerfanito Unit 82N was approved for a Closed Loop permit # 9922 on 4/19/2012. Due to COPC change in plans to Air Pre Set. Pre Set application permit # 10009 was submitted and approved on 5/25/2012. According to Cavitation Pit for a Closed Loop Locations Closure Plan #1 – (The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cutting being transported, moved or distributed on location). COPC is notifying the NMOCD after the fact. Pre Set was conducted on 6/20/2012 and Environmental Samples are attached to this closure report. In the future COPC will comply with closure procedure #1 via: e-mail of move on date, environmental test samples and will be followed by the Pre Set closure report.

Thank you,

Jamie Goodwin ConocoPhillips Regulatory Tech.



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	06-21-12
Laboratory Number:	62420	Date Sampled:	06-20-12
Chain of Custody No:	09554	Date Received:	06-20-12
Sample Matrix:	Soil	Date Extracted:	06-21-12
Preservative:	Cool	Date Analyzed:	06-21-12
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	· ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: Huerfanito Unit 82N/ MOTE 212





EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

N/A

N/A

06-21-12

Client: QA/QC Project #:

Sample ID: 0621TCAL QA/QC Date Reported:

Laboratory Number: 62424 Date Sampled:

Sample Matrix: Methylene Chloride Date Received: N/A

Preservative: N/A Date Analyzed: 06-21-12
Condition: N/A Analysis Requested: TPH

Gasoline Range C5 - C10 06-21-12 9.9960E+02 1.0000E+03 0.04% 0 - 15%

Diesel Range C10 - C28 06-21-12 9.9960E+02 1.0000E+03 0.04% 0 - 15%

Blank Conc. (mg/L-mg/Kg)
Concentration
Detection Limit
Gasoline Range C5 - C10
ND
0.2
Diesel Range C10 - C28
ND
0.1
Total Petroleum Hydrocarbons
ND

Duplicate Conc. (mg/Kg)SampleDuplicate% DifferenceAccept RangeGasoline RangeC5 - C10NDND0.0%0 - 30%Diesel RangeC10 - C28NDND0.0%0 - 30%

Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery :	Accept: Range
Gasoline Range C5 - C10	ND	250	275	110%	75 - 125%
Diesel Range C10 - C28	ND	250	284	114%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Was

SW-846, USEPA, December 1996.

Comments: QA/QC for Samples 62420 and 62424



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

		•	Det.
		Dilution:	50
Condition:	Intact	Analysis Requested:	BTEX
Preservative:	Cool	Date Extracted:	06-21-12
Sample Matrix:	Soil	Date Analyzed:	06-21-12
Chain of Custody:	09554	Date Received:	06-20-12
Laboratory Number:	• 62420	Date Sampled:	06-20-12
Sample ID:	Pre-Set Cuttings	Date Reported:	06-21-12
Client:	ConocoPhillips	Project #:	96052-1706

		Det.	
	Concentration	Limit	
Parameter	(ug/Kg)	(ug/Kg)	
Benzene	ND	10.0	
Toluene	22.3	10.0	
Ethylbenzene	38.4	10.0	
p,m-Xylene	261	10.0	
o-Xylene	59.7	10.0	
Total BTEX	381		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	80.2 %
	1,4-difluorobenzene	89.4 %
	Bromochlorobenzene	91.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Huerfanito Unit 82N/ MOTE 212



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	0621BCAL QA/QC	Date Reported:	06-21-12
Laboratory Number:	62414	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	ŃΑ	Date Analyzed:	06-21-12
Condition:	N/A	Analysis:	BTEX
		Dilution:	50

Calibration (and) Detection Limits (ug/L	U-Cal RF.	C-Cal RE	%Diff.	Blank Conc	Detect. +- Limit
Benzene	6.9371E-06	6.9371E-06	0.000	ND	0.2
Toluene	6.6171E-06	6.6171E-06	0.000	ND	0.2
Ethylbenzene	7.3910E-06	7.3910E-06	0.000	ND	0.2
p,m-Xylene	5.4064E-06	5.4064E-06	0.000	ND	0.2
o-Xylene	7.7691E-06	7.7691E-06	0.000	ND	0.2

Duplicate Conc. (ug/Kg) Sample Duplicate Duplicate Accept Range Detects Limits					
Benzene	164	166	0.01	0 - 30%	10
Toluene	940	960	0.02	0 - 30%	10
Ethylbenzene	1660	1620	0.02	0 - 30%	10
p,m-Xylene	10800	11300	0.05	0 - 30%	10
o-Xylene	2120	2240	0.06	0 - 30%	10

Spike Conc. (ug/Kg)	Sample: Amo	ALTON A COCKONICATION -	the second second of the second		7,000,000,000,000
Benzene	164	2500	2800	105	39 - 150
Toluene	940	2500	4220	123	46 - 148
Ethylbenzene	1660	2500	4870	117	32 - 160
p,m-Xylene	10800	5000	16700	106	46 - 148
o-Xylene.	-2120	2500	5230	113	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References: Metho

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for Samples 62414-62418, 62420 and 62424

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

envirotech-inc.com laboratory@envirotech-inc.com



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	06-21-12
Laboratory Number:	62420	Date Sampled:	06-20-12
Chain of Custody No:	09554	Date Received:	06-20-12
Sample Matrix:	Soil	Date Extracted:	06-21-12
Preservative:	Cool	Date Analyzed:	06-21-12
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

111

29.6

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hýdrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments: Huerfanito Unit 82N/ MOTE 212



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS **QUALITY ASSURANCE REPORT**

Client: QA/QC

Project #: N/A

Sample ID: **QA/QC** Laboratory Number:

Date Reported: 06-21-12 N/A

Sample Matrix:

06-20-12-TPH.QA/QC 62420 Date Sampled: Date Analyzed:

06-21-12

Preservative:

Freon-113 N/A

06-21-12

Date Extracted:

06-21-12

Condition:

N/A

Analysis Needed:

TPH

Calibration I Cal Date C-Cal Date : U-Cal RE: C-Cal RE: % Difference Accept Range

06-13-12

1,850

1,720

7.0%

+/- 10%

Blank Conc. (mg/Kg)

Concentration

Detection Limit

TPH

TPH

TPH

ND

29.6

Duplicate Conc. (mg/Kg)

Sample 111

∰ Duplicate → % Difference 111

0.0%

Accept Range +/- 30%

Spike Conc. (mg/Kg

111

Sample Spike Added Spike Result % Recovery Accept Range 1 2,000

2,070

98.1%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 62420.



Chloride

, Client: ConocoPhillips Project #: 96052-1706 Sample ID: **Pre-Set Cuttings** Date Reported: 06-22-12 Lab ID#: 62420 Date Sampled: 06-20-12 Sample Matrix: Date Received: Soil 06-20-12 Preservative: Date Analyzed: 06-21-12 Coòl Condition: Intact Chain of Custody: 09554

Parameter Concentration (mg/Kg)

Total Chloride

30

Reference: U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983.

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Huerfanito Unit 82N / MOTE 212