

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

5. Lease Designation and Serial No.
SF-078771

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
ROSA UNIT

8. Well Name and No.
ROSA UNIT #67

9. API Well No.
30-039-22045

10. Field and Pool, or Exploratory Area
LAGUNA SECA GALLUP

11. County or Parish, State
RIO ARRIBA, NM

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
WILLIAMS PRODUCTION COMPANY

3. Address and Telephone No.
PO BOX 3102 MS 25-1, TULSA, OK 74101 (918) 561-6254

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1520' FNL & 1510' FEL, SW/4 NE/4, SEC 14 T31N R6W

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment -
Recompletion
Plugging Back
Casing Repair
Altering Casing
Other _____

Change of Plans
New Construction
Non-Routine Fracturing
Water Shut-Off
Conversion to Injection
Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Williams Production Company plans to P&A the above well per the following procedure. Spot a 50 sack class H cement plug down the 1 1/4" tbg across the perms from the cement retainer at 7900' to 6900'. Pick up 100' and reverse clean. Pick up another 100' and wait on the cement to set up. Drop back in and tag the top of the plug. Then fill the 2 7/8" csg with class H cement to surface by spotting 50 sacks for 1500' at a time until full. Estimated start date will be 06/01/05 if not before.

RECEIVED
070 FARMINGTON NM
05 APR 18 PM 1 30

14. I hereby certify that the foregoing is true and correct

Signed Tracy Ross
TRACY ROSS

Title SR. PRODUCTION ANALYST Date April 11, 2005

(This space for Federal or State office use)

Original Signed: Stephen Mason
Approved by _____

Title _____ Date MAY 02 2005

Conditions of approval, if any: