

PN

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1305' FSL, 1235' FWL, Sec. 16, T-32-N, R-8-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-29964

5. Lease Number

6. State Oil & Gas Lease #
V-88-1

7. Lease Name/Unit Name

Susco 16 State

8. Well No.

2

9. Pool Name or Wildcat
Albino Pictured Cliffs

10. Elevation:



Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

4-30-04 MIRU. ND WH. NU BOP. Test BOP, OK. TOOH w/119 jts 2 3/8" tbgs. TIH w/3 7/8" bit & 4 1/2" scraper to 3598'. TOOH. TIH w/4 1/2" cmt retainer, set @ 3598'. Load tbgs w/4 bbl wtr. PT tbgs to 1000 psi/15 min, OK. Load csg w/60 bbl wtr. PT csg to 500 psi/15 min, OK. Load bradenhead w/2.5 bbl wtr. PT bradenhead to 300 psi, failed. SD for weekend.

5-3-04 (Verbal approval to go ahead with plugging from Charlie Perrin, OCD). Establish circ. Plug #1: pump 43 sx Class "B" neat cmt inside csg @ 3032-3598' to cover Pictured Cliffs perms & Fruitland top. TOOH to 2202'. Establish circ. Plug #2: pump 26 sx Class "B" neat cmt inside csg @ 1860-2202' to cover Kirtland and Ojo Alamo tops. TOOH to 750'. Establish circ. Plug #3: pump 12 sx Class "B" neat cmt inside csg @ 592-750' to cover Nacimiento top. TOOH. Load hole w/wtr. TIH, perf 3 sqz holes @ 272'. Attempt to establish circ down csg & out bradenhead. Hole pressured up to 1000 psi. (Verbal approval to change plans from Charlie Perrin, OCD). TIH, perf 3 sqz holes @ 100'. Attempt to establish circ. No flow out bradenhead. (Verbal approval to change plans from Charlie Perrin, OCD). TIH, perf 3 sqz holes @ 50'. Establish circ down csg & out bradenhead w/3 bbl wtr. TIH to 322'. Establish circ. Plug #4: pump 72 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. Shut in bradenhead valve. TIH, found TOC @ 20' in csg. Pump 10 sx Class "B" neat cmt to fill csg. WOC. SDON.

5-4-04 Tag TOC in 4 1/2" csg @ surface. ND BOP. Cut off WH. Annulus TOC @ surface. Install dry hole marker w/12 sx Class "B" neat cmt. RD. Rig released.

Well plugged and abandoned 5-4-04

SIGNATURE Nancy Oltmanns Senior Staff Specialist June 22, 2004

no
(This space for State Use)

Approved by H. Villanueva
5-9-05

DEPUTY OIL & GAS INSPECTOR, DIST. #2
Title

JUN 23 2005
Date