		5. Lease	
. UNITED STATES DEPARTMENT OF THE INTERIOR		NMNM-03733	
		NMINM-03733	
BUREAU OF LAND MANAGEMENT			
		6. If Indian, Allottee or Tribe Name	
SUNDRY NOTICES AND REPORTS ON WELLS		7. Unit Agreement Name	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals)			
1. Oil Well [] Gas Well [] Other []		8. Well Name and No.	
GAS WELL	160 A - 23		BREECH 377
2. Name of Operator: Caulkins Oil Company MAY 2005		9. API Well No. 30-039-25690-00C5	
3. Address of Operator: (505) 334-4323		10. Field and Pool, Exploratory Area	
1409 W. Aztec Blvd. Ste B7, Aztec, NM 87410		PICTURED CLIFFS	
4. Location of Well (Footage, Sec., Twp., Rge.)		11. Country or Parish, State	
1165' F/S 1025' F/W SEC. 23-26N-7W 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF N		Rio Arriba Co., New Mexico	
TYPE OF SUBMISSION	TYPE OF ACTION	OTICE, REPO	RT, OR OTHER DATA
[X] Notice of Intent	[X] Abandonment		[] Change of Plans
[A] Notice of Intent [A] Abandonment [A] Recompletion			New Construction
[] Subsequent Report	[] Plugging Back		[] Non-Routine Fracturing
	[] Casing Repair		[] Water Shut-Off
[] Final Abandonment Notice [] Altering Casing			[] Conversion to Injection
[] Other [] Dispose Water 17. Describe Proposed or Completed Operations:			
5-20-05 This well was previously plugged back to 3833' in September 2004.			
We now intend to plug and abandon this well by the following procedure:			
Rig up.			
T. O. H. with 1 1/2" tubing.			
T. I. H. with cast iron bridge plug; set plug at 2936' – Pictured Cliffs perforations 2986' to 3060'.			
Load hole, test casing to 1000#.			
· · · · · · · · · · · · · · · · · · ·			
T. H. H. Javing down 1.1/2" tubing			
Street place to cover Notine and with 14 people (10 4 ov. A.) 11752 to 10202			
Spot plug to cover Nacimento with 14 sacks (19.4 cu. ft.) 1175' to 1030'.			
T. U. H. laying down 1 1/2" tubing. Circulate final plug with 36 sacks (50 1 cu. ft.) from 384' to surface			
Circulate final plug with 36 sacks (50.1 cu. ft.) from 384' to surface.			
Rig down cementers and rig.			
Install P&A marker.			
No new surface will be disturbed, location area will be cleaned up following operations.			
Estimated starting date, June 27, 2005.			
NOTE: The format is issued in lieu of U.S. BLM Form 3160-5			
18. I HEREBY CERTIFY THE FOREGOING IS TRUE AND CORRECT			
SIGNED: West 2 Verge TITLE: Superintendent DATE: May 20, 2005			
ROBERT L. VERQUER			
APPROVED BY: Original Signed: Steph	en Mason TITLE:	DATE:	MAY 2 6 2005
CONDITIONS OF APPROVAL, IF ANY			
NMOCD			