UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells	× 1.4.75	
	5.	Lease Number
1. Type of Well GAS 070 FARMINGTON	6.	NMNM-012573 If Indian, All. or Tribe Name
	7.	Unit Agreement Name
Name of Operator BURLINGTON		
RESOURCES OIL & GAS COMPANY LP		San Juan 30-6 Unit
3. Address & Phone No. of Operator	8.	Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700	o) ≡ 9.	#400S API Well No.
PO Box 4269, Farmington, INM 67499 (303) 320-9700	ÿ. -	Ari wen No.
l. Location of Well, Footage, Sec., T, R, M	7	30-039-29403
CE BILLS COMPANY	10.	Field and Pool
Unit F (SENW), 1510' FNL & 1465' FWL, Section 14, T30N, R7W, NMPM		Basin Fruitland Coal
	11.	County and State Rio Arriba Co., NM
Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations		
4/27/05 MIRU Aztec #580. NU BOP, PT casing to 600#/30 min. OK. TIH w/8-3/4" bit & tagged ce		
to 2900'. Circ. hole. RIH w/66 jts 7", 20#, J-55 ST&C casing and landed @ 2898'. RU BJ, pumped Scavenger cement – 9 sx (27 cf – 5 bbl slurry), Type III w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM 300 sx (703 cf – 125 bbl slurry) Premium Lite Type III w/3% CaCl2, .25#/sx Celloflake, .2% FL-52. Bumped plug @ 0400 hrs 5/3/05. Never circ to surface. ND BOP, RDMO, Rig released 5/3/05. 5/10 about squeeze since 7" didn't circ. to surface. Dale Gall w/BR took logs to BLM and received approached (Ojo top @ 2210'). Blockage @ 1480'.	-1, .4% FL-5. Displaced w. 0/05 Called Boval to squee:	0 bbls FW. Lead 2, 4% SMS. Lead- 115 bbls FW. LM (Adrienne Brumley) e. CBL show TOC @
Scavenger cement – 9 sx (27 cf – 5 bbl slurry), Type III w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM 300 sx (703 cf – 125 bbl slurry) Premium Lite Type III w/3% CaCl2, .25#/sx Celloflake, .2% FL-52. Bumped plug @ 0400 hrs 5/3/05. Never circ to surface. ND BOP, RDMO, Rig released 5/3/05. 5/10 about squeeze since 7" didn't circ. to surface. Dale Gall w/BR took logs to BLM and received approx 2280' (Ojo top @ 2210'). Blockage @ 1480'. 5/12/05 MIRU Aztec #469. RU BJ & Black Warrior WL. PT –OK. PT 7" casing to 2500#/15 min. holes. RIH w/cement retainer & set @ 2190'. Spot 6 bbls cement to end of tbg. Sting into cement ruppe III cement w/1% Cacl2, ¼#/sx Celloflake, .2% FL-52. Squeeze to 1750 psi. Shut-in. POH w/s aran CBL from 2149' – 1300'. TOC @ 1600'. RD BWWC. NU, TIH w/ bit & tagged cement @ 2.2190'; D/O retainer @ 2190'. Drilled to 2230'. Fell out @ sqz holes. Circ. hole. PT casing to 1000 D/O cement from 2883' to 3261'. Circ. Hole. RIH w/12 jts. 5-1/2", 15.5#, J-55 pre-perf'd liner @ 27 (52' overlap). Perfs @ 2919' – 2941', 3026' – 3130'; 3152' – 3174'. TIH w/2-3/8" 4.7#, J-55 tbg &	Good test. Setainer. Squeetinger. 5/15/149'. D/O co. #/30 min. O 36' & set @ set @ 3218'	0 bbls FW. Lead 2, 4% SMS. Lead- 115 bbls FW. LM (Adrienne Brumley) te. CBL show TOC @ choot 2 squeeze ezed w/150 sx 05 RU BWWC ement from 2149' K. RIH w/bit & 3261' TOL @ 2831' w/SN @ 3193'
Scavenger cement – 9 sx (27 cf – 5 bbl slurry), Type III w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM 300 sx (703 cf – 125 bbl slurry) Premium Lite Type III w/3% CaCl2, .25#/sx Celloflake, .2% FL-52. Sumped plug @ 0400 hrs 5/3/05. Never circ to surface. ND BOP, RDMO, Rig released 5/3/05. 5/10 about squeeze since 7" didn't circ. to surface. Dale Gall w/BR took logs to BLM and received approx 2280' (Ojo top @ 2210'). Blockage @ 1480'. 5/12/05 MIRU Aztec #469. RU BJ & Black Warrior WL. PT –OK. PT 7" casing to 2500#/15 min. holes. RIH w/cement retainer & set @ 2190'. Spot 6 bbls cement to end of tbg. Sting into cement ruppe III cement w/1% Cacl2, ¼#/sx Celloflake, .2% FL-52. Squeeze to 1750 psi. Shut-in. POH w/s aran CBL from 2149' – 1300'. TOC @ 1600'. RD BWWC. NU, TIH w/ bit & tagged cement @ 2/2190'; D/O retainer @ 2190'. Drilled to 2230'. Fell out @ sqz holes. Circ. hole. PT casing to 1000 D/O cement from 2883' to 3261'. Circ. Hole. RIH w/12 jts. 5-1/2", 15.5#, J-55 pre-perf'd liner @ 27/52' overlap). Perfs @ 2919' – 2941', 3026' – 3130'; 3152' – 3174'. TIH w/2-3/8" 4.7#, J-55 tbg & 102 jts). ND BOP, NU WH. 5/23/05 RIH w/pump & rods. Spaced out & PT tbg & pump to 500# –	Good test. Setainer. Squeetinger. 5/15/149'. D/O co. #/30 min. O 36' & set @ set @ 3218'	0 bbls FW. Lead 2, 4% SMS. Lead- (115 bbls FW. LM (Adrienne Brumley) te. CBL show TOC @ choot 2 squeeze czed w/150 sx 05 RU BWWC cment from 2149' K. RIH w/bit & 63261' TOL @ 2831' w/SN @ 3193'
Scavenger cement – 9 sx (27 cf – 5 bbl slurry), Type III w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM 300 sx (703 cf – 125 bbl slurry) Premium Lite Type III w/3% CaCl2, .25#/sx Celloflake, .2% FL-52. Bumped plug @ 0400 hrs 5/3/05. Never circ to surface. ND BOP, RDMO, Rig released 5/3/05. 5/10 about squeeze since 7" didn't circ. to surface. Dale Gall w/BR took logs to BLM and received approx 2280' (Ojo top @ 2210'). Blockage @ 1480'. 5/12/05 MIRU Aztec #469. RU BJ & Black Warrior WL. PT –OK. PT 7" casing to 2500#/15 min. holes. RIH w/cement retainer & set @ 2190'. Spot 6 bbls cement to end of tbg. Sting into cement rower from 11 cement w/1% Cacl2, ½#/sx Celloflake, .2% FL-52. Squeeze to 1750 psi. Shut-in. POH w/s aran CBL from 2149' – 1300'. TOC @ 1600'. RD BWWC. NU, TIH w/ bit & tagged cement @ 2.2190'; D/O retainer @ 2190'. Drilled to 2230'. Fell out @ sqz holes. Circ. hole. PT casing to 1000 D/O cement from 2883' to 3261'. Circ. Hole. RIH w/12 jts. 5-1/2", 15.5#, J-55 pre-perf'd liner @ 27.52' overlap). Perfs @ 2919' – 2941', 3026' – 3130'; 3152' – 3174'. TIH w/2-3/8" 4.7#, J-55 tbg & 102 jts). ND BOP, NU WH. 5/23/05 RIH w/pump & rods. Spaced out & PT tbg & pump to 500# - 14. I hereby certify that the foregoing is true and correct.	Good test. Setainer. Squetinger. 5/15/149'. D/O co. #/30 min. O 36' & set @ set @ 3218' OK. RD & r	0 bbls FW. Lead 2, 4% SMS. Lead- 115 bbls FW. LM (Adrienne Brumley) 2. CBL show TOC @ 2. Choot 2 squeeze 2. Ced w/150 sx 2. SRU BWWC 2. Cement from 2149' 2. K. RIH w/bit & 2. Cell TOL @ 2831' 2. W/SN @ 3193' 2. Celeased rig 5/23/05
Scavenger cement – 9 sx (27 cf – 5 bbl slurry), Type III w/3% CaCl2, .25#/sx Celloflake, 5#/sx LCM 300 sx (703 cf – 125 bbl slurry) Premium Lite Type III w/3% CaCl2, .25#/sx Celloflake, .2% FL-52. Bumped plug @ 0400 hrs 5/3/05. Never circ to surface. ND BOP, RDMO, Rig released 5/3/05. 5/10 about squeeze since 7" didn't circ. to surface. Dale Gall w/BR took logs to BLM and received approx 2280' (Ojo top @ 2210'). Blockage @ 1480'. 5/12/05 MIRU Aztec #469. RU BJ & Black Warrior WL. PT –OK. PT 7" casing to 2500#/15 min. holes. RIH w/cement retainer & set @ 2190'. Spot 6 bbls cement to end of tbg. Sting into cement rType III cement w/1% Cacl2, ½#/sx Celloflake, .2% FL-52. Squeeze to 1750 psi. Shut-in. POH w/s & ran CBL from 2149' – 1300'. TOC @ 1600'. RD BWWC. NU, TIH w/ bit & tagged cement @ 2-2190'; D/O retainer @ 2190'. Drilled to 2230'. Fell out @ sqz holes. Circ. hole. PT casing to 1000 D/O cement from 2883' to 3261'. Circ. Hole. RIH w/12 jts. 5-1/2", 15.5#, J-55 pre-perf'd liner @ 27 (52' overlap). Perfs @ 2919' – 2941', 3026' – 3130'; 3152' – 3174'. TIH w/2-3/8" 4.7#, J-55 tbg & (102 jts). ND BOP, NU WH. 5/23/05 RIH w/pump & rods. Spaced out & PT tbg & pump to 500# -	Good test. Setainer. Squetinger. 5/15/149'. D/O co. #/30 min. O 36' & set @ set @ 3218' OK. RD & r	0 bbls FW. Lead 2, 4% SMS. Lead- (115 bbls FW. LM (Adrienne Brumley) te. CBL show TOC @ choot 2 squeeze ezed w/150 sx 05 RU BWWC tement from 2149' K. RIH w/bit & 3261' TOL @ 2831' w/SN @ 3193' eleased rig 5/23/05