## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells	
7005 JUN 21	PM 1 18 5. Lease Number
Type of Well RECE	NMSF-078504
Type of wen	o. naqan, an or
GAS 070 FARMI	NGTON HM Tribe Name
	7. Unit Agreement Name
Name of Operator	San Juan 32-9 Unit
BURLINGTON	
RESCURCES OIL & GAS COMPANY LP	ione 3
<u> </u>	8. Well Name & Number
Address & Phone No. of Operator	
PO Box 4289, Farmington, NM 87499 (505) 326-9700	San Juan 32-9 Unit #286S 9. API Well No.
10 DOX 1205, 1 distinguish, 11.11 6 / 175 (505) 520 7 / 00	
Location of Well, Footage, Sec., T, R, M	30-045-32520
Sec., TN, RW, NMPM	10. Field and Pool
	Basin Fruitland Coal
Unit P (SESE) 1045' FSL & 1095' FEL, Sec. 14, T32N, R10W NMPM	•
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  Type of Submission	11. County and State San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report
Type of Submission  Notice of Intent  Recompletion  X Subsequent Report  Casing Repair  Water Shut off	San Juan Co., NM REPORT, OTHER DATA
Type of Submission  Notice of Intent  Recompletion  X Subsequent Report  Type of Action  Abandonment Recompletion New Construction Plugging Non-Routine Fracturing	San Juan Co., NM REPORT, OTHER DATA
Type of Submission  Notice of Intent  Recompletion  X Subsequent Report  Casing Repair  Water Shut off	San Juan Co., NM REPORT, OTHER DATA
Type of Submission  Notice of Intent  Abandonment  Recompletion  X Subsequent Report  Plugging Casing Repair  Final Abandonment  Altering Casing Conversion to Injection	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550
Type of Submission  Notice of Intent  Abandonment Recompletion New Construction New Constru	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550
Type of Submission  Notice of Intent  Abandonment  Recompletion  New Construction  Non-Routine Fracturing  Casing Repair  Final Abandonment  Altering Casing  Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'.  G and set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl spps Cell-o-flake. Followed w/ 308sxs(394cu-70bbls) Type 3 lead cement w/ 39/26/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550
Type of Submission  Notice of Intent  Abandonment  Recompletion  New Construction  Non-Routine Fracturing  Casing Repair  Water Shut off  Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'. G and set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl steps Cell-o-flake. Followed w/ 308xsx(394cu-70bbls) Type 3 lead cement w/ 39/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed of D/ROW Process  I hereby certify that the foregoing is true and correct.	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550 wellhead. PT BOP ok. PT csg 600# 30 min ok.
Type of Submission  Notice of Intent  Abandonment  Recompletion  New Construction  Non-Routine Fracturing  Casing Repair  Water Shut off  Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'. G and set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl steps Cell-o-flake. Followed w/ 308xsx(394cu-70bbls) Type 3 lead cement w/ 39/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed of D/ROW Process  I hereby certify that the foregoing is true and correct.	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550 wellhead. PT BOP ok. PT csg 600# 30 min ok.
Type of Submission Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Water Shut off Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'. Gand set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl stops Cell-o-flake. Followed w/ 308sxs(394cu-70bbls) Type 3 lead cement w/ 30's 6/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed to PD/ROW Process  I hereby certify that the foregoing is true and correct.  Amanda Sandoval Title Regulation  Amanda Sandoval Title Regulation	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550 wellhead. PT BOP ok. PT csg 600# 30 min ok.
Type of Submission  Notice of Intent  Abandonment  Recompletion  New Construction  Plugging  Casing Repair  Water Shut off  Altering Casing  Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'. G and set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl spps Cell-o-flake. Followed w/ 308sxs(394cu-70bbls) Type 3 lead cement w/ 39/6/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed and the complete of the complete	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550 wellhead. PT BOP ok. PT csg 600# 30 min ok.
Type of Submission Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Water Shut off Conversion to Injection  Describe Proposed or Completed Operations  7/05 MIRU Bearcat #4. Spud 2 1/4" @ 00:30 6/17/05. Drilling ahead to 457'. Gand set @ 451'. Pumped pre flush 4 bbls H2O. Pumped 11sxs (26cu – 5bbl stops Cell-o-flake. Followed w/ 308sxs(394cu-70bbls) Type 3 lead cement w/ 30's 6/18/05. Circulated 33bbls of cement to reserve pit. WOC. NUBOP. Installed to PD/ROW Process  I hereby certify that the foregoing is true and correct.  Amanda Sandoval Title Regulation  Amanda Sandoval Title Regulation	San Juan Co., NM  REPORT, OTHER DATA  X Other – Spud Report  Circulate hole. Run 10 jts of 9 5/8" 32# H-40 STC slurry) Type 3 scavenger cement with 3% CaCl2, % CaCl2, .25pps Cell-o-flake. Plug down @ 1550 wellhead. PT BOP ok. PT csg 600# 30 min ok.