

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
~~14-08-0001-12395~~ NM-14237

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - (Other instructions on reverse side)

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

PNM Gas Services

3a. Address

87158

3b. Phone No. (include area code)

414 Silver Ave., Albuquerque, NM

505-241-4527

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

625 Ft. from North Line & 1,420 Ft. from West Line
Sec. 20, Township 15-N, Range 1-E

7. If Unit or CA/Agreement, Name and/or No.

Las Milpas Gas Storage

8. Well Name and No.

San Ysidro

9. API Well No.

6

10. Field and Pool, or Exploratory Area

Wildcat

11. County or Parish, State

Sandoval, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☒ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal


☐ Water Shut-Off

☐ Well Integrity

☐ Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

SEE ATTACHED.



020 FACSIMILE
RECEIVED
JUN 23 PM 4 02

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

JOEL LEVINE

Title SENIOR ENGINEER

Signature

Joel Levine

Date

5-20-2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Jim Lovato

Title

Petr. Eng.

Date

6/27/05

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NMOC
FARMING

FORM 3160-5
LAS MILPAS GAS STORAGE SAN YSIDRO WELL #6
SANDOVAL COUNTY, NEW MEXICO
625 FT. FROM NORTH LINE & 1420 FEET FROM WEST LINE
SEC. 20, TOWNSHIP 15-N, RANGE 1-E
LEASE SERIAL NUMBER 14-08-0001-12395

PNM GAS SERVICES
414 SILVER AVE SW.
ALBUQUERQUE, NEW MEXICO 87158
(505)-241-4527

SUNDRY NOTICE:

#13: AS PURSUANT OF NMOCD ADMINISTRATIVE ORDER SWD-973:

- PNM WILL INJECT PRODUCED WATER FOR DISPOSAL PURPOSES INTO THE MESITA BLANCA MEMBER OF THE YESO FORMATION THROUGH PERFORATIONS OF 2,260 FEET TO 2,280 FEET AND THROUGH PLASTIC COATED TUBING SET WITH A PACKER WITHIN 100 FEET OF THE TOP OF THE INJECTION INTERVAL AT 2,160 FEET.
- AS PREPARATION FOR INJECTION, PNM WILL SUEEZE OFF THE CURRENT PERFORATIONS AT 2,208 FEET TO 2,228 FEET, DRILL OUT AND PRESSURE TEST THE SQUEEZED PERFORATIONS
- PNM WILL PERFORATE THE LOWERMOST POROSITY INTERVAL OF THE MESITA BLANCA, LOCATED FROM 2,260 FEET TO 2,280 FEET AT 4 SHOTS PER FOOT
- INJECTION PACKER (EITHER G-TYPE TENSION OR INFLATABLE) SHALL BE PLACED AT 2,160 FEET
- 2,260 FEET OF PLASTIC COATED SPEC TK99 2 3/8" J-55 WILL BE PLACED IN THE WELL
- THE CASING SHALL BE PRESSURE TESTED FROM THE SURFACE TO THE PACKER SETTING DEPTH TO ASSURE CASING INTEGRITY

Jul Leveiro