Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-013
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELL		SF - 077952		
Do not use this form for proposals to drill or to re-entering abandoned well. Use Form 3160-3 (APD) for such proposals.			6. Iffindian, Allottee or Tribe Name	
avanaonea weu. Use Form 3100-3 (APD) for such	proposus.	7. If/Unit or CA/A	greement, Name and/or No.	
SUBMIT IN TRIPLICATE - Other instructions on reverse side (				
MOVE VENTURED THE				
1. Type of Well			8. Well Name and No.	
☐ Oil Well ☐ Gas Well ☐ Other		Angel Peak 24 #9S		
2. Name of Operator Kukui Operating Company		9. API Well No. 30-045-32433		
3a. Address 3b. Phone No. (include area code)		10. Field and Pool, or Exploratory Area		
7415 East Main St. Farmington, NM 87402 (505) 327-4892		Basin Fruitland Coal		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			, State	
2490' FNL & 1870' FEL Sec. 24 , T27N, R10W			w Mexico	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION			
☑ Notice of Intent ☐ Acidize ☐ Deep	en Production (	Start/Resume)	Water Shut-Off	
v	ure Treat Reclamation	Ē	Well Integrity	
	Construction		Other SEE BELOW	
	and Abandon Temporarily Back Water Dispo			
I. Describe Proposed or Completed Operation (clearly state all pertinent details, inclu				
shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)  [1/26/05 Spud 8 ¾" surface hole. Drilled to 125'. Ran 3 jts. (133.82') of 7" 20#, J-55, ST&C casing and set at 143'KB.  Cemented with 125 sx (160 cu.ft.) of Type III with 3% CaCl₂ and ¼ #/sk celloflake.  Circulated 5.0 bbls. of good cement to the surface. Hole was staying full.  1/27/05 Nippled up the BOP and pressure tested the casing to 600psi.  1/31/05 TD well 6 ¼" hole at 2215' KB. Ran 51 jts (2182.44') of 4 ½", J-55, 10.5#, ST&C new casing and landed at 2190.44' KB.  Insert float at 2168' KB. Cemented with 220 sx (513 cu.ft.) of Type III 2% SMS cement with ¼/sk celloflake and 5#/sk gilsonite, followed by 100 sx (140 cu.ft.) of Type III with ½#/sk celloflake, 2% CaCl2 and 5# sk gilsonite. Bumped plug to 1500 psi. Circulation erratic throughout job, but never lost circulation completely. Did not circulate cement to surface.  TOC @ 975' by T5  14. I hereby certify that the foregoing is true and correct				
Name (Printed/Typepl)				
Gwen Brozzo/	Title Production	Clerk		
Signature Museum	Date July 27, 20	005		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE				
		ACC	EPTED FOR RECORD	
Approved by	Title		Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operation thereon.	Office		AUG 0 1 2005	
Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person States any false, fictitious or fraudulent statements or representations as to any matter within its	knowingly and willfully to make any de jurisdiction.	partment or agency <b>5/1A</b> <b>BY</b>	MINION LIEED OFFICE	