This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 evised June 10, 2003

Operator Williams Production Co. Lease Name Rosa Unit Well No. 159

Location Of Well: Unit Letter O Sec 19 Twp 31N Rge 5W API # 30-0392759700

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod.,,, (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	MESA JERDE	G43	Flow	TBG
Lower Completion) akota	Q45	FLOW	TBG.

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	1000 7-8-05	96·HUS	Ta55 C. 253	YES
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	1000 7.8-05	96 HUS	T. 247	YES

Flow Test No. 1

Commenced a	t (hour, date)*	1000 7-1	2-05	Zone producing (Up	oper or Lower):	LOWER.	
Time	Lapsed Time	Pr	essure	Prod. Zone	Remarks		
(Hour, Date)	Since*	Upper Compl.	Lower Compl	l. Temp.			
7-13-05	24 405	T-245 C-241	T. 240	84°	LIME PRESS. THAN NORM	60 PSI HIGHER	7
7.14.05	48HIZ 35WN	T- 236 C- 240	T- 139	89°	LINE TRESS		14
7-15-05	72 Ha 35 min	T 240 C 238	T 152	89°	NORMA!	OPERATION	1.
7-18-05	144 HIL 30min	T. 238 C- 234	T- 138	86	u	· ·	7
1030 7-19-05	1681412 30 min	T- 137 C- 234	T- 154	89.	•	*	6
163°7-26.05	19 den 30 ms	T- 237 C- 234	+- 155	93	Le		5

Production rate during test

Oil:	BOPD	based on	_Bbls. In	Hrs	Grav.	GOR
Gas:	71	MCFPD; Test thru (Orifice or Meter):	ORFICE		

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				, ,
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				, i

(Continue on reverse side)

Flow Test No. 2

mmenced at (hour, date)**				Zone producing (Upper or Lower):		
Time our, Date)	Lapsed Time Since**	Upper Compl.	essure Lower Compl.	Prod. Zone Temp.	Remarks	,
	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7					
	,					
	The state of the s					
arks:	BOPD based		Bbls. In	Hrs	Grav	GOR
eby certify	AUG	- 8 2005	ned is true and cor	mplete to the best Operator	of my knowledge MLL/4MS PiziX	e. Daetron Co.
H.	l Conservation D	weve		By TERR Title 52	MILLAMS ARX EY GEMEL TECK.	33.4
DEFUTY OIL & GAS INSPECTOR, DIST.			E-mail Address			
, ·		Northwee	New Mexico Packer L	Date 7.7	10-05	,

A packer leakage test shall be commenced on each multiply leted well within seven days after actual completion of the well, and lly thereafter as prescribed by the order authorizing the multiple letion. Such tests shall also be commenced on all multiple letions within seven days following recompletion and/or chemical cture treatment, and whenever remedial work has been done on a luring which the packer or the tubing have been disturbed. Tests also be taken at any time that communication is suspected or when sted by the Division.

least 72 hours prior to the commencement of any packer leakage ne operator shall notify the Division in writing of the exact time the to be commenced. Offset operators shall also be so notified.

e packer leakage test shall commence when both zones of the dual etion are shut-in for pressure stabilization. Both zones shall remain n until the well-head pressure in each has stabilized, provided /er, that they need not remain shut-in more than seven days.

or Flow Test No. 1, one zone of the dual completion shall be ced at the normal rate of production while the other zone remains 1. Such test shall be continued for seven days in case of a gas well 4 hours in the case of an oil well. Note: if, on an initial packer te test, a gas well is being flowed to the atmosphere due to the lack peline connection the flow period shall be three hours.

ollowing completion of Flow Test No. 1, the well shall again be 1, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).