

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No. **2005 1916-078110 PM 1 37**

6. If Indian, Allotted or Tribe Name

RECEIVED

070 FARMINGTON NM

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal I Com #9

9. API Well No.

30-045-31789

10. Field and Pool, or Exploratory Area

Harper Hill Fruitland Sand PC

11. County or Parish, State

San Juan, New Mexico

1. Type of Well

☐

Oil
Well

☒

Gas
Well

☐

Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1170' FNL & 2440' FWL (NENW)

Unit C, Sec. 12, T29N, R14W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

TYPE OF ACTION

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☒

Other

TD, production casing

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection


☐

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Pressure test casing to 3500#, held. Run GR-CCL-CNL logs. Perforate Fruitland Sand from 999'-1006', 1012'-1014', 1033'-1037' & 1092'-1101' & Pictured Cliffs Sand from 1129'-1136' w/4 spf (total 116 shots). Acidize w/900 gals 15% HCL. Frac w/141,840# 20/40 Brady sand and 74,130 gals AquaSafe X-20 gel.



14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Vice-President

Date

08/03/2005

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

AUG 05 2005

FARMINGTON FIELD OFFICE
BY *JB*