Form 3160-5 (August 1999)

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Expires: November 30, 2000 AM 11 3 Rease Serial No. The

SUNDRY NOTICES AND REPORTS ON WELL Do not use this form for proposals to drill or to re-en	ter an 6. If Indian, Allottee or Tribe Name
abandoned well. Use Form 3160-3 (APD) for such pre	pposals. RECEIVED
SUBMIT IN TRIPLICATE - Other instructions on reverse	
Type of Well     ☐ Oil Well     ☐ Gas Well     ☐ Other	8. Well Name and No. Angel Peak 1 #20S
2. Name of Operator	9. API Well No. 30-45-32431
Kukui Operating Company  3a. Address  3b. Phone No. (include	area code) 10. Field and Pool, or Exploratory Area
7415 East Main St. Farmington, NM 87402 (505) 327-4892  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal 11. County or Parish, State
1980' FSL & 1050' FEL Sec. 1, T27N, R10W	San Juan, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION
✓ Notice of Intent       ☐ Acidize       ☐ Deepen         ☐ Alter Casing       ☐ Fracture         ☐ Subsequent Report       ☐ Casing Repair       ☐ New Con	
☐ Change Plans ☐ Plug and ☐ Final Abandonment Notice ☐ Convert to Injection ☐ Plug Back	
13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, A Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)	
03/08/05 Spud surface hole (8-3/4", Varel, L116-RR). Drilled to 145' and ran 3jts (133.29') of 7", 20#, ST&C casing and set at 139'KB.  Cemented with 66 sx (85 cu. ft.) of type III with 3% CaC12 and 1/4 #/sk celloflake. Circulated 5.0 bbls of good cement to surface.	
03/09/05 Nippled up the BOP and pressure tested the casing and BOP to 600 psi 03/12/05 TD well at 2480' KB (6-1/4", Varel)	
03/13/05 Ran 63 jts (2446.59') of 4-1/2", 10.5#, J-55, ST&C new casing and landed at 2455' KB. The insert float is at 2434' KB. Cemented with 275 sx (638 cu. ft.) of Type III with 2% SMS, 1/4# sk celloflake and 5# gilsonite, followed by 100sx (140 cu.ft.) of Type III with 2% CaC12, 1/4 # sk celloflake and 5# gilsonite. Bumped plug to 1500 psi. Did not circulate cement. Will run a cement bond log.	
14. I hereby certify that the foregoing is true and correct	The life of the li
Name (Printed/Typed) Gwen Brozzo	Title Production Clerk
Signature William M	Date March 30, 2005  ACCEPTED FOR RECORD
	AL OR STATE OFFICE USE AUG 1 2 7005

which would entitle the applicant to conduct operation thereon.

Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title

Office

