Form 3160-5 (August 1999)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

5.	Lease	Serial	No.
N I	MOEC	704	E (C

I NMSF079456

Λ	
"	
~u	

**SUNDRY NOTICES AND REPORTS ON WELLS** 

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals 1				6. If Indian, Allottee or Tribe Name		
	IPLICATE - Other instru				or CA	Agreement, Name and/or No.
1. Type of Well  Oil Well X Gas Well	Other	0	O FARMINGTO	8. Well N		
2. Name of Operator ConocoPhillips Co.				9. API We	ell No.	
		3b. Phone No. (include (832)486-2463	le area code)	30-039-2		7 ol, or Exploratory Area
4. Location of Well (Footage, Se Sec 20 T24N R3W SWSE	c., T., R., M., or Survey Descriptio 790FSL 1850FEL PPROPRIATE BOX(ES) TO		RE OF NOTICE. R	11. County Rio Arrib NM	ра	
TYPE OF SUBMISSION			PE OF ACTION			
☐ Notice of Intent	☐ Acidize ☐ Alter Casing	☐ Deepen ☐ Fracture Treat	☐ Production (Star☐ Reclamation	/ Resume)		Water Shut-Off Well Integrity
<ul><li>☑ Subsequent Report</li><li>☐ Final Abandonment Notice</li></ul>	<ul><li>☐ Casing Repair</li><li>☐ Change Plans</li><li>☐ Convert to Injection</li></ul>	New Construction Plug and Abandon Plug Back	Recomplete Temporarily Aba Water Disposal	ndon		Other
3. Describe Proposed or Complete	ed Operation (clearly state all pertin	nent details, including esti	mated starting date of ar	y proposed w	ork an	d approximate duration thereof.

all is to deepen directionally or recomplete horizontally, give subsurface locations measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

ConocoPhillips plugged and abandoned this well effective 8/25/05. Daily summary report is attached.



<ul><li>14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)</li><li>Christina Gustartis</li></ul>	Title Regulatory Specialist	
Signature Chie Zustantis	Date 08/29/2005	ACCEPTED FOR RECORD
THIS SPACE FOR FEDERA	L OR STATE OFFICE U	ISE TOTAL CONTROLLED
Approved by	Title	Date AUG 3 0 2005
Conditions of approval, if any, are attached. Approval of this notice does not warracertify that the applicant holds legal or equitable title to those rights in the subject lewhich would entitle the applicant to conduct operations thereon.	ont or Office	FARMING ION FIELD OFFICE BY
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfu fraudulent statements or representations as to any matter within its jurisdiction.	lly to make to any departmen	t or ascenting United States any false, fictitious or

# ConocoPhillips

## Regulatory Summary

### **CHACON HILL 001**

Inactivate, 08/18/2005 00:00

API/Bottom UWI County State/Province Surface Legal Location N/S Dist (ft) N/S Ref E/W Dist (ft) E/W Ref 300392200700 **RIO ARRIBA NEW MEXICO** NMPM-24N-3W-20-O 790.00 1,850.00 Е **Ground Elevation (ft)** 

 Ground Elevation (ft)
 Latitude (DMS)
 Longitude (DMS)
 Spud Date
 Rig Release Date

 6,941.00
 36° 17' 26.376" N
 107° 10' 35.76" W
 05/04/1979
 Rig Release Date

08/18/2005 12:00 - 08/18/2005 15:30

Last 24hr Summary

ROAD RIG & EQUIP TO LOCATION & SPOT.

08/19/2005 08:00 - 08/19/2005 17:30

Last 24hr Summary

HELD SAFETY MEETING. RU RIG. CK PRESS. BH 0#, CSG 80#, TBG 270#. DIG OUT BH, INSTALL 2" VALVE. BLOW DOWN WELL. UNLOAD BOP.SHUT DOWN DUE TO LAND OWNER, PAUL CANDELARIA. APPROVED TO PROCEED. FINISH BLOW DOWN WELL. PUMP 40 BBLS DOWN TBG TO KILL WELL. ND WH. TBG SCREWED INTO BOTTOM OF WH. PU ON TBG, STRIP ON BOP W/ TEST SPOOL. NU BOP & TEST, 250 LOW# - 2500# HI. RU FLOOR. TOH & TALLY 113 STDS 2 3/8" TBG W/SN. SIGNS OF DRILLING MUD ON TBG 850'-3500'. SECURE WELL, SDFN.

### 08/22/2005 08:00 - 08/22/2005 17:30

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS. BH 0#, CSG 10#. BLOW DOWN WELL. PU CSG SCRAPER & TIH TO 7122'. TOH & LD SCRAPER. PU CMT RETAINER, TIH & SET @ 7122'. PT TBG TO 1000#. HELD. STING OUT. LOAD CSG & CIRC CLEAN W/200 BBLS. PT CSG TO 800#. HELD. WHILE MOVING CMT TRK INTO POSITION, FRONT OF TRUCK SUNK INTO SOFT GROUND WHERE OLD PIT HAD BEEN COVERED UP. WAIT ON RU TRK TO PULL OUT. PUMP PLUG #1 W/11 SX,14.52 CU/FT, TYPE III CMT @ 1`4.8 PPG. 7122'-7069'. EST TOC W/ REQUIRED EXCESS 7014'.LD TBG TO 6208'. SIW, SECURE, SDFN.

#### 08/23/2005 08:00 - 08/23/2005 16:00

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS, 0#. LOAD CSG W/2 1/2 BBLS. PUMP PLUG #2 W/17 SX, 22.44 CU/FT, TYPE III CMT @ 14.8 PPG. 6208'-6092'. EST TOC W/REQUIRED EXCESS 6041'. LD TBG TO 4578', STAND BACK 73 STDS, LD STINGER. LOAD CSG & PRESS TEST AGAIN W/BLM REP TO 800#. HELD. RU WIRELINE, RIH & PERF @ 4672' W/3- 3 1/8 HSC. ATT TO ESTAB RATE. 1/8 BPM @ 1400#. APP BY BLM REP TO PUMP BALANCED PLUG & INCREASE CMT. TIH W/73 STDS & 5 JTS. EOT @ 4734. LOAD CSG. PUMP PLUG #3 W/37 SX, 48.84 CU/FT, TYPE III CMT @ 14.8 PPG. 4734'-4572'. EST TOC W/REQUIRED EXCESS 4369'. LD TBG TO 3919'. LOAD CSG. PUMP PLUG #4 W/17 SX, 22.44 CU/FT, TYPE III CMT @ 14.8 PPG. 3919'-3805'. TOC W/REQUIRED EXCESS 3752'. LD TBG TO 3042'. LOAD CSG. PUMP PLUG #5 W/64 SX, 84.48 CU/FT, TYPE III CMT @ 14.8 PPG. 3042'-2462'. EST TOC W/REQUIRED EXCESS 2410'. LD TBG TO 1193', STAND BACK 19 STDS. SECURE, 89.40.

### 08/24/2005 08:00 - 08/24/2005 16:00

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS, 0#. RU WIRELINE, RIH & TAG TOC PLUG #5 @ 2390'. PUH & PERF @ 1278' W/ 3- 3 1/8 HSC. POOH. ESTAB RATE @ 1 1/2 BPM @ 500#. PU DHS CMT RET, TIH & ATT TO SET @ 1224'. WOULD NOT SET. TOH & LD CMT RET. APPROVED BY BLM TO SQUEEZE PLUG WITHOUT CMT RET & WOC. TIH TO 1319'. LOAD CSG. PUMP PLUG # 6 W/51 SX, 67.32 CU/FT, TYPE III CMT @ 14.8 PPG. 1319'-1178'. EST TOC W/REQUIRED EXCESS 1110'. LD ALL TBG. SQUEEZED 29 SX OUTSIDE, LEFT 22 SX INSIDE. SIW. WOC. RU WIRELINE, RIH, TAG TOC PLUG #6 @ 1132'. PUH & PERF @ 356'. ESTAB RATE @ 2 BPM @ 500# & CIRC CLEAN. PUMP PLUG #7, SURF PLUG, W/126 SX, 166.3 CU/FT, TYPE III CMT @ 14.8 PPG. 356'-SURF. CIRC GOOD CMT OUT BH. SIW. RD FLOOR. ND BOP. DIG OUT & CUT OFF WH. CMT IN CSG & ANNULUS DOWN 3'. TOP & INSTALL DRY HOLE MARKER W/20 SX TYPE III CMT @ 14.8 PPG. SECURE LOCATION. SDFN.

### 08/25/2005 08:00 - 08/25/2005 00:00

Last 24hr Summary

HELD SAFETY MEETING. RD RIG. CUT OFF ANCHORS. CLEAN LOCATION. MOL. WELL P&A'D. FINAL REPORT.