Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 2000

Expires Novem	ber 30, 2
Lease Serial No.	

105	AU	NME	-0786731	59
900	.,			

abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian		ttee or Tribe Name
	RIPLICATE - Other instruc	tions on reverse sid	e 070.			Agreement, Name and/or No.
1. Type of Well  Oil Well X Gas Well	☐ Other			8. Well Na		
2. Name of Operator ConocoPhillips Co.				Schlosse 9. API We		N Federal #4
Ba. Address P.O. Box 2197, WL3-6081 Houston Tx 77252  3b. Phone No. (include area code) (832)486-2463				30-045-0		ol, or Exploratory Area
4. Location of Well (Footage, S Sec 34 T28N R11W NEN			Basin Da 11. County San Juar	or Par		
12 CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE DI	NM EDORT OF	В ОТ	TIED DATA
TYPE OF SUBMISSION	TROTATILE BOX(ES) TO				<del>K 01</del>	HER DATA
Notice of Intent  Subsequent Report  Final Abandonment Notice	☐ Alter Casing [☐ Casing Repair	Deepen	Reclamation Recomplete	ŕ		Water Shut-Off Well Integrity Other
— Final Adandonment Notice	Convert to Injection	Plug Back	Water Disposal			
3. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)						
ConocoPhillips plugged a	nd abandoned this well effo	ective 8/15/05. Daily si	ummary report	is attache	ed.	
			SEP	17232 2005 EIVED NS. DIV. T. 8	267.89 W	

San Carlotte San San Carlotte

			01 11 91 51 VI
<ul><li>14. I hereby certify that the foregoing is true and correct Name (<i>Printed/Typed</i>)</li><li>Christina Gustartis</li></ul>	Title Reg	ulatory Special	iist
Signature Chris Dustuty	Date 08/2	9/2005	
THIS SPACE FOR	FEDERAL OR	STATE OFFICE	EUSE ACCEPTED FOR MECCAD
Approved by		Title	Data 3 0 2005
Conditions of approval, if any, are attached. Approval of this notice doe certify that the applicant holds legal or equitable title to those rights in the which would entitle the applicant to conduct operations thereon.	es not warrant or the subject lease	Office	FARMINGTON FIELD OFFICE BY
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly fraudulent statements or representations as to any matter within its jurisd	and willfully to n	nake to any departn	ment or agency of the United States any false, fictitious of

# ConocoPhillips

## **Regulatory Summary**

## SCHLOSSER WN FEDERAL 4

Inactivate, 08/09/2005 00:00 API/Bottom UWI State/Province County Surface Legal Location N/S Dist (ft) N/S Ref E/W Dist (ft) E/W Ref **NEW MEXICO** 300450705500 SAN JUAN NMPM-28N-11W-34-A 1.070.00 1.130.00 Ν Ε Ground Elevation (ft) Latitude (DMS) Longitude (DMS) **Spud Date** Rig Release Date 5,665.00 36° 37' 22.476" N 107° 59' 7.8" W 10/03/1964

08/09/2005 13:30 - 08/09/2005 16:30

Last 24hr Summary

HELD SAFETY MEETING. ROAD RIG & EQUIP TO LOCATION & SPOT. HELD SAFETY MEETING RU RIG. SECURE, SDFN.

08/10/2005 10:00 - 08/10/2005 06:30

Last 24hr Summary

ROAD PUMPTRUCK & DOG HOUSE TO LOCATION. HELD SAFETY MEETING. CK PRESS. TBG 300#, CSG 250#, BH 30#. RU BLOW DOWN LINES, BLOW DOWN WELL. CAUGHT PISTON. PUMP 30 BBLS DOWN TBG TO KILL WELL. ND WH, NU BOP & TESTED. 250# LOW - 2250# HI. TESTED OK. RU FLOOR. PU ON TBG, REMOVE HANGER. TOH W/99 STDS, 5885' & LD 7 JTS, SN & MULESHOE. 205 JTS TOTAL 2 3/8" TBG, 6093'. PT BH. PUMPED 2 BBLS, 47', PRESS TO 300# & HELD. RU WL & RIH W/ GAUGE RING TO 5983'. TIGHT SPOT @ 3606'. CLEANED IT UP. POOH. TIH W/ CMT RET. CMT RET STOPPED @ 3606'. SECURE, SDFN.

### 08/11/2005 06:30 - 08/11/2005 00:00

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS. CSG 40#, BH 0#. BLOW DOWN WELL. PUMP 30 BBLS DOWN CSG TO KILL WELL. TIH W/ 50 STDS. PUMP 10 BBLS, DROP STANDING VALVE. PUMP 20 BBLS, ATT TO PRESS TEST TBG. FAILED. TOH. RU DRIFTING TOOL, TIH DRIFTING EACH STAND. FOUND STANDING VALVE IN STD # 28. LD JT, TOH. PU NEW SN W/ STANDING VALVE & TIH W/ 50 STDS. TEST TBG TO 1000#. TESTED OK. TIH W/ALL TBG. TESTED OK. DRIFTED ALL TBG GOING IN & FOUND 2 BAD JTS. LD TONGS, PU FISHING TOOLS, RIH & RETRIEVE STANDING VALVE. LD TOOLS, PU TONGS. EOT 6094'. PUMP 70 BBLS AHEAD W/ NO CIRC. PUMP PLUG #1 W/40 SX, 52.8 CU/FT, TYPE III CMT @ 14.8 PPG. 6094'-5504'. LD 20 JTS, STAND BACK 24 STDS. SIW, WOC, SECURE, SDFN.

#### 08/12/2005 06:30 - 08/12/2005 16:30

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS, 0#. OPEN WELL. TIH & TAG TOC @ 6080'. LOAD CSG W/ 90 BBLS & ATT TO PRESS TEST. TEST FAILED. PUMPED 1 1/2 BBM @ 300#. PUMP PLUG 1A W/ 40 SX, 52.8 CU/FT, TYPE III CMT @ 14.8 PPG. 6080'-5490'. LD 19 JTS, STAND BACK 24 STDS. SIW, WOC. TIH & TAG TOC @ 5855'. LD TBG TO 5189'. LOAD CSG W/35 BBLS. PRESS TEST CSG TO 500#. HELD OK. PUMP 25 BBLS & CIRC CSG CLEAN. PUMP PLUG #2 W/ 11 SX, 14.52 CU/FT, TYPE III CMT @ 14.8 PPG. 5189'-5086'. EST TOC W/ REQUIRED EXCESS 5027'. LD TBG TO 3164'. LOAD CSG W/2 BBLS. PUMP PLUG #3 W/12 SX, 15.8 CU/FT, TYPE III CMT @ 14.8 PPG. 3164'-3037'. EST TOC W/ REQUIRED EXCESS 2988'. LD TBG TO 2539'. SIW. SECURE, SDFN.

#### 08/15/2005 06:30 - 08/15/2005 16:00

Last 24hr Summary

HELD SAFETY MEETING. CK PRESS, 0#. OPEN WELL. LOAD CSG. PUMP PLUG #4 W/12 SX, 15.8 CU/FT, TYPE III CMT @ 14.8 PPG. 2539'-2428'. EST TOC W/REQUIRED EXCESS 2363'. LD TBG TO 1616'. LOAD CSG. PUMP PLUG # 5 W/32 SX, 42.2 CU/FT, TYPE III CMT @ 14.8 PPG. 1616'-1204'. EST TOC W/REQUIRED EXCESS 1144'. LD TBG TO 598'. LOAD CSG. PUMP PLUG #6 W/37 SX, 48.8 CU/FT, TYPE III CMT @ 14.8 PPG. 598'-53'. LD TBG TO 60' & REVERSE CSG CLEAN. RU WIRELINE, RIH # PERF @ 50' W/3- 3 1/8 HSC PER BLM REP ON LOC. POOH & RD WL. ESTAB CIRC OUT BH & CIRC CLEAN. PUMP PLUG #7, SURFACE PLUG, W/24 SX, 31.6 CU/FT, TYPE III CMT @ 14.8 PPG. 50'-SURF. CIRC GOOD CMT OUT BH. SIW. WASH UP EQUIP. RD FLOOR & PUMP TRK. ND BOP. DIG OUT & CUT OFF WELL HEAD. CMT IN ANNULUS & CSG FULL. INSTALL DRY HOLE MARKER W/10 SX CMT. RD RIG. CUT OFF ANCHORS. CLEAN LOC. MOL. WELL P&A'D. FINAL REPORT.