RECEIVED

Form 3160-5 (August 2007)

UNITED STATES UNITED STATES DEPARTMENT OF THE INTERIOR DEC 07 2012

FORM APPROVED OMB No. 1004-0137

BUREAU OF LAND MANAGEMENT					Expires: July 31, 2010	
** Farmington Field					5光稿se:Serial No. Janemen. I-149-IND-8473	
SUNDRY NOTICES AND REPORTS ON WELLS					6. If Indian, Allottee or Tribe Name	
Do not use	this form for proposals t	to arılı c	r to re-enter	ran	Į	
abandoned well. Use Form 3160-3 (APD) for such proposals.					Navajo Allotted	
SUBMIT IN TRIPLICATE - Other instructions on page 2. 1. Type of Well					7. If Unit of CA/Agreement, Name and/or No.	
Oil Well X Gas Well Other					Huerfanito Unit 8. Well Name and No.	
					Huerfanito Unit 82P	
2. Name of Operator Burlington Resources Oil & Gas Company LP					9. API Well No. 30-045-35329	
			No. (include area	code)	10. Field and Pool or Exploratory Area	
PO Box 4289, Farmington, NM 87499			(505) 326-9700 Blanco MV/Basin Mancos/Basin		•	
4. Location of Well (Footage, Sec., T.,R,M., or Survey Description)			11. Country or Parish, State			
Surface UNIT E (SWNW), 2600' FNL & 270' FWL, Sec. 25, T27N, R9W					San Juan ,	New Mexico
12. CHECK T	HE APPROPRIATE BOX(ES)	TO IND	CATE NATUR	E OF NO	TICE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION		r"·	TYP	E OF AC	TION	
Notice of Intent	Acidize	Deep	en	P	roduction (Start/Resume)	Water Shut-Off
	Alter Casing	Fract	are Treat	☐ R	eclamation	Well Integrity
X Subsequent Report	Casing Repair		Construction	=	ecomplete	X Other Casing Report
	Change Plans	=	and Abandon	=	emporarily Abandon	
Final Abandonment Notice 13. Describe Proposed or Completed Ope	Convert to Injection	Plug			Vater Disposal	ata duration thorace
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) RCVD DEC 14 '12 PLEASE SEE ATTACHED. OIL CONS. DIV. ACCEPTED FOR PEOPLE.						
					DEC	1 2 2012
PT will be conducted by	Completion Rig. Results &	₹ TOC w	vill appear on	next repo	ort. BY <u>W. K. K.</u>	NFIELD OFFICE am Tambekou
14. I hereby certify that the foregoing is t	rue and correct. Name (Printed/Type	ed)				
DENISE JOURNEY			Title REGULATORY TECHNICIAN			
Signature Denise Journey			12/7/2012 Date			
	THIS SPACE FO	R FEDE		ATE OFF	ICE USE	
Approved by						
]			
Condition of many 1 '6	J A		c.	Title		Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.				Office		

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any

AMENDED

HUERFANITO UNIT 82P 30-045-35329 Burlington Resources Blanco MV/Basin Mancos/Basin DK

7/15/12 MIRU AWS 920. ND WH. NU BOPE. <u>PT 9 5/8</u>" casing to 600#/30 min. Test OK.

7/17/12 TIH w/ 8 3/4" bit, tag cmt @ 197' & DO. Drilled ahead w/ 8 3/4" bit to 3,901' – Inter TD reached 7/18/12. Circ. hole. TIH w/ 92 jts. (82 jts., 20#, ST&C & 5 jts., 23#, LT&C) 7", J-55 casing set @ 3,889'.

7/19/12 RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger, 19 sx (57cf-10bbls=3.02 yld) Prem Lite cement w/ 3% CACL, .25 pps cello-flake, 5 pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 402 sx (856cf-152 bbls=2.13 yld) Prem Lite cement w/ 3% CACL, .25 pps cello-flake, 5 pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 92 sx (127cf-23bbls=1.38 yld) Type III cement w/ 1% CACL, .25 pps cello-flake, & 0.2% FL-52. Drop plug & displaced w/ 156 bbls FW. Bump plug w/ 2005#. Plug down @ 08:52 hrs on 7/19/12. Circ, 55 bbls cmt to surface. RD cmt. WOC. PT 7" casing to 1500#/30 min. @ 19:00 hrs on 7/19/12, Test OK TIH w/ 6 ¼" bit, tag cmt @ 3,848' & DO. Drilled ahead w/ 6 ¼" bit to 6,754' (TD), TD reached 7/22/12.

7/23/12 Circ. hole. TIH w/ 162 jts., 4 ½", 11.6#, L-80, LT&C casing, set @ 6,743'. RU to cmt. Pre-flush w/ 10 bbls CW & 2 bbls FW. Pumped scavenger 9 sx (27cf-5bbls=3.02 yld) Prem Lite cement w/ .25 pps cello-flake, 0.3% CD-32, 6.25 pps LCM-1, & 1% FL-52. Tail w/ 213 sx (422cf-75bbls=1.98 yld) Prem. Lite cement w/ .25 pps cello-flake, 0.3% CD-32, 6.25 pps LCM-1, & 1% FL-52. Drop plug & displaced w/ 105 bbls FW (1st 10 bbls w/ sugar water). Bump plug w/ 1934#. Plug down @ 16:17 hrs on 7/23/12. WOC. RD cmt. ND BOPE. NU WH. RD RR @ 06:00 hrs on 7/24/12.