

OPERATOR: ConocoPhillips CO.
FARMINGTON, NM 87401
PHONE: 599-3400

LOCATION INFORMATION

API NUMBER: 3004535353

WELL NAME OR PIPELINE SERVED: ELLIOTT GAS COM H 1C

LEGAL LOCATION: 26 30N 09W

INSTALLATION DATE:

2/8/2013

PPCO. RECTIFIER NO.: **10617W**

ADDITIONAL WELLS:**TYPE OF LEASE:****LEASE NUMBER:**

FEE

GROUP BED INFORMATION

TOTAL DEPTH: **300'**

CASING DIAMETER: 8"

TYPE OF CASING: **PVC**

CASING DEPTH: 40'

CASING CEMENTED

7 ANODE DEPTH:

BOTTOM ANODE DEPTH:

ANODE DEPTHS: 167, 179, 191, 203, 215, 227, 239, 251, 263, 275

AMOUNT OF COKE: 50 BAGS

WATER INFORMATION

WATER DEPTH (1): 60' 300'

WATER DEPTH (2):

GAS DEPTH:

CEMENT PLUGS:

RCVD FEB 20 '13
OIL CONS. DIV.
DIST. 3

OTHER INFORMATION

TOP VENT PERFORATIONS: 160'

VENT PIPE DEPTH: 300'

REMARKS:

COKE DEPTH 150"

* LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

ca

RECTIFIER MFG: _____
MODEL: _____
SERIAL #: _____
C: _____ A-DC: _____

WELL LOG										ANODE PLACEMENT			
DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	ANODE NO.	ANODE DEPTH	AMPS W/O COKE	AMPS W/ COKE
0	SAND	12.70		CASING	250	SHALE		5.60	#3-251	1	275	5.00	4.60
5	SAND			CASING	255	SHALE		5.50		2	263	5.50	10.80
10	SAND			CASING	260	SHALE		5.70		3	251	4.70	11.00
15	SAND			CASING	265	SHALE		5.70	#2-263	4	239	4.00	9.30
20	SAND			CASING	270	SHALE		5.20		5	227	1.80	6.10
25	SAND			CASING	275	SHALE		5.10	#1-275	6	215	2.40	6.00
30	SAND			CASING	280	SANDY SHALE		5.10		7	203	2.30	5.50
35	SAND			CASING	285	SANDY SHALE		5.50		8	191	4.40	8.50
40	SAND			CASING	290	SANDY SHALE				9	179	1.80	9.90
45	SAND				295	SANDY SHALE				10	167	5.40	10.10
50	SANDSTONE				300	SHALE				11			
55	SANDSTONE				305					12			
60	SANDSTONE				310					13			
65	SANDSTONE				315					14			
70	SANDSTONE				320					15			
75	SANDSTONE				325					16			
80	SANDSTONE		1.90		330					17			
85	SANDSTONE		1.70		335					18			
90	SANDY SHALE		1.60		340					19			
95	SANDY SHALE		1.70		345					20			
100	SANDY SHALE		1.70		350					21			
105	SANDY SHALE		2.40		355					22			
110	SANDY SHALE		2.80		360					23			
115	SANDY SHALE		3.00		365					24			
120	SANDY SHALE		2.50		370					25			
125	SANDY SHALE		2.70		375								
130	SANDY SHALE		2.90		380								
135	SANDY SHALE		3.80		385								
140	SANDY SHALE		4.70		390								
145	SANDY SHALE		5.20		395								
150	SANDY SHALE		6.10		400								
155	SANDY SHALE		5.80		405								
160	SHALE		5.10		410								
165	SHALE		5.40	#10-167	415								
170	SANDY SHALE		5.00		420								
175	SANDY SHALE		4.80		425								
180	SANDY SHALE		4.80	#9-179	430								
185	SANDY SHALE		4.60		435								
190	SHALE		4.00	#8-191	440								
195	SHALE		3.30		445								
200	SHALE		3.00		450								
205	SHALE		2.80	#7-203	455								
210	SHALE		2.60		460								
215	SHALE		2.30	#6-215	465								
220	SHALE		2.40		470								
225	SHALE		2.20	#5-227	475								
230	SHALE		2.00		480								
235	SHALE		2.00		485								
240	SHALE		2.40	#4-239	490								
245	SHALE		5.60		495								
										GROUND BED RESISTANCE			
										TOTAL VOLTS: 12.70			
										TOTAL AMPS: 33.40			
										0.38 OHMS			
										SITE ELEVATION: 5788'			
										WATER CONDUCTIVITY:			
										COKE LEVEL: 150'			
										EXTRA CASING USED: 20'			
										ADDITIONAL COMMENTS:			
										DRILL FROM 60' TO 300' WITH WATER INJECT			