

RECEIVED

Form 3160-5
(August 2007)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FEB 22 2013

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

Farmington Field Office

SUNDRY NOTICES AND REPORTS ON WELLS OF LAND MANAGED BY THE BUREAU OF LAND MANAGEMENT
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMNM 89021

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well
 Oil Well Gas Well Other

8. Well Name and No.
Lybrook H32-2306 01H

2. Name of Operator
Encana Oil & Gas (USA) Inc.

9. API Well No.
30-043-21126

3a. Address
370 17th Street, Suite 1700
Denver, CO 80202

3b. Phone No. (include area code)
720-876-5353

10. Field and Pool or Exploratory Area
Lybrook Gallup

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SHL: 1785' FNL and 250' FEL Sec 32, T23N, R6W
BHL: 1785' FNL and 2285' FWL Sec 31, T23, R6W

11. Country or Parish, State
Sandoval, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Encana Oil & Gas (USA) Inc. (Encana) would like to revise the vertical hole size and cement plans for the Lybrook H32-2306 01H well. Encana would like to change the vertical hole size from 8 1/2" to 8 3/4" and increase intermediate cement volume to accommodate the larger hole. Please see attached 10 point drilling plan and wellbore diagram.

RCVD MAR 6 '13
OIL CONS. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)
Amie Weis

Title Drilling Engineer

Signature *Amie Weis*

Date 2-21-13

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by
William Tambekou

Title Petroleum Engineer

Date 02/26/2013

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office FFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

NMOCD A

LOC: Sec 32-T23N-R6W County: Sandoval WELL: Lybrook H32-2306 01H			Encana Natural Gas WELL SUMMARY					ENG: J. Fox/A. 2/21/13 RIG: GLE: 7196 RKBE: 7209	
MWD LWD	OPEN HOLE LOGGING	FORM	DEPTH		HOLE SIZE	CASING SPECS	MW MUD TYPE	DEVIATION INFORMATION	
			TVD	MD					
			60	60'	30	20" 94# 100sx Type I Neat 48.8ppg cmt	Fresh wtr 8.3-9.2		
Surveys After csg is run	None	Nacimiento	20		12 1/4	9 5/8" 36ppf J55 STC TOC @ surface 178 sks Type III Cmt	Fresh wtr 8.4-8.6	Vertical <1°	
Surveys every 500'	No OH logs Mud logger onsite	Ojo Alamo Kirtland Fruitland Coal Pictured Cliffs Ss Lewis Shale Cliffhouse Ss Menefee Fn Point Lookout Ss Mancos Sh KICK OFF PT Mancos Silt Gallup Top	1476 1675 1845 2073 2199 2912 3572 4329 4519 5000 5072 5336		8 3/4	7" 26ppf J55 LTC TOC @ surface 30% OH excess: 578 sks Total. Stage 1 Lead: 231sks Stage 1 Tail: 159sks. Stage 2 Lead: 188sks	Fresh Wtr 8.5-8.8	Vertical <1° KOP 5000 10 deg/100'	
			5544	5720					
		horz target	5573	5903	6 1/8	200' overlap at liner top			
		Base Gallup	5632			6700' Lateral	8.6-9.0 OBM	.25deg updip 5538'TVD TD = 12607' MD	
Surveys every 500' Gyro at CP MWD Gamma Directional	No OH Logs					4 1/2" 11.6ppf SB80 LTC Running external swellable csg packers for isolation of prod string Plan on setting top packer within 100' of intermediate casing shoe	Switch to OBM 8.6-9.0		

- NOTES:**
- 1) Drill with 30" bit to 60', set 20" 94# conductor pipe
 - 2) Drill surface to 500', R&C 9 5/8" casing
 - 3) N/U BOP and surface equipment
 - 4) Drill to KOP of 5000' , 8 3/4" hole size,
 - 5) PU directional tools and start curve at 10deg/100' build rate
 - 6) Drill to casing point of 5720' MD (72deg)
 - 7) R&C 7" casing, circ cmt to surface, switch to OBM
 - 8) Land at 90deg, drill 6700' lateral to 12607', run 4 1/2" liner with external swellable csg packers

Lybrook H32-2306 01H
 SHL: SENE Section 32, T23N, R6W
 1785 FNL and 250 FEL
 BHL: SWNE Section 31, T23N, R6W
 1785 FNL and 2285 FEL
 Sandoval County, New Mexico
 Lease Number: NMNM 089021 & V-1399

**Encana Oil & Gas (USA) Inc.
 Drilling Plan**

1. ESTIMATED TOPS OF GEOLOGICAL MARKERS (TVD)

The estimated tops of important geologic markers are as follows:

<u>Formation</u>	<u>Depth (TVD)</u>
Ojo Alamo Ss.	1476'
Kirtland	1675'
Fruitland Coal	1845'
Pictured Cliffs	2073'
Lewis	2199'
Cliffhouse	2912'
Menefee	3572'
Point Lookout	4329'
Mancos Shale	4519'
Mancos Silt	5072'
Gallup	5336'

The referenced surface elevation is 7196', KB 7209'

2. ESTIMATED DEPTH OF POTENTIAL WATER, OIL, GAS, & OTHER MINERAL BEARING FORMATIONS

<u>Substance</u>	<u>Formation</u>	<u>Depth (TVD)</u>
Gas	Fruitland Coal	1845'
Gas	Pictured Cliffs	2073'
Gas	Cliffhouse	2912'
Gas	Point Lookout	4329'
Oil/Gas	Mancos	4519'

All shows of fresh water and minerals will be reported and protected.

3. PRESSURE CONTROL

- a) Pressure control equipment and configuration will be designed to meet 2M standards.
- b) Working pressure on rams and BOPE will be 3,000 psi
- c) Function test and visual inspection of the BOP will be conducted daily and noted in the IADC Daily Drilling Report.
- d) The Annular BOP will be pressure tested to a minimum of 50 percent of its rated working pressure.
- e) Blind and Pipe Rams/BOP will be tested against a test plug to 100 percent of rated working pressure.
- f) Pressure tests are required before drilling out from under all casing strings set and cemented in place.
- g) BOP controls must be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned.
- h) BOP testing procedures and testing frequency will conform to Onshore Order No. 2.

Lybrook H32-2306 01H

**SHL: SENE Section 32, T23N, R6W.
1785 FNL and 250 FEL**

**BHL: SWNE Section 31, T23N, R6W
1785 FNL and 2285 FEL**

Sandoval County, New Mexico

Lease Number: NMNM 089021 & V-1399

- i) BOP remote controls shall be located on the rig floor at a location readily accessible to the driller. Master controls shall be on the ground at the accumulator and shall have the capability to function all preventers.
- j) The kill line shall be 2-inch minimum and contain two kill line valves, one of which shall be a check valve.
- k) The choke line shall be a 2-inch minimum and contain two choke line valves (2-inch minimum).
- l) The choke and manifold shall contain two adjustable chokes.
- m) Hand wheels shall be installed on all ram preventers.
- n) Safety valves and wrenches (with subs for drill string connections) shall be available on the rig floor at all times.
- o) Inside BOP or float sub shall also be available on the rig floor at all times.

Proposed BOP and choke manifold arrangements are attached.

4. CASING & CEMENTING PROGRAM

The proposed casing and cementing program has been designed to protect and/or isolate all usable water zones, potentially productive zones, lost circulation zones, abnormally pressured zones, and any prospectively valuable deposits of minerals. Any isolating medium other than cement shall receive approval prior to use. The casing setting depth shall be calculated to position the casing seat opposite a competent formation which will contain the maximum pressure to which it will be exposed during normal drilling operations. All indications of useable water shall be reported.

- a) The proposed casing design is as follows:

Casing	Depth	Hole Size	Csg Size	Weight	Grade
Conductor	0-60'	30"	20"	94#	H40, STC New
Surface	0'-500'	12 1/4"	9 5/8"	36#	J55, STC New
Intermediate	0'-5720'MD	8 3/4"	7"	26#	J55, LTC New
Production Liner	5520'-12607'MD	6 1/8"	4 1/2"	11.6#	B80*, LTC New

Casing String				Casing Strength Properties			Minimum Design Factors		
Size	Weight (lb/ft)	Grade	Connection	Collapse (psi)	Burst (psi)	Tensile (1000lb)	Collapse	Burst	Tension
9 5/8"	36	J55	STC	2020	3520	394	1.125	1.1	1.5
7"	26	J55	LTC	4320	4980	367	1.125	1.1	1.5
4 1/2"	11.6	B80	LTC	6350	7780	201	1.125	1.1	1.5

*B80 pipe specifications are attached

Casing design is subject to revision based on geologic conditions encountered.

All casing strings below the conductor shall be pressure tested to 0.22 psi per foot of casing string length or 1,500 psi, whichever is greater, but not to exceed 70 percent of the minimum internal yield. If pressure declines more than 10 percent in 30 minutes, corrective action shall be taken.

- b) The proposed cementing program is as follows:

Top plugs shall be used to reduce contamination of cement by displacement fluid. A bottom plug or other acceptable technique, such as a pre-flush fluid, inner string cement method, etc. shall be utilized to help isolate the cement from contamination by the mud fluid being displaced ahead of the cement slurry.

Lybrook H32-2306 01H

SHL: SENE Section 32, T23N, R6W
1785 FNL and 250 FEL

BHL: SWNE Section 31, T23N, R6W
1785 FNL and 2285 FEL

Sandoval County, New Mexico

Lease Number: NMNM 089021 & V-1399

Casing	Depth	Cement Volume (sacks)	Cement Type&Yield	Designed TOC	Centralizers
Conductor	60'	100sk	Type I Neat 14.8 ppg	Surface	None
Surface	500'	178sk	Type III Cement + 1% CaCl + 0.25lb/sk Cello Flake + 0.2% FL, 14.6ppg, 1.38cuf/sk	Surface	1 per joint on bottom 3 joints
Intermediate	5720'MD	30% open hole excess Stage 1 Lead: 231sks Stage 1 Tail: 159sks Stage 2 Lead: 188sks	Lead: PremLite + 3% CaCl + 0.25lb/sk CelloFlake + 5lb/sk LCM, 12.1ppg 2.13cuf/sk Tail: Type III Cmt + 1% CaCl + 0.25lb/sk Cello Flake 14.5ppg 1.38cuf/sk	Surface	1 per joint for bottom 3 joints, 1 every 3 joints for remaining joints
Production Liner*	5520'-12607'	None – External casing packers	N/A	N/A	N/A

*Production liner clarification: Utilizing external swell casing packer system for zonal isolation will not use cement in the production liner.

Actual volumes will be calculated and determined by conditions onsite. All cement slurries will meet or exceed minimum BLM and New Mexico Oil Conservation Division requirements. Slurries used will be the slurries listed above or equivalent slurries depending on service provider selected. Cement yields may change depending on slurries selected.

All waiting on cement times shall be a minimum of 8 hours or adequate to achieve a minimum of 500 psi compressive strength at the casing shoe prior to drilling out.

5. WELL PLAN & DIRECTIONAL DRILLING PROGRAM

The proposed horizontal well will have a kick off point of 5000'. Directional plans are attached.

Description	Proposed Depth (TVD/MD)	Formation
Horizontal Lateral TD	5538'/12607'	Gallup

Lybrook H32-2306 01H

**SHL: SENE Section 32, T23N, R6W
1785 FNL and 250 FEL**

**BHL: SWNE Section 31, T23N, R6W
1785 FNL and 2285 FEL**

Sandoval County, New Mexico

Lease Number: NMNM 089021 & V-1399

6. DRILLING FLUIDS PROGRAM

a) Surface through Intermediate Casing Point:

Hole Size (in)	Depth (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
30"	0-60' TVD	Fresh Water	8.3-9.2	38-100	4-28
12 1/4"	0-500' TVD	Fresh Water	8.4-8.6	60-70	NC
8 3/4"	500'TVD- 5544'TVD/5720'MD	Fresh Water LSND	8.5-8.8	40-50	8-10

b) Intermediate Casing Point to TD:

Hole Size (in)	MD (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
6 1/8"	5720'-12607'	Synthetic Oil Based Mud	8.6-9.0	15-25	<15

- c) There will be sufficient mud on location to control a blowout should one occur. Mud flow and volume will be monitored both visually and with electronic pit volume totalizers. Mud tests shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.
- d) A closed-loop system will be used to recover drilling fluid and dry cuttings in both phases of the well and on all hole intervals, including fresh water and oil-based operations. Above-ground tanks will be utilized to hold cuttings and fluids for rig operations. A frac tank will be on location to store fresh water. Waste will be disposed of properly at an EPA-approved hazardous waste facility. Fresh water cuttings will be disposed of at Basin Disposal, Inc. and/or Industrial Ecosystems, Inc. The location will be lined in accordance with the Surface Use Plan of Operations.

7. TESTING, CORING and LOGGING

- a) Drill Stem Testing – None anticipated
- b) Coring – None anticipated.
- c) Mud Logging – Mud loggers will be on location from kick off point to TD.
- d) Logging – See Below

Cased Hole:

CBL/CCL/GR/VDL will be run as needed for perforating control

8. ABNORMAL PRESSURES & HYDROGEN SULFIDE

The anticipated bottom hole pressure is +/- 2608 psi based on a 9.0 ppg at 5573' TVD of the landing point of the horizontal lateral. No abnormal pressure or temperatures are anticipated.

No hydrogen sulfide gas is anticipated, however, if H₂S is encountered, the guidelines in Onshore Order No. 6 will be followed.

Lybrook H32-2306 01H

SHL: SENE Section 32, T23N, R6W
1785 FNL and 250 FEL

BHL: SWNE Section 31, T23N, R6W
1785 FNL and 2285 FEL

Sandoval County, New Mexico

Lease Number: NMNM 089021 & V-1399

9. ANTICIPATED START DATE AND DURATION OF OPERATIONS

Drilling is estimated to commence on February 25, 2013. It is anticipated that completion operations will begin within 30 days after the well has been drilled depending on fracture treatment schedules with various pumping service companies.

It is anticipated that the drilling of this well will take approximately 25 days.