

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**CONFIDENTIAL**

FORM APPROVED  
OMB No. 1004-0137  
Expires: July 31, 2010

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.*

**RECEIVED**

MAR 20 2013

**SUBMIT IN TRIPLICATE** -- Other instructions on page 2.

1. Type of Well  
 Oil Well     Gas Well     Other

2. Name of Operator  
Encana Oil & Gas (USA) Inc.

3a. Address  
370 17th Street, Suite 1700  
Denver, CO 80202

3b. Phone No. (include area code)  
720-876-5353

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
SHL: 210' FNL and 667' FWL Sec 6, T23N, R9W  
BHL: 330' FSL and 660' FWL Sec 6, T23N, R9W

5. Lease Section No.  
NM 8005

6. Indian Allottee or Tribe Name  
N/A

7. Unit of CA/Agreement, Name and/or No.  
N/A

8. Well Name and No.  
Good Times D06-2309 01H

9. API Well No.  
30-045-35419

10. Field and Pool or Exploratory Area  
South Bisti-Gallup

11. Country or Parish, State  
San Juan, NM

Farmington Field Office  
Bureau of Land Management

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Encana Oil & Gas (USA) Inc. (Encana) would like to revise the intermediate hole size and cement plans for the Good Times D06-2309 01H well. Encana would like to change the intermediate hole size from 8 1/2" to 8 3/4". Please see attached 10 point drilling plan and wellbore diagram. Drilling is estimated to commence on June 30, 2013.

RCVD MAR 28 '13  
OIL CONS. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)  
Amie Weis

Title Drilling Engineer

Signature *Amie Weis*

Date 3/18/2013

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by  
*William Tambekou*

Title Petroleum Engineer

Date 03/20/2013

Office FFD

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD pr

MWD LWD		OPEN HOLE LOGGING	FORM	DEPTH		HOLE SIZE	CASING SPECS	MW MUD TYPE	DEVIATION INFORMATION
				TVD	MD				
				60	60'		20" 94# 100sx Type I Neat 48.8ppg cmt	Fresh wtr 8.3-9.2	
Surveys After csg is run		None					9 5/8" 36ppf J55 STC  TOC @ surface 178 sks Type III Cmt	Fresh wtr 8.4-8.6	Vertical <1°
Surveys every 500'		No OH logs	Ojo Alamo Kirtland Fruitland Coal Pictured Cliffs Ss Lewis Shale Cliffhouse Ss Menefee Fn Point Lookout Ss Mancos Sh	510 625 905 1247 1404 1981 2582 3658 3826		Stage tool @1300'	7" 26ppf J55 LTC  TOC @ surface 30% OH excess: 517 sks Total Stage 1 Lead: 239 sks Stage 1 Tail: 165 sks Stage 2 Lead: 113 sks	Fresh Wtr 8.5-8.8	Vertical <1°
			KICK OFF PT	4309					
			Mancos Silt	4363					
			Gallup Top	4635					KOP 4309 10 deg/100'
				4854	5029				
Surveys every 500' Gyro at CP MWD Gamma Directional		No OH Logs	horz target Base Gallup Pilot Hole TD	4882 4970 5170	5217		200' overlap at liner top  4165' Lateral	8.6-9.0 OBM	.25deg up dip 4824'TVD TD = 9380' MD
							4 1/2" 11.6ppf SB80 LTC  Running external swellable csg packers for isolation of prod string  Plan on setting top packer within 100' of intermediate casing shoe	Switch to OBM 8.6-9.0	

**NOTES:**

- 1) Drill with 30" bit to 60', set 20" 94# conductor pipe
- 2) Drill surface to 500', R&C 9 5/8" casing
- 3) N/U BOP and surface equipment
- 4) Drill to core point, obtain cores
- 4) Drill to pilot hole TD of 5170' and run OH logs.
- 5) Spot cement kick plug
- 6) Kick off at 4309' and start curve at 10deg/100' build rate
- 7) Drill to casing point of 5029' MD
- 8) R&C 7" casing, circ cmt to surface, switch to OBM
- 9) Land at 90deg, drill 4165' lateral to 9380', run 4 1/2" liner with external swellable csg packers

Good Times D06-2309 01H  
 SHL: NWNW Section 6, T23N, R9W  
 210 FNL and 667 FWL  
 BHL: SWSW Section 6, T23N, R9W  
 330 FSL and 660 FWL  
 San Juan County, New Mexico  
 Lease Number: NMNM 008005

**Encana Oil & Gas (USA) Inc.  
 Drilling Plan**

**1. ESTIMATED TOPS OF GEOLOGICAL MARKERS (TVD)**

The estimated tops of important geologic markers are as follows:

<u>Formation</u>	<u>Depth (TVD)</u>
Ojo Alamo	510'
Kirtland	625'
Fruitland Coal	905'
Pictured Cliffs	1247'
Lewis	1404'
Cliffhouse	1981'
Menefee	2582'
Point Lookout	3658'
Mancos	3826'
Gallup	4635'

The referenced surface elevation is 6802', KB 6815'

**2. ESTIMATED DEPTH OF POTENTIAL WATER, OIL, GAS, & OTHER MINERAL BEARING FORMATIONS**

<u>Substance</u>	<u>Formation</u>	<u>Depth (TVD)</u>
Water	Ojo Alamo	510'
Gas	Fruitland Coal	905'
Gas	Pictured Cliffs	1247'
Gas	Cliffhouse	1981'
Gas	Point Lookout	3658'
Oil/Gas	Mancos	3826'

All shows of fresh water and minerals will be reported and protected.

**3. PRESSURE CONTROL**

- a) Pressure control equipment and configuration will be designed to meet 2M standards.
- b) Working pressure on rams and BOPE will be 3,000 psi
- c) Function test and visual inspection of the BOP will be conducted daily and noted in the IADC Daily Drilling Report.
- d) The Annular BOP will be pressure tested to a minimum of 50 percent of its rated working pressure.
- e) Blind and Pipe Rams/BOP will be tested against a test plug to 100 percent of rated working pressure.
- f) Pressure tests are required before drilling out from under all casing strings set and cemented in place.
- g) BOP controls must be installed prior to drilling the surface casing plug and will remain in use until the well is completed or abandoned.
- h) BOP testing procedures and testing frequency will conform to Onshore Order No. 2.

**Good Times D06-2309 01H**  
**SHL: NWNW Section 6, T23N, R9W**  
**210 FNL and 667 FWL**  
**BHL: SWSW Section 6, T23N, R9W**  
**330 FSL and 660 FWL**  
**San Juan County, New Mexico**  
**Lease Number: NMNM 008005**

- i) BOP remote controls shall be located on the rig floor at a location readily accessible to the driller. Master controls shall be on the ground at the accumulator and shall have the capability to function all preventers.
- j) The kill line shall be 2-inch minimum and contain two kill line valves, one of which shall be a check valve.
- k) The choke line shall be a 2-inch minimum and contain two choke line valves (2-inch minimum).
- l) The choke and manifold shall contain two adjustable chokes.
- m) Hand wheels shall be installed on all ram preventers.
- n) Safety valves and wrenches (with subs for drill string connections) shall be available on the rig floor at all times.
- o) Inside BOP or float sub shall also be available on the rig floor at all times.

Proposed BOP and choke manifold arrangements are attached.

**4. CASING & CEMENTING PROGRAM**

The proposed casing and cementing program has been designed to protect and/or isolate all usable water zones, potentially productive zones, lost circulation zones, abnormally pressured zones, and any prospectively valuable deposits of minerals. Any isolating medium other than cement shall receive approval prior to use. The casing setting depth shall be calculated to position the casing seat opposite a competent formation which will contain the maximum pressure to which it will be exposed during normal drilling operations. All indications of useable water shall be reported.

- a) The proposed casing design is as follows:

Casing	Depth	Hole Size	Csg Size	Weight	Grade
Conductor	0-60'	30"	20"	94#	H40, STC New
Surface	0'-500'	12 1/4"	9 5/8"	36#	J55, STC New
Intermediate	0'-5029'MD	8 3/4"	7"	26#	J55, LTC New
Production Liner	4829'-9380'MD	6 1/8"	4 1/2"	11.6#	B80*, LTC New

Casing String				Casing Strength Properties			Minimum Design Factors		
Size	Weight (lb/ft)	Grade	Connection	Collapse (psi)	Burst (psi)	Tensile (1000lb)	Collapse	Burst	Tension
9 5/8"	36	J55	STC	2020	3520	394	1.125	1.1	1.5
7"	26	J55	LTC	4320	4980	367	1.125	1.1	1.5
4 1/2"	11.6	B80	LTC	6350	7780	201	1.125	1.1	1.5

\*B80 pipe specifications are attached

Casing design is subject to revision based on geologic conditions encountered.

All casing strings below the conductor shall be pressure tested to 0.22 psi per foot of casing string length or 1,500 psi, whichever is greater, but not to exceed 70 percent of the minimum internal yield. If pressure declines more than 10 percent in 30 minutes, corrective action shall be taken.

- b) The proposed cementing program is as follows:

Top plugs shall be used to reduce contamination of cement by displacement fluid. A bottom plug or other acceptable technique, such as a pre-flush fluid, inner string cement method, etc. shall be utilized to help isolate the cement from contamination by the mud fluid being displaced ahead of the cement slurry.

Good Times D06-2309 01H  
 SHL: NWNW Section 6, T23N, R9W  
 210 FNL and 667 FWL  
 BHL: SWSW Section 6, T23N, R9W  
 330 FSL and 660 FWL  
 San Juan County, New Mexico  
 Lease Number: NMNM 008005

Casing	Depth	Cement Volume (sacks)	Cement Type&Yield	Designed TOC	Centralizers
Conductor	60'	100sk	Type I Neat 14.8ppg	Surface	None
Surface	500'	178sk	Type III Cement + 1% CaCl + 0.25lb/sk Cello Flake + 0.2% FL, 14.6ppg, 1.38cuf/sk	Surface	1 turbolizer per joint on bottom 3 joints
Intermediate	4854'TVD/ 5029'MD	30% open hole excess Lead 1: 239sk Tail 1: 165sk Lead 2: 113sk	<b>Lead:</b> PremLite + 3% CaCl + 0.25lb/sk CelloFlake + 5lb/sk LCM, 12.1ppg 2.13cuf/sk <b>Tail:</b> Type III Cmt + 1% CaCl + 0.25lb/sk Cello Flake 14.5ppg 1.38cuf/sk	Surface	1 per joint for bottom 3 joints, 1 every 3 joints for remaining joints
Production Liner*	4829'MD- 9380'MD	None – External casing packers	N/A	N/A	N/A

\*Production liner clarification: Utilizing external swell casing packer system for zonal isolation will not use cement in the production liner.

Actual volumes will be calculated and determined by conditions onsite. All cement slurries will meet or exceed minimum BLM and New Mexico Oil Conservation Division requirements. Slurries used will be the slurries listed above or equivalent slurries depending on service provider selected. Cement yields may change depending on slurries selected.

All waiting on cement times shall be adequate to achieve a minimum of 500 psi compressive strength at the casing shoe prior to drilling out.

## 5. WELL PLAN & DIRECTIONAL DRILLING PROGRAM

The proposed well will be drilled in two phases. A pilot hole will be drilled in the first phase, followed by kicking off a horizontal lateral in the existing wellbore in the second phase. The intent of drilling a pilot hole is to obtain open hole log data. The intent of the second phase of the well is to plug back the pilot hole with cement to the kick off point. After plugging back, the plan is to drill a horizontal lateral from the kick off point in the existing wellbore to the proposed bottom hole location.

Directional plans are attached.

Well Phase	Description	Proposed Depth (TVD/MD)	Formation
1	Vertical Pilot Hole	5170'/5170'	Gallup
2	Horizontal Lateral	4824'/9380'	Gallup

Good Times D06-2309 01H  
 SHL: NWNW Section 6, T23N, R9W  
 210 FNL and 667 FWL  
 BHL: SWSW Section 6, T23N, R9W  
 330 FSL and 660 FWL  
 San Juan County, New Mexico  
 Lease Number: NMNM 008005

**Proposed Plug Back Procedure:**

KOP 4309'

Set kick plug at KOP

1. Spot 300' kick plug from 4209' – 4509'
  - a. 91sx of Class A cement with salt (1.3ft<sup>3</sup>/sk yield)
  - b. Spot tuned spacer
2. Pull uphole and reverse out
3. Pump bottoms up 2 times, pull uphole
4. Tag plug, drill ahead to KOP when cement is solid

**6. DRILLING FLUIDS PROGRAM**

a) Vertical Pilot Hole:

Hole Size (in)	TVD (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
30"	0-60'	Fresh Water	8.3-9.2	38-100	4-28
12 1/4"	0-500'	Fresh Water	8.4-8.6	60-70	NC
8 3/4"	500-5170'	Fresh Water LSND	8.5-8.8	40-50	8-10

b) Kick off Point to Intermediate Casing Point:

Hole Size (in)	TVD (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
8 3/4"	4309' (KOP)- 4854' (5029'MD)	Fresh Water LSND	8.5-8.8	40-50	8-10

c) Intermediate Casing Point to TD:

Hole Size (in)	Depth (ft)	Mud Type	Density (lb/gal)	Viscosity (sec/qt)	Fluid Loss (cc)
6 1/8"	5029'MD- 9380'MD	Synthetic Oil Based Mud	8.6-9.0	15-25	<15

d) There will be sufficient mud on location to control a blowout should one occur. Mud flow and volume will be monitored both visually and with electronic pit volume totalizers. Mud tests shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.

e) A closed-loop system will be used to recover drilling fluid and dry cuttings in both phases of the well and on all hole intervals, including fresh water and oil-based operations. Above-ground tanks will be utilized to hold cuttings and fluids for rig operations. A frac tank will be on location to store fresh water. Waste will be disposed of properly at an EPA-approved hazardous waste facility. Fresh water cuttings will be disposed of at Basin Disposal, Inc. and/or Industrial Ecosystems, Inc. The location will be lined in accordance with the Surface Use Plan of Operations.

Good Times D06-2309 01H

SHL: NWNW Section 6, T23N, R9W  
210 FNL and 667 FWL

BHL: SWSW Section 6, T23N, R9W  
330 FSL and 660 FWL

San Juan County, New Mexico

Lease Number: NMNM 008005

## 7. TESTING, CORING and LOGGING

- a) Drill Stem Testing – None anticipated.
- b) Coring – Obtain core starting in the Mancos formation. Specific cored intervals will be determined real time by onsite geologists.
- c) Mud Logging – Mud loggers will be on location from kick off point to TD.
- d) Logging – See Below

Open Hole:

Triple combo with Spectral Gamma TD to surface casing  
Specialty logs will be decided real time by onsite geologists

Cased Hole:

CBL/CCL/GR/VDL will be run as needed for perforating control

## 8. ABNORMAL PRESSURES & HYDROGEN SULFIDE

The anticipated bottom hole pressure is +/- 2,420 psi based on a 9.0 ppg at 5170' TVD of the vertical pilot hole. No abnormal pressure or temperatures are anticipated.

No hydrogen sulfide gas is anticipated, however, if H<sub>2</sub>S is encountered, the guidelines in Onshore Order No. 6 will be followed.

## 9. ANTICIPATED START DATE AND DURATION OF OPERATIONS

Drilling is estimated to commence on June 30, 2013. It is anticipated that completion operations will begin within 30 days after the well has been drilled depending on fracture treatment schedules with various pumping service companies.

It is anticipated that the drilling of this well will take approximately 25 days.