

RECEIVED

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

JUL 05 2013

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. NM NM 101058

6. If Indian, Allottee or Tribe Name

RCVD JUL 17 '13

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No. OIL CONS. DIV.

1. Type of Well

[X] Oil Well [] Gas Well [] Other

8. Well Name and No. Good Times L10-2410 01H DIST. 3

2. Name of Operator Encana Oil & Gas (USA) Inc.

9. API Well No. 30-045-35442

3a. Address 370 17th Street, Suite 1700 Denver, CO 80202

ATTN: ROBYNN HADEN

3b. Phone No. (include area code) 720-876-3941

10. Field and Pool or Exploratory Area Bisti Lower-Gallup

4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SHL: 1753' FSL and 199' FWL Sec 10, T24N, R10W BHL: 1753' FSL and 330' FWL Sec 9, T24N, R10W

11. Country or Parish, State San Juan, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

Table with 2 main columns: TYPE OF SUBMISSION and TYPE OF ACTION. Includes checkboxes for Notice of Intent, Subsequent Report, Final Abandonment Notice, Acidize, Deepen, Production (Start/Resume), Water Shut-Off, etc.

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones.

Utilized synthetic oil-based mud system from intermediate casing point (5507'MD) to TD of lateral.

Kicked off lateral at 4887'MD on 6/17/13. Landed lateral at 5667'MD on 6/23/13. Length of lateral: 4488'. TD of 10,155'MD/5309'TVD reached 6/26/13. Set production liner 6/27/13.

Hole diameter: 6 1/8", production string diameter: 4 1/2", production string weight and grade: 11.6# SB-80 LTC. Depth of 6 1/8" hole from 5573' to 10,155'MD. Float shoe at 10,153'MD and float collar at 10,137'MD. Production liner set from 5309'MD to 10,153'MD.

Set 17 external swellable casing packers for isolation of production string at the following depths: (1) 9905' (2) 9673' (3) 9399' (4) 9133' (5) 8902' (6) 8666' (7) 8389' (8) 8157' (9) 7924' (10) 7649' (11) 7419' (12) 7157' (13) 6895' (14) 6659' (15) 6424' (16) 6146' (17) 5870'

Rig released 6/27/13. ✓

ACCEPTED FOR RECORD

JUL 08 2013

FARMINGTON FIELD OFFICE BY William Tambekou

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

Robynn Haden

Title Engineering Technologist

Signature

[Handwritten Signature]

Date

7/3/13

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

NMOCDFW