

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-043-21183
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-3925
7. Lease Name or Unit Agreement Name Lybrook H36A-2307
8. Well Number 01H
9. OGRID Number 282327
10. Pool name or Wildcat Lybrook Gallup

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Encana Oil & Gas (USA) Inc.

3. Address of Operator  
370 17<sup>th</sup> Street, Suite 1700 Denver, CO 80202

4. Well Location

SHL: Unit Letter H: 1598 feet from the NORTH line and 436 feet from the EAST line

BHL: Unit Letter D: 400 feet from the NORTH line and 330 feet from the WEST line

Section 36 Township 23N Range 7W NMPM Sandoval County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
7263' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐  
OTHER: Production String ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized high performance water based mud from surface to TD.

Kicked off lateral at 4867' on 5/21/14. Landed lateral at 6376' on 5/29/14. Length of lateral: 4002'. TD of 10,378'MD/5601'TVD reached 5/31/14. Set production liner 6/1/14.

Hole diameter: 6.125", production string diameter: 4.5", production string weight and grade: 11.6# SB80 LTC. Depth of 6.125" hole from 6020'-10,378'MD. Float shoe at 10,374'MD. Float collar at 10,331'MD. Production liner set from 5742'-10,374'MD.

Set 17 external swellable casing packers for isolation of production string at the following depths: (1) 10,101' (2) 9868 (3) 9597' (4) 9363' (5) 9086' (6) 8851' (7) 8575' (8) 8349' (9) 8071' (10) 7807' (11) 7538' (12) 7309' (13) 7036' (14) 6775' (15) 6510' (16) 6278' (17) 6047'

Spud Date: 5/17/14

Rig Release Date: 6/2/14 ✓

OIL CONS. DIV DIST. 3  
JUN 11 2014

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robynn Haden TITLE Engineering Tech DATE 6/9/14

Type or print name Robynn Haden E-mail address: robynn.haden@encana.com PHONE: 720-876-3941

For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector, District #3 DATE 6/13/14  
Conditions of Approval (if any): AV