District I 1625 N. Frinch Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

| Pit, Below-Grade Tank, or  |
|--|
| Proposed Alternative Method Permit or Closure Plan Application   |
| Proposed Alternative Method Permit or Closure Plan Application  Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method |
| Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request   |
| lease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the avironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.  |
| operator: BP America Production CompanyOGRID#:778  |
| OGRID#: 778  |
| Address:200 Energy Court, Farmington, NM 87401   |
| Facility or well name:Gallegos Canyon Unit 360   |
| API Number:3004526455OCD Permit Number:11773   |
| U/L or Qtr/QtrD Section14 Township28N Range12W County:San Juan   |
| Center of Proposed Design: Latitude36.666690 Longitude108.086520 NAD: ☐1927 ☒ 1983   |
| Surface Owner: 🛮 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment  |
| 2.   |
| Pit: Subsection F, G or J of 19.15.17.11 NMAC  |
| Temporary: Drilling Workover   |
| ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid ☐ yes ☐ no  |
| Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other  |
| String-Reinforced  |
| Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D  |
| 3.   |
| Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A  |
| Volume:21.0bbl Type of fluid:Produced water  |
| Tank Construction material:Steel   |
| Secondary containment with leak detection   Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off  |
| ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/Single bottomed, side walls not visible  |
| Liner type: Thicknessmil   |
| 1.   |
| Alternative Method:  |

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

| Fancing: Subsection D of 19.15.17.11 NMAC (Applies in permanent pin, temporary pin, and below-grade tranks)  |   |               |
|--|---|---------------|
| Institution or cohereby  | Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  |               |
| Four foot height, four strands of barbed wire evenly spaced between one and four feet   Alternare. Please specify  |   | , hospital,   |
| Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)   | ·   |               |
| Streen   Nesting   Other   Monthly inspections (if nesting or screening is not physically feasible)    Street   No.   No.   No.   No.     Street   No.   No. | Alternate. Please specify   | •             |
| Streen   Nesting   Other   Monthly inspections (if nesting or screening is not physically feasible)    Street   No.   No.   No.   No.     Street   No.   No. | 6.  |               |
| Monthly inspections (If netting or screening is not physically feasible)   |   |               |
| 12"x 2", 2" lettering, providing Operator's name, site location, and emergency telephone numbers   |   |               |
| 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  | Monthly inspections (If netting or screening is not physically feasible)  |               |
| 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  | 7. Simon Colon dia Config. 17.11 NIMAC  |               |
| Signed in compliance with 19.15.16.8 NMAC    Variances and Exceptions:   |   |               |
| Variances and Exceptions:     Ustifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.     Please check a how if one or more of the following is requiseded.   final feave blank:  |   |               |
| Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 MAC for guidance.  Please check a havi fine or more of the following is requested, if not leave blant:    Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.    Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.    Siting Criteria (regarding permitting): 19.15.17.10 NMAC   Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.    General siting   Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tanks.    Ground water is less than 25 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.   No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from the municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended, (Does not apply to below grade tanks)   Yes   No Written confirmation or verification or must the municipality; Written approval obtained from the municipality    Within the area overlying a subsurface mine. (Does not apply to below grade tanks)   Yes   No No Mine an unstable area. (Does not apply to below grade tanks)   Yes   No Society; Topographic map and the municipal must be the MEMNRD-Mining and Mineral Resources; USGS; NM Geological Society; Topographic map   Yes   No Petide Mineral Resources; USGS; NM Geological Society; Topographic map; Visual inspection (certification) of th |   |               |
| Please check a box if one or more of the following is requested, if not leave blank:   |   |               |
| Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  | -   |               |
| Siting Criteria (regarding permitting): 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source  material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.    General siting   Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.   Yes   No   NA  | ☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.   |               |
| Activations: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.    General siting   Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.   Yes   No   NA  | Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.   |               |
| Activations: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.    General siting   Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.   Yes   No   NA  |   |               |
| General siting  Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.    Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS; Data obtained from nearby wells   Yes   No   NA Office of the State Engineer - iWATERS database search;   USGS; Data obtained from nearby wells   Yes   No   Na   Written confirmation or verification from the municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)   Yes   No   Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division   Yes   No   Yes   No   Yes   No   Seciety; Topographic maps   Yes   No   Ye |   |               |
| General siting  Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  -   NM Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells  Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Witten approval obtained from the municipality  Within an unstable area. (Does not apply to below grade tanks)  - Begineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   | ptable source |
| Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.    NM Office of the State Engineer - iWATERS database search; USGS;   Data obtained from nearby wells   NA   |   |               |
| Cround water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  MN Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   | <b>General siting</b>   |               |
| Within in 100-year floodplain. (Does not apply to below grade tanks)  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  No flore of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the continuously flowing watercourse, or any other significant watercourse on wholloride temporary pits.)  |   |               |
| Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   | Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.   | ☐ Yes ☐ No    |
| adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   | □ NA          |
| Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  |   | Yes No        |
| Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   |               |
| Within an unstable area. (Does not apply to below grade tanks)  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  |   |               |
| - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   | Yes No        |
| Within 100 feet of a continuously flowing water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  |   | □ Vas □ Na    |
| Within a 100-year floodplain. (Does not apply to below grade tanks)  FEMA map  Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  |   | l les l 140   |
| Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  |   | ☐ Yes ☐ No    |
| Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   |               |
| from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   | Below Grade Tanks   |               |
| from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   | Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured   | ☐ Yes ☐ No    |
| Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   |               |
| NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  |   |               |
| Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  □ Yes □ No   | Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site | Yes   No      |
| Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   |   |               |
| or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  | Temporary Pit using Low Chioride Drilling Fluid (maximum chloride content 15,000 mg/liter)  |               |
|  | or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)   | ☐ Yes ☐ No    |

| Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial   | Yes No       |  |  |  |  |
|---|--------------|--|--|--|--|
| <ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>   |              |  |  |  |  |
| Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site   |              |  |  |  |  |
| Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site   | ☐ Yes ☐ No   |  |  |  |  |
| Temporary Pit Non-low chloride drilling fluid   |              |  |  |  |  |
| Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  | Yes No       |  |  |  |  |
| Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  | ☐ Yes ☐ No   |  |  |  |  |
| Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  | ☐ Yes ☐ No   |  |  |  |  |
| Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site   | Yes No       |  |  |  |  |
| Permanent Pit or Multi-Well Fluid Management Pit  |              |  |  |  |  |
| Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site   | Yes No       |  |  |  |  |
| Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image   | ☐ Yes ☐ No   |  |  |  |  |
| Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.   |              |  |  |  |  |
| - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site   | ☐ Yes ☐ No   |  |  |  |  |
| Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site   | Yes No       |  |  |  |  |
| Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.   |              |  |  |  |  |
| Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. |              |  |  |  |  |
| and 19.15.17.13 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:  |              |  |  |  |  |
| Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc   | cuments are  |  |  |  |  |
| attached.  □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  □ A List of wells with approved application for permit to drill associated with the pit.  □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.  and 19.15.17.13 NMAC  □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC             | 15.17.9 NMAC |  |  |  |  |
| Previously Approved Design (attach copy of design) API Number: or Permit Number:  |              |  |  |  |  |
|   | <del></del>  |  |  |  |  |

| Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the   | documents are       |
|---|---------------------|
| ### Author Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC    Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC    Climatological Factors Assessment    Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC    Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC    Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC    Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC    Quality Control/Quality Assurance Construction and Installation Plan    Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC    Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC    Nuisance or Hazardous Odors, including H₂S, Prevention Plan    Emergency Response Plan    Oil Field Waste Stream Characterization    Monitoring and Inspection Plan    Erosion Control Plan    Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC |                     |
| Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.   |                     |
| Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F  | luid Management Pit |
| ☐ Alternative  Proposed Closure Method: ☐ Waste Excavation and Removal ☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method   |                     |
| 14.   |                     |
| Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  |                     |
| 15. Siting Criteria (regarding on site closure methods only): 10 15 17 10 NMAC  |                     |
| Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.  |                     |
| Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   | ☐ Yes ☐ No<br>☐ NA  |
| Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  | Yes No              |
| Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  | Yes No              |
| Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  | ☐ Yes ☐ No          |
| Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  | ☐ Yes ☐ No          |
| Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site   | Yes No              |
| Written confirmation or verification from the municipality; Written approval obtained from the municipality   | Yes No              |
| Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  | ☐ Yes ☐ No          |
| Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance   |                     |

| adopted pursuant to NMSA 1978, Section 3-27-3, as amended.   |                                       |  |  |  |  |  |  |
|--|---------------------------------------|--|--|--|--|--|--|
| - Written confirmation or verification from the municipality; Written approval obtained from the municipality  | ☐ Yes ☐ No                            |  |  |  |  |  |  |
| Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division    Yes   Yes |                                       |  |  |  |  |  |  |
| Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological   |                                       |  |  |  |  |  |  |
| Within a 100-year floodplain.  | Yes No                                |  |  |  |  |  |  |
| - FEMA map   | ☐ Yes ☐ No                            |  |  |  |  |  |  |
| On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   | 11 NMAC<br>15.17.11 NMAC              |  |  |  |  |  |  |
| Operator Application Certification:  |                                       |  |  |  |  |  |  |
| I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.   |                                       |  |  |  |  |  |  |
| Name (Print): Title:   |                                       |  |  |  |  |  |  |
| Signature: Date:   | 4                                     |  |  |  |  |  |  |
| organical desired and the second seco | · · · · · · · · · · · · · · · · · · · |  |  |  |  |  |  |
| e-mail address: Telephone:   |                                       |  |  |  |  |  |  |
|  |                                       |  |  |  |  |  |  |
| e-mail address: Telephone:   |                                       |  |  |  |  |  |  |
| e-mail address:  |                                       |  |  |  |  |  |  |
| e-mail address:    Telephone:  | the closure report.                   |  |  |  |  |  |  |
| e-mail address:  | the closure report.                   |  |  |  |  |  |  |
| e-mail address:    Telephone:  | the closure report.<br>complete this  |  |  |  |  |  |  |

Form C-144 Oil Conservation Division Page 5 of 6

| Operator Closure Certification:   |                                   |
|---|-----------------------------------|
| I hereby certify that the information and attachments submitted with this closure<br>belief. I also certify that the closure complies with all applicable closure require |                                   |
| Name (Print):Jeff Peace   | Title: Area Environmental Advisor |
| Signature: Seff Pasco   | Date:June 23, 2014                |
| e-mail address:peace.jeffrey@bp.com   | Telephone:(505) 326-9479          |

#### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

OIL CONS. DIV DIST. 3

JUL 2 4 2014

# Gallegos Canyon Unit 360 API No. 3004526455 Unit Letter D, Section 14, T28N, R12W

This plan will address the method, procedures, and protocols for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites pursuant to Subsection A of 19.15.17.13 NMAC. As stipulated in Paragraph (1) of Subsection C of 19.15.17.13 NMAC, BP will not commence closure without first obtaining approval of the closure plan submitted pursuant to Paragraph (3) of Subsection B of 19.15.17.9 NMAC. If deviations from this plan are necessary, BP will request preapproval from the Division District III office of any specific changes and will be included on form C-144. BP shall close its BGTs within 60 days of cessation of the operation as required by Paragraph (4) of Subsection G of 19.15.17.13 NMAC.

#### General Closure Plan

1. BP shall notify the surface owner by certified mail, return receipt requested that it plans to close a BGT. Notice given will be at least 72 hours in advanced, but not more than one week prior to any closure operation. The notice shall include the well name, API number, and legal description of the location. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

No notice was sent. This well was P&A'd in 2012 and the BGT was closed in conjunction with recent recompletion activities for the adjacent well, the GCU 207E. As a result the work was not done as part of normal BGT closure activities and a closure notice was not sent.

2. BP shall notify the division District III office verbally and in writing at least 72 hours, but not more than one week, prior to any closure operation. The notice shall include the Operator's name, and the location of the BGT to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was sent. This well was P&A'd in 2012 and the BGT was closed in conjunction with recent recompletion activities for the adjacent well, the GCU 207E. As a result the work was not done as part of normal BGT closure activities and a closure notice was not sent.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
  - f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
  - g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
  - h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
  - i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
  - j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
  - k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the Division District III office approves. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.
  - The BGT was transported to a storage area for sale and re-use.
- 5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for some other purpose.
  - All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample to include any obvious stained or wet soils, or other evidence of a release under the BGT. The composite sample shall be collected and analyzed as required for the constituents listed in Table 1 within Subparagraph (a) of Paragraph (3) of Subsection C of 19.15.17.13 NMAC (see Table 1 on following page).

|  | Table                                       |                                     |              |
|--|---|-------------------------------------|--------------|
| Depth below bottom of pit to groundwater less than 10,000 mg/l TDS | sure Criteria for Soils Bene<br>Constituent | Method*                             | Limit**      |
|  | Chloride                                    | EPA 300.0                           | 600 mg/kg    |
|  | TPH   | EPA SW-846<br>Method 418.1          | 100 mg/kg    |
| ≤50 feet   | BTEX  | EPA SW-846 Method<br>8021B or 8260B | 50 mg/kg     |
|  | Benzene                                     | EPA SW-846 Method<br>8021B or 8015M | 10 mg/kg     |
|  | Chloride                                    | EPA 300.0                           | 10,000 mg/kg |
|  | ТРН   | EPA SW-846<br>Method 418.1          | 2,500 mg/kg  |
| 51 feet-100 feet   | GRO+DRO                                     | EPA SW-846<br>Method 8015M          | 1,000 mg/kg  |
|  | BTEX  | EPA SW-846 Method<br>8021B or 8260B | 50 mg/kg     |
|  | Benzene                                     | EPA SW-846 Method<br>8021B or 8015M | 10 mg/kg     |
|  | Chloride                                    | EPA 300.0                           | 20,000 mg/kg |
| > 100 feet   | ТРН   | EPA SW-846<br>Method 418.1          | 2,500 mg/kg  |
|  | GRO+DRO                                     | EPA SW-846<br>Method 8015M          | 1,000 mg/kg  |
|  | BTEX  | EPA SW-846 Method<br>8021B or 8260B | 50 mg/kg     |
|  | Benzene                                     | EPA SW-846 Method<br>8021B or 8015M | 10 mg/kg     |

Notes:

mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons, TDS = total dissolved solids.

- \* Or other test methods approved by the division
- \*\* Numerical limits or natural background level, whichever is greater

| Constituents | Testing Method                      | Release Verification | Sample  |
|--------------|-------------------------------------|----------------------|---------|
|              | 21 bbl BGT                          | (mg/Kg)              | results |
| Benzene      | US EPA SW-846 Method 8021B or 8015M | 10                   | ND      |
| Total BTEX   | US EPA SW-846 Method 8021B or 8260B | 50                   | ND      |
| TPH          | US EPA SW-846 Method 418.1          | 100                  | ND      |
| Chlorides    | US EPA Method 300.0                 | 600 or background    | ND      |

# Soil under the BGT was sampled and TPH, BTEX, and chlorides were below the stated limits. Sampling data is attached.

7. If any contaminant concentration exceeds those standards set in Table 1, BP will acknowledge NMOCD's position to require additional delineation upon review of the results. BP will not proceed with any further closure activities until approval is first granted by NMOCD.

Contaminant concentrations did not exceed the applicable standards in Table 1.

8. If the sampling demonstrates that all contaminant constituents do not exceed the concentrations specified in Table 1, then BP shall backfill the excavation, with non-waste containing, uncontaminated, earthen material.

The area under the BGT was backfilled with clean soil.

9. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Paragraph (2) of Subsection H of 19.15.17.13 NMAC, re-contour the BGT location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Paragraph (5) of Subsection H of 19.15.17.13 NMAC.

The area over the BGT is still within the active area of the adjacent well, the GCU 207E. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

11. BP may propose an alternative to the re-vegetation or re-contouring requirement if it can demonstrate to the NMOCD's District III office that the proposed alternative provides equal or greater prevention of erosion, and protection of fresh water, public health and the environment. BP will seek surface owner approval of the proposed alternative and provide written documentation of the surface owner's approval to NMOCD for its approval.

BP will notify NMOCD District III and the surface owner if alternative re-vegetation or recontouring are proposed.

12. Areas reasonably needed for production operations or for subsequent drilling operations shall be compacted, covered, paved, or otherwise stabilized and maintained in such a way as to minimize dust and erosion to the extent practicable.

The area over the BGT was backfilled and compacted to the same level as the rest of the adjacent location.

13. The soil cover for closures after site contouring, where the BGT has been removed and if necessary remediated beneath the BGT to chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, shall consist of the background thickness of topsoil or one foot or suitable material, whichever is greater.

The area over the BGT was backfilled with clean soil.

14. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT was backfilled and compacted to the same level as the rest of the active location.

15. All areas disturbed by the closure of the BGT, except areas reasonably needed for production operations or for subsequent drilling operations, shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable.

The area over the BGT was backfilled with clean soil and is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

16. Topsoils and subsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded in the first favorable growing season following closure of the BGT.

The area over the BGT was backfilled and compacted to the same level as the rest of the location. This area will be reseeded as part of final reclamation when the well is plugged and abandoned.

17. Reclamation of all disturbed areas no longer in use shall be considered complete when all ground surface disturbing activities at the site have been completed, and a uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre-disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds.

BP will notify NMOCD District III when reclamation is complete after the well has been plugged and abandoned.

18. The re-vegetation and reclamation obligations imposed by other applicable federal or tribal agencies on lands managed by those agencies shall supersede these provisions and govern the obligations of BP subject to those provisions, provided that the other requirements provide equal or better protection of fresh water, human health and the environment.

BP will comply with applicable re-vegetation and reclamation obligations from other agencies if applicable.

19. Pursuant to Subparagraph (e) of Paragraph (5) of Subsection H of 19.15.17.13 NMAC, BP shall notify the NMOCD when reclamation and re-vegetation has been successfully achieved.

BP will notify NMOCD when reclamation and re-vegetation has been successfully achieved.

- 20. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. necessary attachments to document all closure activities
  - b. sampling results
  - c. information required by 19.15.17 NMAC
  - d. details on back-filling, capping and covering, where applicable.

Closure report on C-144 form is included.

21. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 form has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011
Submit 1 Copy to appropriate District Office in

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

|  |   |  | IVER   | case Mullin  | catioi.                             | OPERA                                     | orrective A<br>TOR   | CHOII                                 | □ Initi:                                | al Report                                   | ⊠ F                                 | Final Report                  |
|--|---|--|--|--|-------------------------------------|---|--|---------------------------------------|---|---|-------------------------------------|-------------------------------|
| Name of Company: BP  |   |  |  |  |                                     | Contact: Jeff Peace                       |  |                                       |   |   | mai report                          |                               |
| Address: 200 Energy Court, Farmington, NM 87401                    |   |  |  |  |                                     |   | No.: 505-326-94  | 79                                    |   |   |                                     |                               |
|  |   | gos Canyon I                                 |  |  |                                     |   | e: Natural gas v   |                                       |   |   |                                     |                               |
| Surface Ow   | ner: Feder  | al   |  | Mineral C  | Owner: I                            | Federal                                   |  |                                       | API No                                  | . 30045264                                  | 55                                  |                               |
|  |   |  |  | LOCA   | ATION                               | OF RE                                     | LEASE  | •                                     |   |   |                                     |                               |
| Unit Letter<br>D   | Section<br>14   | Township 28N                                 | Range<br>12W   | Feet from the 1,000  | North/<br>North                     | South Line                                | Feet from the 950  | East/W<br>West                        | est Line                                | County: Sa                                  | n Juan                              |                               |
|  |   | Latit  | <b>ude</b> 36  | .666690  |                                     | Longitud                                  | <b>e</b> 108.086520  |                                       |   |   |                                     |                               |
|  |   |  |  | NAT  | URE                                 | OF REL                                    | EASE   |                                       |   |   |                                     |                               |
| Type of Rele   |   |  |  |  |                                     | Volume of                                 | Release: N/A   |                                       | Volume F                                | Recovered: N                                | /A                                  |                               |
| Source of Re   | lease: belov  | w grade tank -                               | 21 bbl   |  |                                     |   | Hour of Occurrenc  | e:                                    | Date and                                | Hour of Disc                                | overy: N                            | N/A                           |
| Was Immedi   | ate Notice (  | Given?                                       |  |  |                                     | N/A<br>If YES, To                         | W/hom?   |                                       |   |   |                                     |                               |
| was immedi   | ate Hottee (  |  | Yes [  | No 🛛 Not Re  | equired                             | 11 165, 10                                | WHOIII:  |                                       |   |   |                                     |                               |
| By Whom?   |   |  |  |  | •                                   | Date and I                                |  |                                       |   |   |                                     |                               |
| Was a Water  | course Read   | ched?  |  |  |                                     |   | olume Impacting t  | he Water                              | course.                                 |   |                                     |                               |
|  |   |  | Yes 🛭  | No   |                                     |   |  |                                       |   |   |                                     |                               |
| If a Watercou  | ırse was Im   | pacted, Descr                                | ibe Fully.*  | •  |                                     |   |  |                                       |   |   |                                     |                               |
| the BGT. So  | il analysis r   | esulted in TP.                               | H, BTEX :  | and chlorides belo   | ow standa                           | ards. Analys                              | the BGT was dor<br>is results are attac  | ched.                                 |   |   | ·                                   |                               |
| backfilled an  | d compacte  | d and is still v                             | vithin the a   | active well area of  | f the adja                          | cent well, th                             | e GCU 207E.  |                                       | •                                       |   |                                     |                               |
| regulations a<br>public health<br>should their c<br>or the environ | Il operators<br>or the envi-<br>operations h<br>nment. In a | are required to ronment. The ave failed to a | o report an<br>acceptance<br>adequately<br>ICD accep | d/or file certain re<br>te of a C-141 repo<br>investigate and re | elease no<br>ort by the<br>emediate | otifications as<br>NMOCD m<br>contaminati | knowledge and und perform correct arked as "Final Recontract pose a threet the operator of recontract and under the operat | tive actio<br>eport" do<br>eat to gro | ns for rele<br>es not reli<br>und water | eases which neve the opera<br>, surface wat | nay enda<br>ator of lia<br>er, huma | anger<br>ability<br>an health |
| _  | n   | n  |  |  |                                     |   | OIL CONS   | SERV <i>E</i>                         | ATION                                   | DIVISIO                                     | <u>N</u>                            |                               |
| Signature:   | 1966 l  | Joses  |  |  |                                     |   |  |                                       |   |   |                                     |                               |
| Printed Name   | e: Jeff Peace   | 9  |  |  | A                                   | Approved by                               | Environmental Sp   | pecialist:                            |   |   |                                     |                               |
| Title: Area E  |   |  |  |  | A                                   | Approval Dat                              | e:   | E                                     | xpiration I                             | Date:                                       |                                     |                               |
| E-mail Addre   | ess: peace is   | effrey@bp.cor                                | n  |  | (                                   | Conditions of                             | Approval:  |                                       | •                                       |   |                                     |                               |
|  |   |  |  |  |                                     |   |  |                                       |   | Attached                                    | Ш                                   |                               |
| Date: June 2   | 3, 2014   |  | Phone: 50  | 5-326-9479   |                                     |   |  |                                       |   |   |                                     | ,                             |

<sup>\*</sup> Attach Additional Sheets If Necessary

| CLIENT: BP   | P.O. BOX 87, I   | ENGINEERING, INC.<br>BLOOMFIELD, NM 8741  | 13                                    | API #: 3004526455  TANK ID (if applicble): A                                      |
|--|--|---|---------------------------------------|---|
|  |  | 05) 632-1199  |                                       | (if applicble): A   |
| FIELD REPORT:  | (circle one): BGT CONFIRMATION   | / RELEASE INVESTIGATION / OTHER:  |                                       | PAGE #:1 of1  |
|  | ON: SITE NAME: GCU#  |   |                                       | DATE STARTED: <b>04/04/14</b>   |
| QUAD/UNIT: D SEC: 14   |  |   | NM                                    | DATE FINISHED:  |
| 1/4 -1/4/FOOTAGE: 1,000'N /  |  | TYPE: FEDERAL/STATE/FEE/IN  | DIAN                                  | ENVIRONMENTAL   |
| LEASE #: SF078905  |  | CRUSSFIRE<br>CONTRACTOR: MBF - D. HAGA  |                                       | SPECIALIST(S): JCB  |
| REFERENCE PO   |  | es coord.: 36.66671 X 108   | 3.08665                               | GL ELEV.: 5,702'  |
| 1) 21 BGT (SW/SB)  | GPS COORD.:  | 36.66669 X 108.08652  | DISTANCE/BEAR                         | RING FROM W.H.: 40', S76E   |
|  |  | D   |                                       |   |
|  |  |   |                                       |   |
|  |  |   | DISTANCE/BEAR                         | ING FROM W.H.:  |
| SAMPLING DATA  |  | OR LAB USED: HALL   | _                                     | READING (ppm)   |
| B Comment of the Comm |  | 4/14 SAMPLE TIME: 0840 LAB ANALYSIS:  |                                       |   |
|  |  | SAMPLE TIME: LAB ANALYSIS:  |                                       |   |
|  |  | SAMPLE TIME: LAB ANALYSIS:  |                                       |   |
|  | <del></del>  | SAMPLE TIME: LAB ANALYSIS.  |                                       |   |
| SOIL COLOR: DARK YI COHESION (ALL OTHERS): NON COHESIVE SOIL CONSISTENCY (NON COHESIVE SOIL  | ELLOWISH ORANGE  LIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIV S): LOOSE / FIRM / DENSE / VERY DENSE ST / WET / SATURATED / SUPER SATURATED  TE # OF PTS5 |   | PLASTIC / CC<br>FT / FIRM / S<br>ON - | OHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC<br>STIFF / VERY STIFF / HARD            |
| SITE OBSERVAT<br>APPARENT EVIDENCE OF A RELEASE OF<br>EQUIPMENT SET OVER RECLAIMED A   | ONS: LOST INTEGRITY OF EQUIPMENT SERVED AND/OR OCCURRED: YES NO EX   | IT: YES NO EXPLANATION - PLANATION:   |                                       |   |
| SOIL IMPACT DIMENSION ESTIMA   | TION: <u>NA</u> ft. X <u>NA</u>  | ft. X NA ft. EXCAVA   | ATION EST                             | MATION (Cubic Yards) : NA   |
| DEPTH TO GROUNDWATER: >100   | NEAREST WATER SOURCE: >1,00  | 0' NEAREST SURFACE WATER: <1,000  | MMOCI                                 | TPH CLOSURE STD: 1,000 ppm  |
| SITE SKETCH  | BGT Located: off on s  |   | ↑ OVM C                               | CALIB. READ. = 101.0 ppm RF = 1.00 CALIB. GAS = 100 ppm  7:22 ampm DATE: 04/04/14 |
| MARKER<br>⊕  | BEF<br>POSIT   | M   | ``\                                   | MISCELL. NOTES  |
| $\oplus$   | FORMER   | \   | W                                     |   |
|  | SEPARATOR -  | PBGTL   | PC                                    | )#:   |
|  | POSITION   | T.B. ~ 6'<br>B.G.   | P                                     |   |
|  | \  | X Lio.  | -                                     | #:<br>  |
|  | \  |   | l —                                   | rmit date(s): 03/31/14<br>CD Appr. date(s): 03/31/14                              |
|  |  |   | Tani                                  |   |
|  | FORMER METER   | 1   | Ā                                     | BGT Sidewalls Visible: Y (N)  |
|  | RUN<br>POSITION  | X - S.I   | P.D.                                  | BGT Sidewalls Visible: Y / N  |
|  | CAVATION DEPRESSION; B.G. = BELOW GRADE; B =   | BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL H                               | HEAD;                                 | BGT Sidewalls Visible: Y / N  |
|  | )US BELOW-GRADE TANK LOCATION;   | E POINT DESIGNATION; R.W. = RETAINING WALL; NA - NO<br>DTTOM; DB - DOUBLE BOTTOM. | <u>М</u> .                            | agnetic declination: 10°E   |
| NOTES:   |  | ONSITE: 04/04/14  |                                       |   |

#### **Analytical Report**

#### Lab Order 1404414

Date Reported: 4/14/2014

### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 21 BGT 5-pt @ 6'

Project: GCU 360

**Collection Date:** 4/4/2014 8:40:00 AM

Lab ID: 1404414-001

Received Date: 4/9/2014 10:00:00 AM

| Analyses                       | Result   | RL Qu    | al Units | DF | Date Analyzed         | Batch  |
|--------------------------------|----------|----------|----------|----|-----------------------|--------|
| EPA METHOD 8015D: DIESEL RANGE | ORGANICS |          |          |    | Analyst               | :: BCN |
| Diesel Range Organics (DRO)    | ND       | 9.9      | mg/Kg    | 1  | 4/10/2014 8:34:39 PM  | 12624  |
| Surr: DNOP                     | 97.8     | 66-131   | %REC     | 1  | 4/10/2014 8:34:39 PM  | 12624  |
| EPA METHOD 8015D: GASOLINE RAN | IGE      |          |          |    | Analyst               | NSB    |
| Gasoline Range Organics (GRO)  | ND       | 4.9      | mg/Kg    | 1  | 4/10/2014 11:09:02 PM | 12623  |
| Surr: BFB                      | 85.2     | 74.5-129 | %REC     | 1  | 4/10/2014 11:09:02 PM | 12623  |
| EPA METHOD 8021B: VOLATILES    |          |          |          |    | Analyst               | : NSB  |
| Benzene                        | ND       | 0.049    | mg/Kg    | 1  | 4/10/2014 11:09:02 PM | 12623  |
| Toluene                        | ND       | 0.049    | mg/Kg    | 1  | 4/10/2014 11:09:02 PM | 12623  |
| Ethylbenzene                   | ND       | 0.049    | mg/Kg    | 1  | 4/10/2014 11:09:02 PM | 12623  |
| Xylenes, Total                 | ND       | 0.097    | mg/Kg    | 1  | 4/10/2014 11:09:02 PM | 12623  |
| Surr: 4-Bromofluorobenzene     | 100      | 80-120   | %REC     | 1  | 4/10/2014 11:09:02 PM | 12623  |
| EPA METHOD 300.0: ANIONS       |          |          |          |    | Analyst               | : JRR  |
| Chloride                       | ND       | 30       | mg/Kg    | 20 | 4/10/2014 3:30:56 PM  | 12646  |
| EPA METHOD 418.1: TPH          |          |          |          |    | Analyst               | BCN    |
| Petroleum Hydrocarbons, TR     | ND       | 20       | mg/Kg    | 1  | 4/10/2014             | 12560  |

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

#### Hall Environmental Analysis Laboratory, Inc.

WO#:

1404414 14-Apr-14

Client:

Blagg Engineering

Project:

GCU 360

Sample ID MB-12646

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID:

PBS

Batch ID: 12646

RunNo: 17936

Prep Date:

Analysis Date: 4/10/2014

**PQL** 

SeqNo: 517496

Units: mg/Kg

Analyte

4/10/2014

HighLimit

**RPDLimit** 

Qual

Chloride

ND 1.5

Sample ID LCS-12646

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 12646

RunNo: 17936

Prep Date:

4/10/2014

Analysis Date: 4/10/2014

SeqNo: 517497

Units: mg/Kg

Result

%REC 93.6

HighLimit

Result

15.00

1.5

Qual

14

110

Chloride

**PQL** 

%RPD

%RPD

SPK value SPK Ref Val

LowLimit

**RPDLimit** 

Analyte

SPK value SPK Ref Vai %REC

90

Qualifiers:

E

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0 RPD outside accepted recovery limits R

Value above quantitation range

Analyte detected in the associated Method Blank Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

Reporting Detection Limit

Page 2 of 6

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1404414

14-Apr-14

Client:

Blagg Engineering

Project:

Analyte

Analyte

GCU 360

Sample ID MB-12560

SampType: MBLK

TestCode: EPA Method 418.1: TPH

LowLimit

LowLimit

Client ID:

**PBS** 

Batch ID: 12560

**PQL** 

20

RunNo: 17911

Prep Date:

4/7/2014

Analysis Date: 4/10/2014

Result

SPK value SPK Ref Val

100.0

SPK value SPK Ref Val %REC

SeqNo: 516689

Units: mg/Kg

HighLimit

%RPD

%RPD

**RPDLimit** Qual

Petroleum Hydrocarbons, TR

Sample ID LCS-12560

ND

SampType: LCS

TestCode: EPA Method 418.1; TPH

Client ID: LCSS

Batch ID: 12560

RunNo: 17911

Units: mg/Kg

Prep Date: 4/7/2014 Analysis Date: 4/10/2014

98

Result

Result

98

SeqNo: 516690 %REC

97.8

HighLimit

120

**RPDLimit** Qual

Qual

Petroleum Hydrocarbons, TR Sample ID LCSD-12560

SampType: LCSD

TestCode: EPA Method 418.1: TPH

Batch ID: 12560

RunNo: 17911

120

Client ID: LCSS02 Prep Date: 4/7/2014

Analysis Date: 4/10/2014

**PQL** 

20

SeqNo: 516691

Units: mg/Kg

Analyte

SPK value SPK Ref Val %REC LowLimit

HighLimit %RPD **RPDLimit** 

Petroleum Hydrocarbons, TR

20

100.0

97.8

80

0

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range E

Analyte detected below quantitation limits J

RSD is greater than RSDlimit О

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Η

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Page 3 of 6

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1404414 14-Apr-14

Client:

Blagg Engineering

| Project: GCU 3              | 660                      |  |
|-----------------------------|--------------------------|--|
| Sample ID MB-12644          | SampType: <b>MBLK</b>    | TestCode: EPA Method 8015D: Diesel Range Organics      |
| Client ID: PBS              | Batch ID: 12644          | RunNo: 17898   |
| Prep Date: 4/10/2014        | Analysis Date: 4/10/2014 | SeqNo: 516499 Units: %REC                              |
| Analyte                     | Result PQL SPK value     | SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual |
| Surr: DNOP                  | 7.5 10.00                | 74.9 66 131  |
| Sample ID LCS-12644         | SampType: <b>LCS</b>     | TestCode: EPA Method 8015D: Diesel Range Organics      |
| Client ID: LCSS             | Batch ID: 12644          | RunNo: 17898   |
| Prep Date: 4/10/2014        | Analysis Date: 4/10/2014 | SeqNo: 516503 Units: %REC                              |
| Analyte                     | Result PQL SPK value     | SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual |
| Surr: DNOP                  | 3.8 5.000                | 75.5 66 131  |
| Sample ID MB-12624          | SampType: MBLK           | TestCode: EPA Method 8015D: Diesel Range Organics      |
| Client ID: PBS              | Batch ID: 12624          | RunNo: 17898   |
| Prep Date: 4/9/2014         | Analysis Date: 4/10/2014 | SeqNo: 516973 Units: mg/Kg                             |
| Analyte                     | Result PQL SPK value     | SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual |
| Diesel Range Organics (DRO) | ND 10                    |  |
| Surr: DNOP                  | 9.5 10.00                | 95.4 66 131  |
| Sample ID LCS-12624         | SampType: LCS            | TestCode: EPA Method 8015D: Diesel Range Organics      |
| Client ID: LCSS             | Batch ID: 12624          | RunNo: 17898   |
| Prep Date: 4/9/2014         | Analysis Date: 4/10/2014 | SeqNo: 516974 Units: mg/Kg                             |
| Analyte                     | Result PQL SPK value     | SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual |
| Diesel Range Organics (DRO) | 46 10 50.00              | 0 91.9 60.8 145  |
| Surr: DNOP                  | 4.4 5.000                | 87.9 66 131  |

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit O
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- Reporting Detection Limit

Page 4 of 6

# Hall Environmental Analysis Laboratory, Inc.

Result

25

920

**PQL** 

5.0

WO#:

1404414

14-Apr-14

Client:

Blagg Engineering

Project:

Analyte

Sun: BFB

Gasoline Range Organics (GRO)

GCU 360

| Sample ID MB-12623            | SampType: MBLK               | ζ                                  | TestCode: EPA Method 8015D: Gasoline Range |             |           |              |          |      |  |  |  |  |
|-------------------------------|------------------------------|------------------------------------|--|-------------|-----------|--------------|----------|------|--|--|--|--|
| Client ID: PBS                | Batch ID: 12623 RunNo: 17906 |                                    |  | 7906        |           |              |          |      |  |  |  |  |
| Prep Date: 4/9/2014           | Analysis Date: 4/10/         | 2014                               | SeqNo: <b>517100</b>                       |             |           | Units: mg/Kg |          |      |  |  |  |  |
| Analyte                       | Result PQL SI                | PK value SPK Ref                   | Val %REC                                   | LowLimit    | HighLimit | %RPD         | RPDLimit | Qual |  |  |  |  |
| Gasoline Range Organics (GRO) | ND 5.0                       |                                    |  |             |           |              |          |      |  |  |  |  |
| Surr: BFB                     | 870                          | 1000                               | 86.6                                       | 74.5        | 129       |              |          |      |  |  |  |  |
| Sample ID LCS-12623           | SampType: LCS                | SampType: LCS TestCode: EPA Method |  |             |           |              | е        |      |  |  |  |  |
| Client ID: LCSS               | Batch ID: 12623              |                                    | RunNo: 17906                               |             |           |              |          |      |  |  |  |  |
| Prep Date: 4/9/2014           | Analysis Date: 4/10/         | 2014                               | SegNo: 5                                   | Units: mg/K | a         |              |          |      |  |  |  |  |

0

%REC

102

92.2

LowLimit

71.7

74.5

HighLimit

134

129

%RPD

**RPDLimit** 

Qual

SPK value SPK Ref Val

25.00

1000

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 5 of 6

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1404414

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 360

| Sample ID MB-12623         | Sampl                    | ype: <b>M</b> E | BLK       | Tes                 |      |          |             |      |          |      |
|----------------------------|--------------------------|-----------------|-----------|---------------------|------|----------|-------------|------|----------|------|
| Client ID: PBS             | Batcl                    | n ID: <b>12</b> | 623       | RunNo: <b>17906</b> |      |          |             |      |          |      |
| Prep Date: 4/9/2014        | Analysis Date: 4/10/2014 |                 |           | SeqNo: 517142       |      |          | Units: mg/k | (g   |          |      |
| Analyte                    | Result                   | PQL             | SPK value | SPK Ref Val         | %REC | LowLimit | HighLimit   | %RPD | RPDLimit | Qual |
| Benzene                    | ND                       | 0.050           |           |                     |      |          |             |      |          |      |
| Toluene                    | ND                       | 0.050           |           |                     |      |          |             |      |          |      |
| Ethylbenzene               | ND                       | 0.050           |           |                     |      |          |             |      |          |      |
| Xylenes, Total             | ND                       | 0.10            |           |                     |      |          |             |      |          | ,    |
| Surr: 4-Bromofluorobenzene | 1.0                      |                 | 1.000     |                     | 105  | 80       | 120         |      |          |      |

| Sample ID LCS-12623        | Samp       | Гуре: <b>LC</b> | s         | Tes         | 8021B: Volatiles     |          |           |              |             |      |  |  |  |
|----------------------------|------------|-----------------|-----------|-------------|----------------------|----------|-----------|--------------|-------------|------|--|--|--|
| Client ID: LCSS            | Batc       | h ID: <b>12</b> | 623       | F           | RunNo: 1             | 7906     |           |              |             |      |  |  |  |
| Prep Date: 4/9/2014        | Analysis [ | Date: 4/        | 10/2014   | \$          | SeqNo: <b>517143</b> |          |           | Units: mg/Kg |             |      |  |  |  |
| Analyte                    | Result     | PQL             | SPK value | SPK Ref Val | %REC                 | LowLimit | HighLimit | %RPD         | RPDLimit    | Qual |  |  |  |
| Benzene                    | 1.1        | 0.050           | 1.000     | 0           | 109                  | 80       | 120       |              | <del></del> |      |  |  |  |
| Toluene                    | 1.0        | 0.050           | 1.000     | 0           | 102                  | 80       | 120       |              |             |      |  |  |  |
| Ethylbenzene               | 1.0        | 0.050           | 1.000     | 0           | 102                  | 80       | 120       |              |             |      |  |  |  |
| Xylenes, Total             | 3.0        | 0.10            | 3.000     | 0           | 100                  | 80       | 120       |              |             |      |  |  |  |
| Surr: 4-Bromofluorobenzene | 1.1        |                 | 1.000     | 107 80      |                      |          | 120       |              |             |      |  |  |  |

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 6 of 6



4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

# Sample Log-In Check List

| Client Name: BLAGG Work Order Number   | r: 1404414                             |                               | RcptNo:                           | 1                   |
|--|--|-------------------------------|-----------------------------------|---------------------|
| Received by/date: CH 09/14   | ······································ |                               |                                   |                     |
| Logged By: Michelle Garcia 4/9/2014 10:00:00 AM  | l                                      | Militale Ca                   | ·<br>run                          |                     |
| Completed By: Michelle Garcia 4/9/2014 11:51:17 AM                                     | I                                      | Mirale Ga<br>Mirale Ga        | ر نین                             |                     |
| Reviewed By: CS 04/09/14   |  | ' 7"                          |                                   |                     |
| Chain of Custody   |  |                               |                                   |                     |
| Custody seals intact on sample bottles?  | Yes 🗌                                  | No 🗆                          | Not Present                       |                     |
| 2. Is Chain of Custody complete?   | Yes 🗹                                  | No 🗆                          | Not Present                       |                     |
| 3. How was the sample delivered?   | Courier                                |                               |                                   |                     |
| <u>Log In</u>  |  |                               |                                   |                     |
| 4. Was an attempt made to cool the samples?  | Yes 🗹                                  | No 🗌                          | NA 🗆                              |                     |
| 5. Were all samples received at a temperature of >0° C to 6.0°C                        | Yes 🗹                                  | No 🗌                          | na 🗀                              |                     |
| 6. Sample(s) in proper container(s)?   | Yes 🗹                                  | No 🗆                          |                                   |                     |
| 7. Sufficient sample volume for indicated test(s)?                                     | Yes 🗹                                  | No 🗌                          |                                   |                     |
| 8. Are samples (except VOA and ONG) properly preserved?                                | Yes 🗹                                  | No 🗆                          |                                   |                     |
| 9. Was preservative added to bottles?  | Yes 🗌                                  | No 🗹                          | NA 🗆                              |                     |
| 10.VOA vials have zero headspace?  | Yes                                    | No 🗆                          | No VOA Viais 🗹                    |                     |
| 11. Were any sample containers received broken?  | Yes 🗆                                  | No 🗹                          |                                   |                     |
|  | _                                      |                               | # of preserved<br>bottles checked |                     |
| 12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)       | Yes 🗹                                  | No ∐                          | for pH: (<2 o                     | r >12 unless noted) |
| 13. Are matrices correctly identified on Chain of Custody?                             | Yes 🗹                                  | No 🗆                          | Adjusted?                         |                     |
| 14. Is it clear what analyses were requested?  | Yes 🗹                                  | No 🗆                          |                                   |                     |
| 15. Were all holding times able to be met? (If no, notify customer for authorization.) | Yes 🗹                                  | No 🗌                          | Checked by:                       |                     |
| Our alst Hamilton //Konjallockla)  |  |                               |                                   |                     |
| Special Handling (if applicable)   | <b>,</b> ,                             | $\Box$                        | NA 🗹                              |                     |
| 16. Was client notified of all discrepancies with this order?                          | Yes 📖                                  | No 🗆                          | NA 🛂                              | 1                   |
| Person Notified: Date:   |  |                               |                                   |                     |
| By Whom: Via:  | eMail                                  | Phone   Fax                   | ∐ In Person                       |                     |
| Regarding: Client Instructions:  | application to a strange process       | and the same and a same and a | e name of the second              |                     |
|  |  | Marin School of Marine is     | to More an estimate had soone     | J                   |
| 17. Additional remarks:  |  |                               |                                   |                     |
| 18. Cooler Information  Cooler No Temp °C Condition Seal Intact Seal No 1 1.8 Good Yes | Seal Date                              | Signed By                     |                                   |                     |

| Cileric Biagg Engineering, Inc. |             |               | Standard 🗆 Rush                        |                           |                      |                    |  |  | A        | NA        | LYS          | SIS        | LA              | <b>30</b> 1 | RAT     | OR   | Y        |             |
|---------------------------------|-------------|---------------|--|---------------------------|----------------------|--------------------|--|--|----------|-----------|--------------|------------|-----------------|-------------|---------|--|----------|-------------|
|                                 | BP Americ   | а             |  | Project Name              | <b>9</b> :           |                    |  |  |          |           |              |            |                 | onme        |         |  | •        |             |
| Mailing Addr                    | ress:       | P.O. Bo       | x 87                                   | GCU 360                   |                      |                    |  | 4901   | Haw      |           |              |            |                 |             |         | 109  |          |             |
|                                 |             |               | eld, NM 87413                          | Project #:                |                      |                    |  | 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107 |          |           |              |            |                 |             |         |  |          |             |
| Phone #:                        |             | (505)32       | 0-1183                                 |                           |                      |                    |  | 111  |          |           |              |            |                 | Reque       |         |  |          |             |
| email or Fax                    | <b>c#</b> : |               |  | Project Mana              | iger:                |                    |  |  |          |           |              |            |                 |             |         |  |          | T           |
| QA/QC Packa                     | age:        |               |  |                           | Jeff Blagg           |                    |  | 1 1  |          |           |              |            |                 |             |         |  |          |             |
| Standard                        |             | )             |  |                           | _                    |                    |  | (GRO) DRO)   |          |           |              | - [        |                 | 1 1         |         |  |          |             |
| <b>,</b>                        |             | Sampler:      | Jeff Blagg                             |                           |                      | 7 1                |  | 5  |          | }         |              |            |                 |             | .       | ے ا  |          |             |
| □ EDD (Type)                    |             | On Ice:       | ⊈∕Yes                                  |                           |                      |                    | ) 8  | 2  | 1        |           |              |            |                 | 1 1         | ]       | S  |          |             |
|                                 |             | Sample Tem    | perature:                              | 8                         |                      |                    |  |  |          | 1 1       | 1            | 1          | Ì               | 1 1         |         | ≥  |          |             |
| Date                            | Time        | Matrix        | Sample Request ID                      | Container<br>Type and #   | Preservative<br>Type | HEAL!              |  | BTEX (8021)  |          | TPH 418.1 |              |            |                 |             |         |  | Chloride | Air Bubbles |
| 04/04/2014                      | 8:40        | Soil          | 21 BGT 5-pt @ 6'                       | 1x 4oz                    | cool                 | -0                 |  | x  |          | ( x       | 1            |            | _               |             | 1       |  | ×        | +           |
|                                 |             |               |  |                           | ·                    | <del> </del>       |  |  |          | ╁┈        | +-           |            | $\neg \uparrow$ | 十           | +       | ╁╌┼  | _        | +           |
|                                 |             |               |  |                           |                      |                    | <del>-</del>   | +  |          | +         | -            | $\vdash$   | $\dashv$        | +           | +       | ┼╌┤  |          | +           |
|                                 |             | <del> </del>  | <del></del>                            | ]                         |                      |                    |  | ╁╼╂  |          | -         | <b> </b>     | -          |                 | -           | +-      | +  |          | 4-          |
|                                 | ļ. ———      | <del>- </del> |  |                           |                      |                    | <del></del>  | 1  |          | -         | <u> </u>     |            |                 |             | ┷       | <del>                                     </del> |          | _           |
|                                 |             |               |  |                           |                      |                    |  |  |          |           | _            |            |                 | _           |         | 1  |          |             |
|                                 | <u></u>     |               |  |                           |                      |                    |  |  |          |           |              |            |                 |             |         |  |          |             |
|                                 |             |               | <u> </u>                               |                           |                      |                    |  | 1 1  |          |           |              |            |                 |             |         |  |          |             |
|                                 |             |               |  |                           |                      |                    |  |  |          |           |              |            |                 |             | T       |  |          | T           |
|                                 |             |               |  |                           |                      |                    |  |  |          |           |              |            |                 |             | 1       |  |          | T           |
|                                 |             |               |  |                           |                      |                    |  |  |          | 1         |              |            |                 | _           | +       | 1  | _        | 十           |
|                                 |             |               |  |                           | <del> </del>         |                    |  | 1 1  | _        |           | <del> </del> |            | $\dashv$        | +           | 十       | +  | _        | 十           |
|                                 |             |               |  |                           |                      |                    |  | ╂─┤  |          | _         | <del> </del> | ┝╌╢        | _               |             | ╁─      | +  |          | +           |
| Date:                           | Time:       | Relinquist    | ned by:                                | Received by:              | <u> </u>             | I Pate             | Time   | Rem  | arks:    | Bill B    | ļ            | L-#        | L_              | <u> </u>    |         | ــــــــــــــــــــــــــــــــــــــ           |          |             |
| 13/2014                         | 821         | Jef           | 1 Blegg                                | Christy Wester 4/8/11 821 |                      |                    | Paykey: ZFEIRK0SJS  BP Contact: Jeff Peace Please copy results to: |  |          |           |              |            |                 |             |         |  |          |             |
| Date:                           | Time:       | Refinquish    | wdy Waller                             | Received by               | A no                 | Date<br>4/09/12/1/ | Time   |  | e.jeffr  |           |              |            |                 |             | 1 7 *   |  |          |             |
| If nec                          |             |               | Hall Environmental may be subcontracte | ed to other accredite     | d laboratories. This |                    |  | ility. An  | у вир-со | ntracted  | data w       | vill be cl | early no        | tated or    | the and | alytical r                                       | report.  |             |



