District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

۶

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration PCUD SEP 25 '14
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:EPNG Com B LS 3
API Number:3004510071 OCD Permit Number:
U/L or Qtr/QtrLSection32Township31NRange10WCounty:San Juan
Center of Proposed Design: Latitude36.852378 Longitude107.908998 NAD: ☐1927 ☒ 1983 Surface Owner: ☐ Federal ☒ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. ☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed — side walls not visible
Liner type: Thickness mil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptant material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
manerial are provided below. String erice ta does not apply to drying pads of above grade taines.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	No.
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	Yes No
watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	L Tes L No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. 	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC
 ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Finds of the following its mercure to attach ad to the application. Places indicate her advantage to the standard to the application.	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	aocuments are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
 ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 	
☐ Monitoring and Inspection Plan ☐ Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval of Within the area overlying a subsurface mine.		
Within the area overlying a subsurface mine.	btained from the municipality	☐ Yes ☐ No
- Written confirmation or verification or map from the NM EMNRD-Mining an	d Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Society; Topographic map	Mineral Resources; USGS; NM Geological	Yes No
Within a 100-year floodplain.		
- FEMA map		Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the forby a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Su Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) Protocols and Procedures - based upon the appropriate requirements of 19.15.17 Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19. Waste Material Sampling Plan - based upon the appropriate requirements of 19. Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill Soil Cover Design - based upon the appropriate requirements of Subsection H o Re-vegetation Plan - based upon the appropriate requirements of Subsection H o	ments of 19.15.17.10 NMAC bsection E of 19.15.17.13 NMAC priate requirements of Subsection K of 19.15.17 based upon the appropriate requirements of 19. 13 NMAC ments of 19.15.17.13 NMAC 15.17.13 NMAC cuttings or in case on-site closure standards cannot 19.15.17.13 NMAC f 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.		
Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate an	nd complete to the best of my knowledge and beli	ef.
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	
OCD Approval: Permit Application (including closure plan) Glosure Plan (o	nly) OCD Conditions (see attachment) Approval Date: 17/21/	Sayl
OCD Representative Signature: State OC	D Permit Number:	2017
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMA Instructions: Operators are required to obtain an approved closure plan prior to imp. The closure report is required to be submitted to the division within 60 days of the co section of the form until an approved closure plan has been obtained and the closure	D Permit Number: AC Ilementing any closure activities and submitting mpletion of the closure activities. Please do not	the closure report.
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMA Instructions: Operators are required to obtain an approved closure plan prior to imp. The closure report is required to be submitted to the division within 60 days of the co section of the form until an approved closure plan has been obtained and the closure	D Permit Number:	the closure report. complete this

Form C-144 Oil Conservation Division Page 5 of 6

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requires	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Peace	Date: _September 25, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

EPNG Com B LS 3 API No. 3004510071 Unit Letter K, Section 32, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

				38	шиа г	e, NIVI 8/3	103						
			Rele	ease Notific	atio	n and Co	orrective A	ction	····				
						OPERA'	ГOR	☐ Initi	al Report	\boxtimes	Final Report		
Name of Co	mpany: B	P				Contact: Jef							
		Court, Farmi	ngton, N	M 87401		Telephone 1	No.: 505-326-94	79		_			
		Com B LS 3					e: Natural gas v						
6 6 0	- C+ +		-										
Surface Ow	ner: State			Mineral C)wner:	State		API No	. 30045100	71			
			-			N OF RE	LEASE						
Unit Letter K	Section 32	Township 31N	Range 10W	Feet from the 1,650	North South	/South Line	Feet from the 1,650	East/West Line West	County: Sa	n Juan	l		
		Latit	u de 36	.852378		_ Longitud	e107.908998_						
				NAT	URE	OF REL	EASE						
Type of Rele							Release: N/A		Recovered: N				
		w grade tank –	95 bbl				lour of Occurrence	e: Date and	Hour of Disc	overy	:		
Was Immediate Notice Given?													
By Whom?						Date and F	lour						
Was a Water	course Read	ched?					lume Impacting t	he Watercourse.					
			Yes 🛚	No									
If a Watercou	ırse was Im	pacted, Descri	be Fully.*			<u>l</u>							
				n Taken.* Samplin and chloride belov				ne during removal ned.	to ensure no s	soil im	ipacts from		
				ten.* BGT was reactive well area.	moved a	and the area u	nderneath the BG	T was sampled. T	he area under	the B	GT was		
regulations al public health should their cor the environ	I operators or the envibre or the envi- operations had a ment. In a	are required to ronment. The nave failed to a	report ar acceptanc dequately CD accep	id/or file certain re te of a C-141 repo investigate and re	elease n ort by the emediat	otifications a e NMOCD m e contaminati	nd perform correctarked as "Final Roon that pose a three the operator of the correct of the corr	nderstand that purs tive actions for rele eport" does not reli eat to ground water responsibility for co	eases which releve the operary, surface wat	nay en ator of er, hui ith any	ndanger Tliability man health		
Signature:	John .	Passa	,				OIL CONS	<u>SERVATION</u>	<u>DIVISIO</u>	<u>N</u>			
Printed Name	Jeff Peac	e				Approved by	Environmental Sp	pecialist:					
Title: Area E	nvironment	al Advisor				Approval Dat	e:	Expiration	Date:				
E-mail Addre	ess: peace.je	effrey@bp.con	n			Conditions of	Approval:		Attached	Conditions of Approval:			

Date: September 25, 2014

Phone: 505-326-9479

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINE P.O. BOX 87, BLOOM		7/13	API#: 3004510071
CLICIT.	(505) 632		7413	TANK ID (if applicble): A
FIELD REPORT:	(circle one): BGT CONFIRMATION RELI	EASE INVESTIGATION / OT	rher:	PAGE#: _1 of _1
SITE INFORMATIO	N: SITE NAME: EPNG COM I	B LS #3		DATE STARTED: 06/08/12
	P: 31N RNG: 10W PM: N		J M	DATE FINISHED:
· · · · · · · · · · · · · · · · · · ·	650'W NE/SW LEASE TYPE: FEI			
	PROD. FORMATION: MV CONTRA			ENVIRONMENTAL SPECIALIST(S): JCB
REFERENCE POIN	T: WELL HEAD (W.H.) GPS COORD	36.85243 X 1	107.909	028 GL ELEV.: 6137'
1) 95 BGT (A) (DW/DB)	GPS COORD.: 36.852378	X 107.908998	DISTANCE/BE	ARING FROM W.H.: 100', S66E
2)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:
3)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:
4)	GPS COORD.:		DISTANCE/BE	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB US	SED: HALL		OVM READING (ppm)
1) SAMPLE ID:	SAMPLE DATE:SAMP	PLE TIME: 1334 LAB ANALYSIS	S: _ 418.1, 8	015, 8021, 300.00 (Chlor.) 0.0
2) SAMPLE ID:	SAMPLE DATE:SAMP	PLE TIME: LAB ANALYSIS	3:	
3) SAMPLE ID:	SAMPLE DATE:SAMP	PLE TIME: LAB ANALYSIS	3:	
4) SAMPLE ID:	SAMPLE DATE: SAMP	PLE TIME: LAB ANALYSIS	S:	
SOIL DESCRIPTIO	N: SOIL TYPE: SAND / SILTY SAND /	SILT / SILTY CLAY / CLAY	/ GRAVEL	/OTHER
SOIL COLOR:				
COHESION (ALL OTHERS): NON COHESIVE / SLIGH		, ,		C / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC
CONSISTENCY (NON COHESIVE SOILS): MOISTURE DRY/SLIGHTLY MOIST / MOIST /				FT / FIRM / STIFF / VERY STIFF / HARD PLANATION
SAMPLE TYPE: GRAB / COMPOSITE	-# OF PTS 5		/[NO] LXI	LANATION -
DISCOLORATION/STAINING OBSERV	ED: YES NO EXPLANATION -			
ANY AREAS DISPLAYING WETNESS: YES /	NO EYPLANATION -			
-	OBSERVED AND/OR OCCURRED: Y /	EXPLANATION:		
ADDITIONAL COMMENTS:				
EXCAVATION DIMENSIONS (if applical	ole): NA ft. X NA ft. X	NA ft. cu	hic vards ex	cavated (if applicable):
	EAREST WATER SOURCE: >1,000' NEARES			
SITE SKETCH	PI	OT PLAN circle: attach	ed OVM	CALIB. READ. = 52.8 ppm DE - 0.53
				CALIB. READ. = 52.8 ppm RF = 0.52 CALIB. GAS = 100 ppm
		•	_	1:00 am(pm) DATE: 06/08/12
				MISCELL. NOTES
⊕ WELL			1	0: N1593516
HEAD) #:82749
	X	PBGTL	PH	
	(x x x) ←	—— ТВ ~ 6'		#:
	X	B.G.	oc	CD Appr. date(s): 01/05/12
			,	
			Tani ID	Permit date(s): 06/14/10
			11-	BGT Sidewalls Visible: Y / N
		X - S.P.D	<u>). </u> —	BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
	/ATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT D		ALL:	
	E; SW - SINGLE WALL; DW - DOUBLE WALL; SB - SINGLE B		" _ <u>IV</u>]	agnetic declination: 10 °E
TRAVEL NOTES: CALLOUT:	. 0	NSITE: 06/08/12		

revised: 04/10/12 BEI1005E-4.SKF

Analytical Report

Lab Order 1206510

Date Reported: 6/19/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg EngineeringProject: EPNG COM B LS3

Client Sample ID: 95 BGT 5-pt @ 6'

Collection Date: 6/8/2012 1:34:00 PM

Lab ID: 1206510-001 Matrix: SOIL Received Date: 6/13/2012 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.6	mg/Kg	1	6/15/2012 10:00:50 AM
Surr: DNOP	116	77.6-140	%REC	1	6/15/2012 10:00:50 AM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	6/18/2012 2:36:05 AM
Surr: BFB	92.5	69.7-121	%REC	1	6/18/2012 2:36:05 AM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.047	mg/Kg	1	6/15/2012 7:21:16 PM
Toluene	ND	0.047	mg/Kg	1	6/15/2012 7:21:16 PM
Ethylbenzene	ND	0.047	mg/Kg	1	6/15/2012 7:21:16 PM
Xylenes, Total	ND	0.095	mg/Kg	1	6/15/2012 7:21:16 PM
Surr: 4-Bromofluorobenzene	97.9	80-120	%REC	1	6/15/2012 7:21:16 PM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	ND	7.5	mg/Kg	5	6/18/2012 11:04:38 AM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	19	mg/Kg	1	6/18/2012

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit
- U Samples with CalcVal < MDL

Hall Environmental Analysis Laboratory, Inc.

WO#: 1206510

19-Jun-12

Client:

Blagg Engineering

Project:

EPNG COM B LS3

Sample ID MB-2426

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 2426

PQL

RunNo: 3496

Prep Date: 6/17/2012

Analysis Date: 6/18/2012

Result

SeqNo: 98288

Units: mg/Kg

Analyte Petroleum Hydrocarbons, TR

ND

100.0

100.0

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

RPDLimit

Qual

Prep Date: 6/17/2012

Sample ID LCS-2426

SampType: LCS

Batch ID: 2426

Analysis Date: 6/18/2012

TestCode: EPA Method 418.1: TPH RunNo: 3496

SeqNo: 98292

HighLimit

Units: mg/Kg

115

Analyte Petroleum Hydrocarbons, TR

Client ID: LCSS

Result

PQL

SPK value SPK Ref Val

%REC 98.6

LowLimit 87.8

TestCode: EPA Method 418.1: TPH

%RPD

RPDLimit

Qual

Qual

Sample ID LCSD-2426

Prep Date: 6/17/2012

LCSS02

SampType: LCSD

99

Batch ID: 2426

20

20

RunNo: 3496

Units: mg/Kg

RPDLimit

Analyte Petroleum Hydrocarbons, TR

Client ID:

Analysis Date: 6/18/2012 Result **PQL**

100

SPK value SPK Ref Val

SeqNo: 98293

%REC LowLimit

102

HighLimit 87.8

%RPD 115 3.86

8.04

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits R

В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit Reporting Detection Limit

RL

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

Result

49

4.8

10

WO#: 1206510 19-Jun-12

RPDLimit

%RPD

Client:

Blagg Engineering

Project:

Analyte

Surr: DNOP

Diesel Range Organics (DRO)

EPNG COM B LS3

Sample ID MB-2387	SampType: MBLK	TestCode: EPA Method	d 8015B: Diesel Range	Organics	
Client ID: PBS	Batch ID: 2387	RunNo: 3454			
Prep Date: 6/14/2012	Analysis Date: 6/15/2012	SeqNo: 96646			
Analyte	Result PQL SPK value	ie SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10				
Surr: DNOP	12 10.0	0 115 77.6	140		
Sample ID LCS-2387	SampType: LCS	TestCode: EPA Method	8015B: Diesel Range	Organics	-
Client ID: LCSS	Batch ID: 2387	RunNo: 3454			
Prep Date: 6/14/2012	Analysis Date: 6/15/2012	SegNo: 97001	Units: mg/Kg		

SPK value SPK Ref Val %REC

50.00

5.000

HighLimit

140

LowLimit

52.6

77.6

97.3

96.1

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1206510

19**-**Jun-12

Client:

Blagg Engineering

Project:

EPNG COM B LS3

Sample ID MB-2369	SampT	SampType: MBLK TestCode: EPA Method 8015B: Gasoline Range								
Client ID: PBS Batch ID: 2369 RunNo: 3471										
Prep Date: 6/13/2012	Analysis D	ate: 6/	15/2012	2 SeqNo: 97259 Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	940		1000		93.8	69.7	121			

Sample ID LCS-2369	Sampl	ype: LC	s	TestCode: EPA Method 8015B: Gasoline Range										
Client ID: LCSS	Batcl	n ID: 23	69	F	RunNo: 3	471								
Prep Date: 6/13/2012	Analysis [ate: 6/	15/2012	S	SeqNo: 9	7263	Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	28	5.0	25.00	0	113	98.5	133							
Surr: BFB	1000		1000		101	69.7	121							

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1206510

19-Jun-12

Client: Project: Blagg Engineering

EPNG COM B LS3

Sample ID MB-2369

SampType: MBLK

TestCode: EPA Method 8021B: Volatiles

Client ID:

PBS

Batch ID: 2369

RunNo: 3471

Prep Date:

Analysis Date: 6/15/2012

6/13/2012

SeqNo: 98203

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

HighLimit

RPDLimit %RPD

Qual

Analyte Benzene Toluene

Ethylbenzene

Xylenes, Total

Result **PQL** ND 0.050

ND

0.96

ND 0.050 ND 0.050

0.10

1.000

96.0

120

Sample ID LCS-2369 Client ID:

LCSS

Surr: 4-Bromofluorobenzene

SampType: LCS

Batch ID: 2369

RunNo: 3471

TestCode: EPA Method 8021B: Volatiles

80

Prep Date:

6/13/2012

Analysis Date: 6/15/2012

SeqNo: 98204

Units: mg/Kg

%RPD **RPDLimit** Qual

Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit 1.0 0.050 1.000 0 103 83.3 107 Benzene 0.050 1.000 0 99.3 74.3 Toluene 0.99 115 0.96 0.050 1.000 0 95.8 80.9 122 Ethylbenzene 3.000 85.2 2.9 0 96.1 123 Xylenes, Total 0.10 Surr: 4-Bromofluorobenzene 1.0 1.000 101 80 120

Qualifiers:

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits R

В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Reporting Detection Limit

RL

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins Nt. Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	_		Wo	ork Orc	ler N	lumb	er: 1	206510					
Received by/d	late:		nelizin	C										
Logged By:	Lindsay Ma	angin	6/13/2012 10:0	00:00 AM				O me	lyHl ag io UU ~					
Completed By: Lindsay Mangin 6/13/2012 10:41:13 AN								Jung	ly Hlageo					
Reviewed By: A DUISIZ														
Chain of Cu	ustody /	′ (()												
1. Were sea	ıls intaot?				Yes		No	•	Not P	resent	~			
2. Is Chain	2 Is Chain of Custody complete?						No		Not P	resent				
3. How was	3. How was the sample delivered?													
<u>Log In</u>														
4. Coolers are present? (see 19. for cooler specific information)						V i	No			NA				
5. Was an a	5. Was an attempt made to cool the samples?						No			NA	,			
6. Were all	samples receive	ed at a temperatu	re of >0° C to 6.	0°C	Yes	.	No	• !		NA				
7. Sample(s	s) in proper conta	ainer(s)?			Yes	V	No							
8. Sufficient	8. Sufficient sample volume for indicated test(s)?						No	:						
9. Are samp	oles (except VO	A and ONG) prop	erly preserved?		Yes	•	No	;						
10. Was pres	servative added	to bottles?			Yes		No	✓.		NA				
11 VOA vials	s have zero head	dspace?			Yes	-	No		No VOA	A Vials	√ :			
		ners received brol	ken?		Yes		No	·	:					
13. Does par	perwork match b crepancles on cl	ottle labels?			Yes	· V	No	:	· t	f of pres pottles c or pH:				
14. Are matri	ices correctly ide	entified on Chain	of Custody?		Yes	√ .	No		•	ψ. p	(<	2 or >12	unless r	ioted)
15. Is it clear	what analyses v	were requested?			Yes	✓	No			Ad	ljusted?			
	holding times ab		•		Yes	✓	No	•						
• •	tify customer for	•							į	Ch	ecked b	y:		
	ndling (if app					, ,			*					
17. Was clie	nt notified of all o	discrepancies wit	h this order?		Yes	: !	No	:		NA	.•			
Per	son Notified:			Date:										
_	Whom:	Anniel de La Lacianie de la Calenda de L	Management of the state of the	Via:	eMa	il :	P	none	Fax	In	Person			
	arding:					~~~				*************		Manage.		
	ent Instructions:	1												
18. Additiona	al remarks:													
19. Cooler I														
Coole				al No S	eal Da	te	<u> </u>	Sign	ed By	-	•			
[!	1.1	Good Y	US							.1				

Client: BLAGE ENGINEERING INC. BP AMERICA Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 97413 Phone #: 505-632-1199 email or Fax#:			Turn-Around Time: Standard □ Rush Project Name:					HALL ENVIRONMENTAL ANALYSIS LABORATORY														
																					,	
								www.hallenvironmental.com														
			EPNG COM B LS 3 Project #:				4901 Hawkins NE - Albuquerque, NM 87109															
										5-34				-	-		-4 10					
			Project Manager:							**			-		num egg 1						Ŧ	
QA/QC Package: Standard				JEPF BLAGG Sampler: JEFF BLAGG				(8021)	+ TPH (Gas only)	as/Dies					04,50	PCB's						
Accreditation				Sampler:	IBSS R.	A1_6		± TMB's	Ĭ,	Ö			- 1		02,1)82					i	1.
□ NEL		□ Othe	г	Ondices of Syles of No.					Ħ	15B	8.1	4.	F		3,E	/8(<u></u>	. 1			Įź
□ EDD (Type)			Samolealem	obiotujer d	Total Sales	a de la companya de		삤	8	441	d 5(P. P.	als	8	des		Ò	المد			,	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type			BTEX & WIBE	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHUNEIDE		Š	Air Ruhhlos /
98/12	1334	Sol	95 BGT 5-PEC. 6	40ex1	COOL	-0	<u>ا</u>	χ		X	<u>k</u>	_				$\tilde{}$			X		<u> </u>	f
																			1	十	+	十
						ļ			\dashv	-+	_		\dashv	_		-		_	\dashv		+	+
	<u> </u>									-	\dashv		\dashv	_	\dashv				\dashv		+	+
					1					_	_		_									\perp
h												į	Ī		ĺ							Γ
			- 																	\top		厂
												\top	\neg				\neg	_		_	+	+
		_								_	-	\dashv		-+	-	-	\dashv	-	-+	+	+	十
								\dashv	_	\dashv	\dashv	\dashv	-	-	-					+		⊬
						<u> </u>			_	_		-	-		-	-				+		╀
										4	_	_	_	_	_		_	_				Ļ
						<u></u>																L
Date: 6/12/12	Time: 0935	Relinquishe	od by: UBlegg	Received by:	Westers	6.1	0935	Rem With	arks:	ے : م	7R0	∀	DRI	0	0~	8	015	B				
Date:	Time:	Relinduishe	ed by:	Received by	ime	WO: N 1593516 PK: 2 SCHWLBGT																
/12/12 1610 Christie Waster										JEFK PEACE												
Ti .	Fnacaecani	eam	nitted to Hall Environmental may be subc	ontracted to other ac	creditor laborators	E This serves as	notice of this	noccih	ilita A	nu nuh				عط الله	ماممیار				-1. 1° -1			



