

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-043-21196
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. NM 16586
7. Lease Name or Unit Agreement Name Lybrook E33-2307
8. Well Number 02H
9. OGRID Number 282327
10. Pool name or Wildcat Alamito-Gallup
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6853' GR

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Encana Oil & Gas (USA) Inc.

3. Address of Operator
370 17th Street, Suite 1700 Denver, CO 80202

4. Well Location
 Unit Letter E : 1770 feet from the NORTH line and 545 feet from the WEST line
 Section 33 Township 23N Range 7W NMPM County SANDOVAL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER: Production Casing/Cement

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized high performance water based mud from intermediate casing point (5507'MD) to TD of lateral.

Kicked off lateral at 4386' on 9/08/14. Landed lateral at 5708' on 9/11/14. Length of lateral: 4422'. TD of 10,130'MD/4998'TVD reached 9/13/14. Set production liner 9/13/14.

Hole diameter: 6.125", production string diameter: 4.5", production string weight and grade: 11.6# SB80 LTC. Depth of 6.125" hole from 5587'-10,130'MD. Float shoe at 10,128'MD. Float collar at 10,086'MD. Production liner set from 5346'-10,130'MD.

Set 13 external swellable casing packers for isolation of production string at the following depths: (1) 9779' (2) 9432' (3) 9079' (4) 8734' (5) 8382' (6) 8025' (7) 7672' (8) 7320' (9) 6975' (10) 6630' (11) 6287' (12) 5944' (13) 5601'

Spud Date: 9/4/14

Rig Release Date: 9/14/14 ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cristi Bauer TITLE Operations Technician DATE 9/23/14

Type or print name Cristi Bauer E-mail address: Cristi.Bauer@encana.com PHONE: 720-876-5867

For State Use Only

APPROVED BY: [Signature] TITLE AV DATE 9/30/14
 Conditions of Approval (if any):