

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

CONFIDENTIAL

WELL API NO. 30-043-21198
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. ST NM V-1697, ST NM LG-3924
7. Lease Name or Unit Agreement Name Lybrook P32-2307
8. Well Number 01H
9. OGRID Number 282327
10. Pool name or Wildcat Alamito-Gallup

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	OIL CONS. DIV DIST. 3
2. Name of Operator Encana Oil & Gas (USA) Inc.	NOV 03 2014
3. Address of Operator 370 17th Street, Suite 1700 Denver, CO 80202	

4. Well Location Unit Letter <u>P</u> : <u>664</u> feet from the <u>SOUTH</u> line and <u>31</u> feet from the <u>EAST</u> line Section <u>32</u> Township <u>23N</u> Range <u>7W</u> NMPM County <u>SANDOVAL</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6874' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐  
OTHER: Production Liner ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized high performance water based mud from intermediate casing point (5089'MD) to TD of lateral.

Kicked off lateral at 3338' on 9/6/14. Landed lateral at 5731' on 9/18/14. Length of lateral: 3899'. TD of 9630'MD/4973'TVD reached 9/20/14. Set production liner 9/21/14.

Hole diameter: 6.125", production string diameter: 4.5", production string weight and grade: 11.6# SB80 LTC. Depth of 6.125" hole from 5485'-9630'MD. Float shoe at 9629'MD. Float collar at 9586'MD. Production liner set from 4903'-9630'MD.

Set 12 external swellable casing packers for isolation of production string at the following depths: (1) 9282' (2) 8940' (3) 8585' (4) 8227' (5) 7878' (6) 7522' (7) 7166' (8) 6816' (9) 6471' (10) 6125' (11) 5777' (12) 5433'

Spud Date: 9/3/14

Rig released 9/21/14 ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cristi Bauer TITLE Operations Technician DATE 10/29/14

Type or print name Cristi Bauer E-mail address: Cristi.Bauer@encana.com PHONE: 720-876-5867  
For State Use Only

APPROVED BY: [Signature] TITLE DEPUTY OIL & GAS INSPECTOR DATE 11/7/14  
Conditions of Approval (if any): AV