

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

David Martin
Cabinet Secretary

Brett F. Woods, Ph.D.
Deputy Cabinet Secretary

David R. Catanach
Division Director
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 1-19-15

Well information;

Operator WPX, Well Name and Number NE Charco Com # 263H

API# 30-039-31298, Section 5, Township 23 N/S, Range 06 E/W

Conditions of Approval:

(See the below checked and handwritten conditions)

- Notify Aztec OCD 24hrs prior to casing & cement.
- Hold C-104 for directional survey & "As Drilled" Plat
- Hold C-104 for NSL NSP, DHC
- Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
 - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
 - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
 - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.



NMOCD Approved by Signature

2-19-2015
Date 

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JAN 20 2015

APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
NMNM086033

6. If Indian, Allottee or Tribe Name

1a. Type of Work: DRILL REENTER

1b. Type of Well: Oil Well Gas Well Other Single Zone Multiple Zone

2. Name of Operator
WPX Energy Production, LLC

3a. Address
P.O. Box 640 Aztec, NM 87410

3b. Phone No. (include area code)
(505) 333-1849

4. Location of Well (Report location clearly and in accordance with any State requirements. *)
At surface 2425' FNL & 231' FWL, sec 5, T23N, R6W
At proposed prod. zone 2002' FSL & 230' FEL, sec 5, T23N, R6W

7. If Unit or CA Agreement, Name and No.
CA 132829

8. Lease Name and Well No.
NE Chaco COM #263H

9. API Well No.
30-039-31298

10. Field and Pool, or Exploratory
Chaco Unit NE HZ (OIL)

11. Sec., T., R., M., or Bk. and Survey or Area
SHL: Section 5, T23N, R6W
BHL: Section 5, T23N, R6W

12. County or Parish
Rio Arriba County

13. State
NM

14. Distance in miles and direction from nearest town or post office*
approximately 4 miles east of Lybrook, New Mexico

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 231'

16. No. of Acres in lease
80

17. Spacing Unit dedicated to this well
640.56 acres

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 22'

19. Proposed Depth
11,399' MD / 5,561' TVD

20. BLM/BIA Bond No. on file
UTB000178

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
6882' GR

22. Approximate date work will start*
March 1, 2015

23. Estimated duration
1 month

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature: *Andrea Felix* Name (Printed/Typed): Andrea Felix Date: 1-19-15

Title: Regulatory Specialist Senior

Approved by (Signature): *[Signature]* Name (Printed/Typed): Date: 2/10/15

Title: AEM Office: FFO

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

WPX Energy Production, LLC, proposes to develop the Chaco Unit NE HZ (OIL) pool at the above described location in accordance with the attached drilling and surface use plans.

The well pad surface is on lease under jurisdiction of BLM FFO and is co-located with the NE Chaco COM #253H.

This location has been archaeologically surveyed by La Plata Archaeological Consultants. Copies of their report have been submitted directly to the BLM.

New access road is approximately 209' on lease on BLM surface.

New pipeline is approximately 328.2' on lease on BLM surface.

BLM'S APPROVAL OR ACCEPTANCE OF THIS ACTION DOES NOT RELIEVE THE LESSEE AND OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS"

NMCCDA

District I
1625 N. French Drive, Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II
811 S. First Street, Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV
1220 S. St. Francis Drive, Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department

Form C-102
Revised August 1, 2011

Submit one copy to
Appropriate District Office

OIL CONSERVATION DIVISION
1220 South St. Francis Drive
Santa Fe, NM 87505



JAN 20 2015

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-039-31298		*Pool Code 98088	*Pool Name CHACO UNIT NE HZ
*Property Code 313800	*Property Name NE CHACO COM		*Well Number 263H
*OGRID No. 120782	*Operator Name WPX ENERGY PRODUCTION, LLC		*Elevation 6882'

¹⁰ Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	5	23N	6W		2425	NORTH	231	WEST	RIO ARRIBA

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	5	23N	6W		2002	SOUTH	230	EAST	RIO ARRIBA

¹² Dedicated Acres 640.56 Acres Entire Section	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No. R-13817A 9,237.3 acres
---	-------------------------------	----------------------------------	---

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION





¹⁷ OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom-hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.
Signature: *Andrea Felix* Date: 1-19-2015
Printed Name: Andrea Felix
E-mail Address: andrea.felix@wpxenergy.com

¹⁸ SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.
Date Revised: DECEMBER 19, 2014
Survey Date: DECEMBER 17, 2013
Signature and Seal of Professional Surveyor

Certificate Number 15269

**WPX ENERGY PRODUCTION, LLC NE CHACO COM #263H
 PROPOSED ACCESS ROAD SURVEY LOCATED IN THE
 NE/4 SE/4 OF SECTION 6 & W/2 W/2 OF SECTION 5, T23N, R6W
 NMPM, RIO ARriba COUNTY, NEW MEXICO**



PLAT NOTE:
 BEFORE ANY CONSTRUCTION BEGINS,
 CONTRACTOR IS ADVISED TO CALL
 ONE-CALL FOR LOCATION OF ANY
 MARKED OR UNMARKED PIPELINES OR
 CABLES IN THE AREA OF THE PROJECT

BASIS OF BEARING:
 REAL-TIME KINEMATIC GPS SURVEY
 SOLUTION OBTAINED FROM SATELLITES
 TRACKED ON JANUARY 15, 2014 FROM
 A REFERENCE STATION POSITIONED IN
 NW/4 NW/4 OF SECTION 6, T23N, R6W



~ SURFACE OWNERSHIP ~ Bureau of Land Management	
0+00 TO 2+09.0	209.0 FT / 12.7 RODS

I, Jason C. Edwards, a registered Professional Surveyor under the laws of the State of New Mexico, hereby certify that this plat was prepared from field notes of an actual survey meeting the minimum requirements of the standards for easement surveys and is true and correct to the best of my knowledge and belief.

JASON C. EDWARDS Date: December 19, 2014
 Jason C. Edwards, P.L.S.
 New Mexico L.S. #15269

Prepared for: WPX ENERGY PRODUCTION P.O. BOX #640 AZTEC, NM 87410		Land Surveyor: Jason C. Edwards Mailing Address: Post Office Box 6612 Farmington, NM 87499 Business Address: 111 East Pinon Street Farmington, NM 87402 (505) 325-2654 (Office) (505) 326-5650 (Fax)	CHECKED BY: JCE DRAWN BY: NJK
		SURVEYS, INC.	SHEET 4 OF 7 FILENAME: 23065A1

WPXENERGY.

WPX ENERGY

Operations Plan

(Note: This procedure will be adjusted on site based upon actual conditions)

DATE: 12/16/2014 **FIELD:** Chaco Unit NE HZ (Oil)
WELL NAME: NE Chaco Com #263H **SURFACE:** BLM
SH Location: SWNW 5-23N-6W **ELEVATION:** 6882' GR
BH Location: NESE 5-23N-6W **MINERALS:** BLM
Rio Arriba County, NM

MEASURED DEPTH: 11,399'

I. **GEOLOGY:** Surface formation – San Jose

A. **FORMATION TOPS:** (KB)

Name	MD	TVD	Name	MD	TVD
Ojo Alamo	1565	1544	Point Lookout	4511	4336
Kirtland	1639	1614	Mancos	4756	4568
Picture Cliffs	2127	2077	Kickoff Point	5024	4822
Lewis	2237	2181	Top Target	5918	5563
Chacra	2589	2515	Landing Point	6266	5650
Cliff House	3738	3604	Base Target	6266	5650
Menefee	3780	3643			
			TD	11399	5561

- B. **MUD LOGGING PROGRAM:** Mudlogger on location from surface csg to TD.
C. **LOGGING PROGRAM:** LWD GR from surface casing to TD.
D. **NATURAL GAUGES:** Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

II. **DRILLING**

- A. **MUD PROGRAM:** LSND mud (WBM) will be used to drill the 12-1/4" Surface hole, the 8 3/4" Directional Vertical hole, and the curve portion of the wellbore. A LSND (WBM) or (OBM) will be used to drill the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.
- B. **BOP TESTING:** While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The anticipated reservoir is expected to be less than 1300 psi, so the BOPE will be tested to **250 psi (Low) for 5 minutes** and **1500 psi (High) for 10 minutes**. Pressure test surface casing to **600 psi for 30 minutes** and intermediate casing to **1500 psi for 30 minutes**. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. The drum brakes will be inspected and tested each tour. **All tests and inspections will be recorded in the tour book as to time and results.**

III. MATERIALS**A. CASING PROGRAM:**

<u>CASING TYPE</u>	<u>OH SIZE (IN)</u>	<u>DEPTH (MD) (FT)</u>	<u>CASING SIZE (IN)</u>	<u>WEIGHT(LB)</u>	<u>GRADE</u>
Surface	12.25"	400'+	9.625"	36#	J-55
Intermediate	8.75"	6266'	7"	23#	K-55
Prod. Liner	6.125"	6116' - 11399'	4-1/2"	11.6#	N-80
Tie-Back String	N/A	Surf. - 6116'	4-1/2"	11.6#	N-80

B. FLOAT EQUIPMENT:

- SURFACE CASING:** 9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.
- INTERMEDIATE CASING:** 7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,700 ft., 2,500' ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft.
- PRODUCTION LINER:** Run 4-1/2" Liner with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSI (Sliding Sleeve) positioned inside the 330ft Hard line. Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers. Set seals on Liner Hanger. Test TOL to 1500 psi for 15 minutes.
- TIE-BACK CASING:** None

C. CEMENTING:

(Note: Volumes may be adjusted onsite due to actual conditions)

- SURFACE:** 10 bbl Fr Water Spacer + 190 sx (222.3 cu.ft.) of "Premium Cement" + 2% Calcium Chloride Cement + 0.125# pps of Poly-E-Flake, 15.8 #/gal (1.17 cu ft./sk, Vol 39.58 Bbls.). The 100% excess should circulate cement to the surface. WOC 12 hours. Test csg to 600psi. Total Volume: (222.3 cu-ft/190 sx/39.6 Bbls). TOC at Surface.
- INTERMEDIATE:** 20 bbl (112 cu-ft) Mud Flush III spacer + Lead: +/- 700 sx Foamed 50/50 Poz Cement. 13.0 ppg + 0.1% Halad 766 + 0.2% Versaset + 1.5% Chem-Foamer 760 (Yield :1.43 cu-ft/ sk. / Vol: 1216 cu-ft / 216.5 Bbls.) + TAIL: 100.sx 13.5 #/gal. + 0.2% Versaset + 0.15% HALAD-766 (Yield: 1.28 cu-ft / sk / Vol: 128 cu-ft / 22.8 Bbls.). + Fresh Water Displacement (1,362 cu-ft / +/- 242 Bbls) + 100 sx Top-Out Cement Premium: Yield: (1.17 cu-ft/ sk / (Vol: 117 cu-ft / 20.8 Bbls), WOC 12 hrs. Test Casing to 1500 PSI for 30 minutes. Total Cement Volume: (900 sx / 1461 cu-ft / 260 bbls). Mix with +/- 84,000 SCF Nitrogen. TOC at surface.
- PRODUCTION LINER:** **STAGE 1:**10 bbl (56.cu-ft) Fr Water Spacer. **STAGE 2:**40 bbl 9.5 ppg (224.6 cu-ft) Tuned Spacer III + 0.5 gal/bbl Musol + 38.75 ppb Barite + 0.5 gal/bbl SEM-7. **STAGE 3:** 10 bbl Fr Water Spacer. **STAGE 4: Lead Cement:** 50 / 50 Poz Premium + 0.2% Versaset + 0.2% Halad -766, Yield 1.43 cu ft/sk; 13.0 ppg, (10 sx / 14.3 cu ft. / 2.5 bbls). **STAGE 5:** 200 sx. Foamed Lead Cement: 50 / 50 Poz Standard + 0.2% Versaset + 0.2% HALAD-766 + 1.5% Chem-Foamer 760. Yield 1.97 cu-ft/sk. 13.0 ppg (200 sx / 394 cu-ft. / 70.2 bbls.). **STAGE 6:** Tail Cement : 100 sx. 50/50 Poz Standard + 0.2% Versaset + 0.05% HALAD-766 + .05% SA-1015, Weight: 13.5 ppg (100 sx / Yield 1.28 cu ft/sk. / 128 cu ft. / 22.8 bbls) **STAGE 7:** Displace w/ +/- 137 bbl Fr Water. Total Cement (563.3 cu ft / 95.5 bbls). Mix Foamed Cement w/ +/- 75,000 SCF Nitrogen. Est. TOC +/- 5,644 ft.

IV. COMPLETION

A. CBL

1. Run CCL for perforating.

B. PRESSURE TEST

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

C. STIMULATION

1. Stimulate with approximately 2,805,000# 20/40 mesh sand and 340,000# 16/30 mesh sand in 619,113 gallons water with 42,696 mscf N2 for 17 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

D. RUNNING TUBING

1. Production Tubing: Run 2-7/8", 6.5#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing near Top of Liner.

- Although this horizontal well will be drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15 B(4) NMAC.

NOTE:

Installation of RSI sleeves at Toe of Lateral.

Proposed Operations:

A 4-1/2" 11.6# N-80 Liner will be run to TD and landed +/- 150 ft. into the 7" 23# K-55 Intermediate casing with a Liner Hanger and pack-off assembly then cemented to top of liner hanger.

After cementing and TOL clean up operations are complete, the TOL will be tested to 1500 psi (per BLM).

The Drilling Rig will be rigged down at this point and Completion operations will begin.

A 4-1/2" 11.6# N-80 tie-back string with seal assembly will be run and stung into the PBR of the liner hanger, tested to 1500 PSI and hung off at the surface. After Stimulation and Testing operations are complete the 4-1/2" tie-back string will be removed from the well.



SAN JUAN BASIN

SJ 05-23N-06W

253 - 263 Pad

NE Chaco Com #263H - Slot 263

Wellbore #1

Plan: Plan #2 10Dec14 kjs

Standard Planning Report - Geographic

10 December, 2014

Database:	COMPASS-SANJUAN	Local Co-ordinate Reference:	Well NE Chaco Com #263H - Slot 263
Company:	SAN JUAN BASIN	TVD Reference:	WELL @ 6896.00usft (Original Well Elev)
Project:	SJ 05-23N-06W	MD Reference:	WELL @ 6896.00usft (Original Well Elev)
Site:	253 - 263 Pad	North Reference:	True
Well:	NE Chaco Com #263H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #2 10Dec14 kjs		

Project	SJ 05-23N-06W, San Juan county, NM		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico West 3003		

Site	253 - 263 Pad				
Site Position:	Northing:	1,911,888.80 usft	Latitude:	36.2540600	
From:	Map	Easting:	598,260.46 usft	Longitude:	-107.5000700
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	0.20 °

Well	NE Chaco Com #263H - Slot 263					
Well Position	+N/-S	0.00 usft	Northing:	1,911,868.30 usft	Latitude:	36.2540037
	+E/-W	0.00 usft	Easting:	598,258.03 usft	Longitude:	-107.5000785
Position Uncertainty		0.00 usft	Wellhead Elevation:	0.00 usft	Ground Level:	6,882.00 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	11/13/2014	9.31	63.01	50,150

Design	Plan #2 10Dec14 kjs			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	110.09

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
550.00	0.00	0.00	550.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,480.88	18.62	326.24	1,464.59	124.63	-83.31	2.00	2.00	0.00	326.24	
5,023.93	18.62	326.24	4,822.23	1,065.00	-711.91	0.00	0.00	0.00	0.00	
5,861.94	60.00	109.69	5,534.80	1,052.00	-397.90	9.00	4.94	17.12	147.80	
5,921.94	60.00	109.69	5,564.80	1,034.49	-348.98	0.00	0.00	0.00	0.00	
6,266.34	90.99	110.09	5,650.00	922.33	-39.29	9.00	9.00	0.12	0.78	
11,398.96	90.99	110.09	5,561.00	-840.85	4,780.16	0.00	0.00	0.00	0.00	TD / PBHL #263H



WPX
Planning Report - Geographic

Database:	COMPASS-SANJUAN	Local Co-ordinate Reference:	Well NE Chaco Com #263H - Slot 263
Company:	SAN JUAN BASIN	TVD Reference:	WELL @ 6896.00usft (Original Well Elev)
Project:	SJ 05-23N-06W	MD Reference:	WELL @ 6896.00usft (Original Well Elev)
Site:	253 - 263 Pad	North Reference:	True
Well:	NE Chaco Com #263H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #2 10Dec14 kjs		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.00	0.00	0.00	0.00	0.00	0.00	1,911,868.30	598,258.03	36.2540037	-107.5000785
200.00	0.00	0.00	200.00	0.00	0.00	1,911,868.30	598,258.03	36.2540037	-107.5000785
400.00	0.00	0.00	400.00	0.00	0.00	1,911,868.30	598,258.03	36.2540037	-107.5000785
550.00	0.00	0.00	550.00	0.00	0.00	1,911,868.30	598,258.03	36.2540037	-107.5000785
Start Build 2.00									
600.00	1.00	326.24	600.00	0.36	-0.24	1,911,868.66	598,257.79	36.2540047	-107.5000793
800.00	5.00	326.24	799.68	9.06	-6.06	1,911,877.34	598,251.94	36.2540286	-107.5000991
1,000.00	9.00	326.24	998.15	29.32	-19.60	1,911,897.56	598,238.33	36.2540842	-107.5001450
1,200.00	13.00	326.24	1,194.44	61.04	-40.80	1,911,929.20	598,217.02	36.2541714	-107.5002169
1,400.00	17.00	326.24	1,387.58	104.07	-69.57	1,911,972.13	598,188.11	36.2542896	-107.5003145
1,480.88	18.62	326.24	1,464.59	124.63	-83.31	1,911,992.65	598,174.29	36.2543461	-107.5003611
Hold 18.62° Inc, 326.24° Az									
1,600.00	18.62	326.24	1,577.47	156.25	-104.45	1,912,024.19	598,153.05	36.2544329	-107.5004328
1,800.00	18.62	326.24	1,767.01	209.33	-139.93	1,912,077.15	598,117.38	36.2545787	-107.5005531
2,000.00	18.62	326.24	1,956.54	262.41	-175.41	1,912,130.11	598,081.72	36.2547246	-107.5006735
2,200.00	18.62	326.24	2,146.07	315.50	-210.90	1,912,183.07	598,046.05	36.2548704	-107.5007938
2,400.00	18.62	326.24	2,335.61	368.58	-246.38	1,912,236.03	598,010.39	36.2550162	-107.5009142
2,600.00	18.62	326.24	2,525.14	421.66	-281.86	1,912,288.99	597,974.72	36.2551620	-107.5010345
2,800.00	18.62	326.24	2,714.68	474.74	-317.35	1,912,341.95	597,939.05	36.2553079	-107.5011549
3,000.00	18.62	326.24	2,904.21	527.83	-352.83	1,912,394.91	597,903.39	36.2554537	-107.5012752
3,200.00	18.62	326.24	3,093.74	580.91	-388.32	1,912,447.87	597,867.72	36.2555995	-107.5013956
3,400.00	18.62	326.24	3,283.28	633.99	-423.80	1,912,500.83	597,832.06	36.2557453	-107.5015159
3,600.00	18.62	326.24	3,472.81	687.07	-459.28	1,912,553.79	597,796.39	36.2558912	-107.5016363
3,800.00	18.62	326.24	3,662.35	740.16	-494.77	1,912,606.75	597,760.72	36.2560370	-107.5017566
4,000.00	18.62	326.24	3,851.88	793.24	-530.25	1,912,659.71	597,725.06	36.2561828	-107.5018770
4,200.00	18.62	326.24	4,041.41	846.32	-565.73	1,912,712.67	597,689.39	36.2563286	-107.5019973
4,400.00	18.62	326.24	4,230.95	899.40	-601.22	1,912,765.63	597,653.72	36.2564744	-107.5021177
4,600.00	18.62	326.24	4,420.48	952.49	-636.70	1,912,818.59	597,618.06	36.2566203	-107.5022380
4,800.00	18.62	326.24	4,610.02	1,005.57	-672.19	1,912,871.55	597,582.39	36.2567661	-107.5023584
5,000.00	18.62	326.24	4,799.55	1,058.65	-707.67	1,912,924.52	597,546.73	36.2569119	-107.5024787
5,023.93	18.62	326.24	4,822.23	1,065.00	-711.91	1,912,930.85	597,542.46	36.2569294	-107.5024931
5,023.94	18.62	326.24	4,822.24	1,065.01	-711.92	1,912,930.85	597,542.46	36.2569294	-107.5024931
KOP 9°/100									
5,200.00	9.79	25.03	4,993.50	1,102.18	-721.26	1,912,967.99	597,532.99	36.2570315	-107.5025248
5,400.00	20.36	87.69	5,187.39	1,119.13	-678.95	1,912,985.09	597,575.24	36.2570781	-107.5023813
5,600.00	37.07	102.20	5,362.38	1,107.70	-584.49	1,912,973.99	597,669.73	36.2570467	-107.5020610
5,800.00	54.54	108.35	5,501.32	1,068.99	-447.13	1,912,935.75	597,807.23	36.2569403	-107.5015951
5,861.94	60.00	109.69	5,534.80	1,052.00	-397.90	1,912,918.93	597,856.52	36.2568936	-107.5014281
Hold 60° Inc for 60'									
5,921.94	60.00	109.69	5,564.80	1,034.49	-348.98	1,912,901.59	597,905.50	36.2568455	-107.5012621
Begin 9°/100 Build									
6,000.00	67.02	109.80	5,599.59	1,010.90	-283.26	1,912,878.22	597,971.30	36.2567807	-107.5010393
6,200.00	85.02	110.02	5,647.70	945.06	-101.54	1,912,813.01	598,153.25	36.2565999	-107.5004229
6,266.34	90.99	110.09	5,650.00	922.33	-39.29	1,912,790.49	598,215.57	36.2565374	-107.5002118
Landing Pt 90.99° Inc, 110.09° Az									
6,400.00	90.99	110.09	5,647.68	876.42	86.22	1,912,745.01	598,341.24	36.2564113	-107.4997861
6,600.00	90.99	110.09	5,644.22	807.71	274.02	1,912,676.95	598,529.27	36.2562226	-107.4991491
6,800.00	90.99	110.09	5,640.75	739.01	461.81	1,912,608.89	598,717.30	36.2560338	-107.4985122
7,000.00	90.99	110.09	5,637.28	670.30	649.61	1,912,540.84	598,905.33	36.2558451	-107.4978753
7,200.00	90.99	110.09	5,633.81	601.60	837.41	1,912,472.78	599,093.36	36.2556563	-107.4972383
7,400.00	90.99	110.09	5,630.34	532.89	1,025.20	1,912,404.72	599,281.40	36.2554676	-107.4966014
7,600.00	90.99	110.09	5,626.88	464.19	1,213.00	1,912,336.66	599,469.43	36.2552788	-107.4959644
7,800.00	90.99	110.09	5,623.41	395.48	1,400.80	1,912,268.60	599,657.46	36.2550900	-107.4953275
8,000.00	90.99	110.09	5,619.94	326.78	1,588.59	1,912,200.54	599,845.49	36.2549013	-107.4946906

Database:	COMPASS-SANJUAN	Local Co-ordinate Reference:	Well NE Chaco Com #263H - Slot 263
Company:	SAN JUAN BASIN	TVD Reference:	WELL @ 6896.00usft (Original Well Elev)
Project:	SJ 05-23N-06W	MD Reference:	WELL @ 6896.00usft (Original Well Elev)
Site:	253 - 263 Pad	North Reference:	True
Well:	NE Chaco Com #263H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Plan #2 10Dec14 kjs		


Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
8,200.00	90.99	110.09	5,616.47	258.07	1,776.39	1,912,132.48	600,033.52	36.2547125	-107.4940537	
8,400.00	90.99	110.09	5,613.00	189.37	1,964.19	1,912,064.43	600,221.56	36.2545237	-107.4934167	
8,600.00	90.99	110.09	5,609.54	120.66	2,151.98	1,911,996.37	600,409.59	36.2543349	-107.4927798	
8,800.00	90.99	110.09	5,606.07	51.96	2,339.78	1,911,928.31	600,597.62	36.2541462	-107.4921429	
9,000.00	90.99	110.09	5,602.60	-16.75	2,527.58	1,911,860.25	600,785.65	36.2539574	-107.4915060	
9,200.00	90.99	110.09	5,599.13	-85.45	2,715.37	1,911,792.19	600,973.68	36.2537686	-107.4908691	
9,400.00	90.99	110.09	5,595.66	-154.16	2,903.17	1,911,724.13	601,161.72	36.2535798	-107.4902322	
9,600.00	90.99	110.09	5,592.19	-222.86	3,090.97	1,911,656.07	601,349.75	36.2533910	-107.4895953	
9,800.00	90.99	110.09	5,588.73	-291.57	3,278.76	1,911,588.02	601,537.78	36.2532022	-107.4889584	
10,000.00	90.99	110.09	5,585.26	-360.27	3,466.56	1,911,519.96	601,725.81	36.2530134	-107.4883215	
10,200.00	90.99	110.09	5,581.79	-428.98	3,654.36	1,911,451.90	601,913.84	36.2528246	-107.4876846	
10,400.00	90.99	110.09	5,578.32	-497.68	3,842.15	1,911,383.84	602,101.88	36.2526358	-107.4870477	
10,600.00	90.99	110.09	5,574.85	-566.39	4,029.95	1,911,315.78	602,289.91	36.2524470	-107.4864108	
10,800.00	90.99	110.09	5,571.39	-635.09	4,217.75	1,911,247.72	602,477.94	36.2522582	-107.4857739	
11,000.00	90.99	110.09	5,567.92	-703.80	4,405.54	1,911,179.66	602,665.97	36.2520694	-107.4851371	
11,200.00	90.99	110.09	5,564.45	-772.50	4,593.34	1,911,111.61	602,854.00	36.2518805	-107.4845002	
11,398.96	90.99	110.09	5,561.00	-840.85	4,780.16	1,911,043.90	603,041.05	36.2516927	-107.4838666	

TD at 11398.97

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
TD / PBHL #263H - plan hits target center - Point	0.00	0.00	5,561.00	-840.85	4,780.16	1,911,043.90	603,041.05	36.2516927	-107.4838666	
POE #263H - plan misses target center by 35.92usft at 6278.85usft MD (5649.79 TVD, 918.04 N, -27.54 E) - Point	0.00	0.00	5,650.00	884.30	-39.88	1,912,752.46	598,215.11	36.2564330	-107.5002138	

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment	
550.00	550.00	0.00	0.00	Start Build 2.00	
1,480.88	1,464.59	124.63	-83.31	Hold 18.62° Inc, 326.24° Az	
5,023.94	4,822.24	1,065.01	-711.92	KOP 9°/100	
5,861.94	5,534.80	1,052.00	-397.90	Hold 60° Inc for 60'	
5,921.94	5,564.80	1,034.49	-348.98	Begin 9°/100 Build	
6,266.34	5,650.00	922.33	-39.29	Landing Pt 90.99° Inc, 110.09° Az	
11,398.96	5,561.00	-840.85	4,780.16	TD at 11398.97	

Well Name: NE Chaco Com #263H
 Surface Location: 253 - 263 Pad
 NAD 1927 (NADCON CONUS) , US State Plane 1927 (Exact solution) New Mexico West 3003
 Ground Elevation: 6882.00
 +N/-S +E/-W Northing Easting Latitude Longitude Slot
 0.00 0.00 1911868.30 598258.03 36.2540037 -107.5000785 263
 WELL @ 6896.00usft (Original Well Elev)



Azimuths to True North
 Magnetic North: 9.31°
 Magnetic Field
 Strength: 50149.9snT
 Dip Angle: 63.01°
 Date: 11/13/2014
 Model: IGRF2010



Project: SJ 05-23N-06W
 Site: 253 - 263 Pad
 Well: NE Chaco Com #263H
 Plan #2 10Dec14 kjs

ANNOTATIONS

TVD	MD	Inc	Azi	+N/-S	+E/-W	Vsect	Departure	Annotation
550.00	550.00	0.00	0.00	0.00	0.00	0.00	0.00	Start Build 2.00
1464.59	1480.88	18.82	326.24	124.63	-83.31	-121.05	149.91	Hold 18.62° Inc, 326.24° Az
4822.24	5023.94	18.82	326.24	1065.01	-711.92	-1034.42	1281.04	KOP 9°100
5534.80	5861.94	60.00	109.69	1052.00	-397.90	-735.05	1659.51	Hold 60° Inc for 60'
5584.80	5921.94	60.00	109.69	1034.49	-348.98	-683.09	1711.47	Begin 9°100 Build
5650.00	6266.34	90.99	110.09	922.33	-39.29	-353.71	2040.84	Landing Pt 90.99° Inc, 110.09° Az
5561.00	11398.96	90.99	110.09	-840.85	4780.16	4778.13	7172.69	TD at 11398.97

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
TD / PBH-L #263H	5561.00	-840.85	4780.16	1911043.90	603041.05	36.2516927	-107.4838666
POE #263H	5650.00	884.30	-39.88	1912752.46	598215.11	36.2564330	-107.5002137



Vertical Section at 110.09° (900 usft/in)

Soils will be excavated from the well-connect pipeline trenches using a trencher or backhoe. Each trench will be 4 to 5 feet in depth. The trench will be 16 inches in width if a trencher is used or 24 inches in width if a backhoe is used. Soft plugs will be placed within the trench every quarter mile. When stringing pipe, one joint of pipe will be set back every quarter mile. Backfilling operations will be performed within a reasonable amount of time to ensure that the trench is not left open for more than 24 hours. If a trench is left open overnight, it will be fenced with a temporary fence or a night watchman will be utilized.

After a pipe has been welded and coated, a side-boom tractor will be used to place the pipe into the trench. Prior to construction commencement, WPX will notify the BLM-FFO of additional types of construction equipment to be used. The soils excavated from the trenches will be returned to the trenches, atop the pipe, and compacted to prevent subsidence. The trenches will be compacted after approximately 2 feet of fill is placed within the trenches and after the ground surface has been leveled. Prior to the well-connect pipelines being placed in service, the pipes will be pressure tested. Pipeline markers will be installed along the well-connect pipeline corridor within the line of sight. These markers will not create safety hazards. Construction plats are provided in the APD permit packages.

To install the anode bed a vertical bore is drilled and casing of the specified size and amount is set. Casing is a minimum of 20 feet in length. Upon encountering ground water, drilling shall cease and depth to ground water (DTGW) recorded using a conductive tape technique (Wellsounder) before commencing to the desired bore depth. This information is recorded on the supplied groundwater depth log form. The bore will be completed to a desired vertical bore depth of approximately 300 feet. Given a 240 foot anode length and varying lengths of surface casing, the overall bore shall be allowed to vary by no more than ± 60 feet from the standard 300 feet. Once the bore is completed and cased, the anode is installed in accordance with the manufacturer's specifications. The bore is then backfilled with Conducrete using a tremie tube technique starting from TD of the bore. The casing will be cut and capped 12 inches below the surface. The specified flush grade valve box is then installed directly over the bed. The bed location (Lat/Long) is recorded and full drill log report is completed and filed with WPX. The bed will not be energized for a minimum of 45 days.

9. METHODS FOR HANDLING WASTE DISPOSAL

- ✓ Drilling operations will utilize a closed-loop system. Drilling of the horizontal lateral will be accomplished with water-based mud. All cuttings will be hauled to a commercial disposal facility or land farm. WPX will follow New Mexico Oil Conservation Division "Pit Rule" guidelines and Onshore Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit will be used.

If drilling has not been initiated on the well pad within 120 days of the well pad being constructed, the operator will submit a site-stabilization plan to the BLM-FFO.

All garbage and trash will be placed in a metal trash basket. The trash and garbage will be hauled off site and dumped in an approved landfill, as needed. Portable toilets will be provided and maintained during construction, as needed (see Figures B.3 and B.4 [Appendix B] for the location of toilet[s] and trash receptacle[s]).

10. ANCILLARY FACILITIES

Three potential staging areas (all previously disturbed well pads) will be used; they are described in Section 2.2 (Project Description). During staging, WPX will stay within the boundaries of the previously disturbed well pads. During interim (post-construction) reclamation, WPX will repair any damage to and reseed the staging areas (with the exception of portions of well pads that Elm Ridge or Bannon prefers to remain unseeded).

11. WELL SITE LAYOUT

The approximate cuts, approximate fills, and orientation for the well pad are depicted on the construction plats in the APD permit packages. Rig orientation and the location of drilling equipment and topsoil or

Directions from the Intersection of US Hwy 550 & US Hwy 64

in Bloomfield, NM to WPX Energy Production, LLC NE Chaco COM #263H

2425' FNL & 231' FWL, Section 5, T23N, R6W, N.M.P.M., Rio Arriba County, NM

Latitude: 36.254017°N Longitude: 107.500684°W Datum: NAD1983

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Southerly on US Hwy 550 for 50.2 miles to Mile Marker 101:

Go Left (Northerly) for 0.3 miles to fork in roadway;

Go Right (Northerly) which is straight for 0.9 miles to fork in roadway;

Go Right (Northerly) which is straight for 0.6 miles to fork in road at Elm Ridge Marcus #2 well;

Go Right (Easterly) for 0.4 miles to new access on left-hand side of existing roadway which continues for 209.0' to staked WPX NE Chaco COM #263H location.

3000 PSI BOP Schematic

