ConocoPhillips

Schematic - Current

JACKSON COM #1N

District	Field Name	API / UWI	County	State/Province
SOUTH	MV/DK COM	3004535415	SAN JUAN	NEW MEXICO

Original Spud Date	Surface Legal Location	East/West Distance (ft)	East/West Reference	North/South Distance (ft)	North/South Reference
12/11/2014	009-028N-009W-L	15.00	FWL	1,738.00	FSL

DEVIATED - Original Hole 4/2/2015 12:13:18 PM

MD (ftKB)	Vertical schematic (actual)
17.1	Casing Hanger (Fluted); 17.0-17.6; 0.60; 7; 6.366; 2-1
	Tubing Hanger; 17.0-17.8; 0.75; 7 1/16; 1.995; 1-1
18.0	Casing Hanger (Fluted); 17.0-18.1; 1.15; 4 1/2; 4.000; 3-2
	CASING HANGER; 17.0-19.8; 2.83; 9 5/8; 9.001; 1-1
22.0	Casing Pup Joint; 17.6-21.9; 4.35; 7; 6.366; 2-2
	Casing Pup Joint; 18.1-22.8; 4.69; 4 1/2; 4.000; 3-3
36.1	Casing Pup Joint; 22.8-35.9; 13.14; 4 1/2; 4.000; 3-4
	Tubing; 17.8-48.8; 31.00; 2 3/8; 1.995; 1-2
65.0	Tubing Pup Joints; 48.8-65.0; 16.20; 2 3/8; 1.995; 1-3
	CASING JOINTS; 19.8-433.1; 413.31; 9 5/8; 9.001; 1-2
433.1	FLOAT COLLAR; 433.2-434.7; 1.50; 9 5/8; 9.001; 1-3
	CASING JOINTS; 434.7-463.9; 29.27; 9 5/8; 9.001; 1-4
463.9	SAW TOOTH COLLAR; 463.9-464.8; 0.88; 9 5/8; 9.001; 1-5
470.1	Casing Joints; 36.0-3,673.5; 3,637.51; 4 1/2; 4.000; 3-5
2,040.0	Casing Joints; 21.9-4,920.0; 4,898.10; 7; 6.366; 2-3
2,812.0	
3,193.9	
	Marker Joint; 3,673.5-3,683.6; 10.11; 4 1/2; 4.000; 3-6
3,683.7	Tubing; 65.0-7,506.2; 7,441.22; 2 3/8; 1.995; 1-4
4,669.9	
4,750.0	
	Float Collar; 4,920.0-4,920.9; 0.81; 7; 6.366; 2-4
4,920.9	Casing Joints; 4,920.9-4,965.1; 44.27; 7; 6.366; 2-5
4,966.9	Float Shoe; 4,965.1-4,966.7; 1.58; 7; 6.366; 2-6
5,076.1	PERF - MENEFEE; 5,076.0-5,318.0; 1/26/2015
5,350.1	Casing Joints; 3,683.6-7,144.0; 3,460.45; 4 1/2; 4.000; 3-7
5,608.9	PERF - POINT LOOKOUT; 5,356.0-5,609.0; 1/26/2015
6,544.0	
7,157.2	Marker Joint; 7,144.0-7,157.2; 13.21; 4 1/2; 4.000; 3-8
7,379.9	Casing Joints; 7,157.2-7,645.6; 488.40; 4 1/2; 4.000; 3-9
7,458.0	
7,506.2	Tubing Pup Joint For Marker; 7,506.2-7,508.3; 2.10; 2 3/8; 1.995; 1-5
	Tubing; 7,508.3-7,539.3; 31.00; 2 3/8; 1.995; 1-6
7,539.4	PERF - DAKOTA; 7,458.0-7,618.0; 1/24/2015
	Profile Nipple; 7,539.3-7,540.1; 0.85; 2 3/8; 1.780; 1-7
7,541.0	Expendable Check w/ Mule Shoe; 7,540.1-7,541.0; 0.92; 2 3/8; 1.780; 1-8
7,618.1	
7,634.8	
	Float Collar; 7,645.6-7,646.2; 0.57; 4 1/2; 4.000; 3-10
7,646.3	Float Shoe; 7,646.2-7,647.0; 0.80; 4 1/2; 4.000; 3-11
7,650.9	

OIL CONS. DIV DIST. 3

APR 03 2015

 PV

Report Printed: 4/2/2015