	4
•	District I
	1625 N. French Dr., Hobbs, NM 88240
	District II
	811 S. First St., Artesia, NM 88210
	District III
	1000 Rio Brazos Road, Aztec, NM 87410
	District IV
	1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration
45 - 13076 □ Permit of a pit or proposed alternative method △ PR 08 2015 △ Closure of a pit, below-grade tank, or proposed alternative method
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 124
API Number: 3004513076 OCD Permit Number:
U/L or Qtr/QtrDSection35Township28NRange12WCounty:San Juan
Center of Proposed Design: Latitude36.62269 Longitude108.08570 NAD: □1927 ⊠ 1983 Surface
Owner: 🛛 Federal 🗌 State 🗌 Private 🗋 Tribal Trust or Indian Allotment
2.
□ <u>Pit</u> : Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
🗌 Visible sidewalls and liner 🗌 Visible sidewalls only 🖾 Other _Single walled/double bottomed; side walls not visible
Liner type: Thickness mil 🗌 HDPE 🗌 PVC 🗌 Other
4. <u>Alternative Method:</u>

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

6.

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting						
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells						
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 						
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No					
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No					
Below Grade Tanks						
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No					
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)						
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No					

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stoc watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	ck 🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinl or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stoc	Yes No
 watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or pla lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	aya
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	f
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15 <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that</i>	
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NI Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit.	
 Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	U 01 19.15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

 I2. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	documents are
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well FI Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
 ^{14.} <u>Waste Excavation and Removal Closure Plan Checklist</u>: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	attached to the
^{15.} Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	rce material are Please refer to
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	 Yes □ No NA Yes □ No NA
Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

٢

*		
	 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
	 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
	 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 	
	Society; Topographic map Within a 100-year floodplain.	🗌 Yes 🗌 No
	- FEMA map	Yes No
	 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure ple by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	.11 NMAC 15.17.11 NMAC
	17. Operator Application Certification:	
	I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
	Name (Print): Title:	
	Signature: Date:	
	e-mail address: Telephone:	
	e-mail address: Telephone: <u>OCD Approva</u> I: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: Title: OCD Permit Number:	2015
	18. OCD Approval: Permit Application (including closure plan) OCD Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Orthology Approval Date: 4/14/2 Title: OCD Permit Number: 0CD Permit Number: 19. 19.	2015
	18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Output Permit Plan Approval Date: 4/14/14/14/14/14/14/14/14/14/14/14/14/14	
	18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/14/ Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	
	18. OCD Approval: Permit Application (including closure plan) OClosure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number: Approval Date: 4/14/14/14/14/14/14/14/14/14/14/14/14/14	complete this

*

22.	
Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and le closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Peace	Date:April 7, 2015
e-mail address:peace.jeffrey@bp.com	Telephone: (505) 326-9479

٠

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 124, BGT Tank A (95 bbl)</u> <u>API No. 3004513076</u> <u>Unit Letter D, Section 35, T28N, R12W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	119.1
TPH	US EPA Method SW-846 418.1	100	1,400
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled and benzene and chloride levels were below the stated limits. TPH was 1,400 ppm by Method 418.1 and was 1,700 ppm by Method 8015D. Total BTEX was 119.1 ppm by Method 8021B. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release occurred. Remediation of the release was addressed through the spill and release guidelines.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

÷

٠

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr.

Form C-141 Revised August 8, 2011

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

District IV 1220 S. St. Frar	icis Dr., Sant	a Fe, NM 8750	5			Fe, NM 875					
			Rele	ease Notifi	catio	on and Co	orrective A	ction suf			
						OPERA '			ial Report	\bowtie	Final Repor
Name of Co	ompany: B	Р				Contact: Jet	f Peace		1		1
Address: 20	Address: 200 Energy Court, Farmington, NM 87401					Telephone 1	No.: 505-326-94	-79			
Facility Name: Gallegos Canyon Unit 124					Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Feder	al		Mineral (Owner	· Federal		APIN	0. 3004513	076	
Surface of	ner: r cucr							11111	0. 5004515	070	
XX ** X **	G .:	T 1'	D			DN OF RE		T		*	
D D	1 0			h/South Line h	Feet from the 1,190			County: San Juan			
		Lat	itude_3	5.62269		Longitud	e108.08570_				
				NAT	UR	E OF REL	EASE				
Type of Rele							Release: unknow		Recovered: 1		
		v grade tank –	- 95 bbl, T	ank A		unknown	Iour of Occurrenc	e: Date and 2015; 1:		covery	: February 3,
Was Immedia	ate Notice (Yes 🛛	No 🗌 Not R	equirec	If YES, To	Whom?				
By Whom?						Date and H					
Was a Water	course Reac		Yes 🛛	No		If YES, Vo	olume Impacting t	he Watercourse.			
If a Watercou	irse was Imj	pacted, Descr	ibe Fully."								
the BGT. So Total BTEX	il analysis r was 119.1 p	esulted in ben opm by Metho	zene and o d 8021B.	chlorides below s Analysis results	tandarc are atta	ds. TPH was 1 ached.	the BGT was dor 400 ppm by Meth nderneath the BG	nod 418.1 and wa	s 1,700 ppm	by Met	hod 8015D.
release occur	red. The rel	ease was addi	essed thro		release	e guidelines. A	final C-141 will b				
regulations al public health should their o or the environ	l operators or the envir operations h ument. In a	are required to conment. The ave failed to a	o report an acceptanc adequately OCD accep	d/or file certain r e of a C-141 repo investigate and r	elease ort by the emedia	notifications and he NMOCD mate contamination of the second secon	knowledge and us nd perform correc arked as "Final Ro on that pose a thre e the operator of r	tive actions for re eport" does not re eat to ground wate	leases which lieve the ope er, surface wa	may er rator of ater, hu	ndanger Fliability man health
Signature:	left	Peace					OIL CONS	SERVATION	DIVISIO	DN	
Printed Name	e: Jeff Peace	e				Approved by	Environmental Sp	pecialist:			
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Expiration	Date:		
E-mail Addre	ess: peace.je	effrey@bp.com	n			Conditions of	Approval:		Attached		
Date: April		ets If Necess		5-326-9479							

		1			
CLIENT: BP	BLAGG ENGINEERING, INC.	API #: 3004513076			
CLIENT:	P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	TANK ID (if applicble):			
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: 1 of 2			
SITE INFORMATION	: SITE NAME: GCU # 124	DATE STARTED: 02/03/15			
QUAD/UNIT: D SEC: 35 TWP:	28N RNG: 12W PM: NM CNTY: SJ ST: NM	DATE FINISHED:			
	90'W NW/NW LEASE TYPE: FEDERAL/STATE / FEE / INDIAN STRIKE PROD. FORMATION: DK CONTRACTOR: MBF - S. GLYNN	ENVIRONMENTAL SPECIALIST(S): NJV			
REFERENCE POINT	-				
	30.02271 × 100.00001				
		RING FROM W.H.: 91', S81.5E			
	GPS COORD.: DISTANCE/BEA				
4)		RING FROM W.H.:			
		RING FROM W.H.:			
SAMPLING DATA:		READING (ppm)			
-	(95) SAMPLE DATE: 02/03/15 SAMPLE TIME: 1320 LAB ANALYSIS: 418.1/8				
. .	25) SAMPLE DATE: 02/03/15 SAMPLE TIME: 1330 LAB ANALYSIS: 418.1/8	, ,			
	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:				
	SAMPLE DATE:SAMPLE TIME: LAB ANALYSIS:				
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SILT / SILTY CLAY / CLAY / GRAVEL OTHER ROAD E	ASE BENEATH BGT			
SOIL COLOR: DARK YELLOW	ISH ORANGE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / C	OHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC			
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC					
MOISTURE: DRY/SLIGHTLY MOIST (MOIST) WE		OLORED SOILS ONLY			
SAMPLE TYPE: GRAB COMPOSITE #		NATION - DIRECTLY BENEATH BGT			
	D EXPLANATION - BENEATH BGT BETWEEN 5 & 7 FT. BELOW GRADE	DIRECTET DEREATTED			
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION - BULL PLUG & POSSIB	LY BOTTOM OF BGT			
APPARENT EVIDENCE OF A RELEASE OBSERVE	DAND/OR OCCURRED : YES NO EXPLANATION: DISCOLORED SOILS VERY APPARENT				
EQUIPMENT SET OVER RECLAIMED AREA: OTHER APPARENT IMPACTED SOILS A	TES NO EXPLANATION - BULL PLUG & POSSIBLY BOTTOM OF BGT PPEARS LIMITED TO BGT FOOTPRINT. WILL EXCAVATE OBVIOUS & DISTINCT	IVE DISCOLORED SOILS &			
TRANSPORT TO CROUCH MESA.					
SOIL IMPACT DIMENSION ESTIMATION:		TIMATION (Cubic Yards) :15			
	EAREST WATER SOURCE: <u>>1,000'</u> NEAREST SURFACE WATER: <u>>1,000'</u> NMOC	CD TPH CLOSURE STD: 1,000 ppm			
SITE SKETCH	BGT Located : off on site PLOT PLAN circle: attached OW	CALIB. READ. = NA ppm RF =0.52			
METER		CALIB. GAS = NA ppm			
RUN	N TIME	: NA am/pm DATE: NA			
	< SEPARATOR	MISCELL, NOTES			
	W	/O:			
		EF. #: P-12			
₩.H. ⊕		K: ZEVH01BGT2			
		J #: Z2-006Q0			
		ermit date(s): 06/14/10			
	PBGTL T.B. ~ 6'	CD Appr. date(s): 11/06/14			
	B.G.	nk OVM = Organic Vapor Meter			
	A	BGT Sidewalls Visible: Y /N			
	X - S.P.D.	BGT Sidewalls Visible: Y / N			
	N DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD;	BGT Sidewalls Visible: Y / N			
APPLICABLE OR NOT AVAILABLE; SW - SINGLE	WALL, DW - DOUBLE WALL, SB - SINGLE BOTTOW, DB - DOUBLE BOTTOW.	lagnetic declination: 10° E			
NOTES: GOOGLE EARTH IMAGE	RY DATE: 11/17/2013. ONSITE: 02/03/15				

.

,

Analytical Report Lab Order 1502112 Date Reported: 2/5/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 5' (95) Project: GCU #124 Collection Date: 2/3/2015 1:20:00 PM Lab ID: 1502112-001 Matrix: SOIL Received Date: 2/4/2015 8:30:00 AM Analyses Result RL Qual Units DF Date Analyzed Batch

	And have been all the second se	NAME OF TAXABLE PARTY.	States and states	NAME AND ADDRESS OF TAXABLE PARTY.	out the design of the design of the local division of the	and a second	NAMES AND ADDRESS OF TAXABLE PARTY.
EPA METHOD 8015D: DIESEL RANGE OF	GANICS					Analyst	JME
Diesel Range Organics (DRO)	400	10		mg/Kg	1	2/4/2015 10:00:15 AM	17553
Surr: DNOP	74.9	63.5-128		%REC	1	2/4/2015 10:00:15 AM	17553
EPA METHOD 8015D: GASOLINE RANGE						Analyst	NSB
Gasoline Range Organics (GRO)	1300	59		mg/Kg	20	2/4/2015 9:52:14 AM	R24097
Surr: BFB	419	80-120	S	%REC	20	2/4/2015 9:52:14 AM	R24097
EPA METHOD 8021B: VOLATILES						Analyst	NSB
Benzene	ND	0.29		mg/Kg	20	2/4/2015 9:52:14 AM	R24097
Toluene	ND	0.59		mg/Kg	20	2/4/2015 9:52:14 AM	R24097
Ethylbenzene	8.1	0.59		mg/Kg	20	2/4/2015 9:52:14 AM	R24097
Xylenes, Total	110	1.2		mg/Kg	20	2/4/2015 9:52:14 AM	R24097
Surr: 4-Bromofluorobenzene	152	80-120	S	%REC	20	2/4/2015 9:52:14 AM	R24097
EPA METHOD 300.0: ANIONS						Analyst	LGT
Chloride	ND	30		mg/Kg	20	2/4/2015 12:01:04 PM	17559
EPA METHOD 418.1: TPH						Analyst	JME
Petroleum Hydrocarbons, TR	1400	200		mg/Kg	10	2/4/2015 12:00:00 PM	17511

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method	od Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysi	s exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 7
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.	1 450 1 01 /
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

Client:	Blagg E	ngineering
Project:	GCU #1	24
		0 T 11514

	the second se							
Sample ID MB-17559	SampType: MBLK	MBLK TestCode: EPA Method 300.0: Anions						
Client ID: PBS	Batch ID: 17559	RunNo: 24117						
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710960	Units: mg/Kg					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual				
Chloride	ND 1.5							
Sample ID LCS-17559	SampType: LCS	TestCode: EPA Method	300.0: Anions					
Client ID: LCSS	Batch ID: 17559	RunNo: 24117						
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710961	Units: mg/Kg					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual				
Chloride	14 1.5 15.00	0 92.3 90	110					

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 7

WO#: 1502112 05-Feb-15

Client:Blagg EngineeringProject:GCU #124

Sample ID MB-17511	SampType: MBLK			
Client ID: PBS	Batch ID: 17511	RunNo: 24075		
Prep Date: 2/2/2015	Analysis Date: 2/4/2015	SeqNo: 710256	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-17511	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 17511	RunNo: 24075		
Prep Date: 2/2/2015	Analysis Date: 2/4/2015	SeqNo: 710257	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	97 20 100.0	0 96.6 86.7	126	
Sample ID LCSD-17511	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 17511	RunNo: 24075		
Prep Date: 2/2/2015	Analysis Date: 2/4/2015	SeqNo: 710258	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	99 20 100.0	0 99.3 86.7	126 2.77	20

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 7

1502112 05-Feb-15

WO#:

Client: Blagg Engineering

Project: GCU #124

Sample ID MB-17553	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: PBS	Batch ID: 17553	RunNo: 24074								
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710059	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Diesel Range Organics (DRO)	ND 10		5							
Surr: DNOP	12 10.00	116 63.5	128							
Sample ID MB-17554	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: PBS	Batch ID: 17554	RunNo: 24073								
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710152	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Surr: DNOP	8.5 10.00	85.3 63.5	128							
Sample ID LCS-17554	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 17554	RunNo: 24073	5 5							
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710153	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Surr: DNOP	4.4 5.000	88.1 63.5	128							
Sample ID LCS-17553	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 17553	RunNo: 24073	5							
Prep Date: 2/4/2015	Analysis Date: 2/4/2015	SeqNo: 710303	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Diesel Range Organics (DRO)	56 10 50.00	0 112 67.8	130							
Surr: DNOP	4.9 5.000	97.2 63.5	128							
Sample ID MB-17578	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: PBS	Batch ID: 17578	RunNo: 24112								
Prep Date: 2/5/2015	Analysis Date: 2/5/2015	SeqNo: 710887	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Surr: DNOP	11 10.00	109 63.5	128							
Sample ID LCS-17578	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 17578	RunNo: 24111								
Prep Date: 2/5/2015	Analysis Date: 2/5/2015	SeqNo: 710956	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
			rightennik vord b rit bennik skuda							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

WO#: 1502112 05-Feb-15

Page 5 of 7

Client: Blagg Engineering Project: GCU #124

Sample ID 5ML RB	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range									
Client ID: PBS	Batch ID: R24097 RunNo: 24097									
Prep Date:	Analysis D	ate: 2/	4/2015	S	eqNo: 7	10491	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	940		1000		94.5	80	120			
Sample ID 2.5UG GRO LCS	SampT	ype: LC	S	Test	Code: EF	PA Method	8015D: Gaso	line Rang	е	
Client ID: LCSS	Batch	ID: R2	4097	R	unNo: 24	4097				
Prep Date:	Analysis D	ato: 21	4/2045	SeqNo: 710492			Lipito: mar/l/	~		
Thep Date.	Analysis D	ale. ZI	4/2015	0	equo. 7	10492	Units: mg/K	g		
Analyte	Result	PQL		SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	,						0	0	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

WO#: 1502112 05-Feb-15

Page 6 of 7

Client:Blagg EngineeringProject:GCU #124

	and the second se												
Sample ID 5ML RB	SampType: MBLK TestCode: EPA Method 8021B: Volatiles												
Client ID: PBS	Batch	n ID: R2	4097	R	aunNo: 24	4097							
Prep Date:	Analysis D	ate: 2/	4/2015	SeqNo: 710517			Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
							100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100						
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120						
Surr: 4-Bromofluorobenzene Sample ID 100NG BTEX LCS		ype: LC		Test			120 8021B: Volat	iles					
	SampT	ype: LC	S			PA Method		iles					
Sample ID 100NG BTEX LCS	SampT	n ID: R2	S 4097	R	tCode: EF	PA Method							
Sample ID 100NG BTEX LCS Client ID: LCSS	SampT Batch	n ID: R2	S 4097 4/2015	R	Code: EF	PA Method	8021B: Volat		RPDLimit	Qual			
Sample ID 100NG BTEX LCS Client ID: LCSS Prep Date:	SampT Batch Analysis D	n ID: R2 ate: 2/	S 4097 4/2015	R	Code: EF cunNo: 24 seqNo: 71	PA Method 4097 10518	8021B: Volat Units: mg/K	g	RPDLimit	Qual			
Sample ID 100NG BTEX LCS Client ID: LCSS Prep Date: Analyte	SampT Batch Analysis D Result	n ID: R2 ate: 2/ PQL	S 4097 4/2015 SPK value	R S SPK Ref Val	Code: EF cunNo: 24 seqNo: 71 %REC	PA Method 4097 10518 LowLimit	8021B: Volat Units: mg/K HighLimit	g	RPDLimit	Qual			
Sample ID 100NG BTEX LCS Client ID: LCSS Prep Date: Analyte Benzene Toluene	SampT Batch Analysis D Result 1.1	n ID: R2 hate: 2 / PQL 0.050	S 4097 4/2015 SPK value 1.000	R S SPK Ref Val 0	tCode: EF tunNo: 24 GeqNo: 7* %REC 107	PA Method 4097 10518 LowLimit 80	8021B: Volat Units: mg/K HighLimit 120	g	RPDLimit	Qual			
Sample ID 100NG BTEX LCS Client ID: LCSS Prep Date: Analyte Benzene	SampT Batch Analysis D Result 1.1 1.1	DID: R2 pate: 2/ PQL 0.050 0.050	S 4097 4/2015 SPK value 1.000 1.000	R S SPK Ref Val 0 0	tCode: EF tunNo: 24 SeqNo: 71 %REC 107 106	PA Method 4097 10518 LowLimit 80 80	8021B: Volat Units: mg/K HighLimit 120 120	g	RPDLimit	Qual			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 7 of 7

1502112 05-Feb-15

WO#:

	HALL
	ENVIRONMENTAL
199	ANALYSIS
	LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	15021	12		RcptNo:	1
Received by/date: LM	02/04/15					
Logged By: Anne Thorne 2	/4/2015 8:30:00 AM		a	ne Arm	_	
Completed By: Anne Thorne 2	/4/2015		1	me Am		
Reviewed By:	0 2/04/15			na prem		
Chain of Custody						
1. Custody seals intact on sample bottles?		Yes		No 🗌	Not Present	
2. Is Chain of Custody complete?		Yes	\checkmark	No 🗌	Not Present	
3. How was the sample delivered?		Courie	<u>er</u>			
Log In						
4. Was an attempt made to cool the samples?		Yes	\checkmark	No 🗌	NA 🗌	
5. Were all samples received at a temperature of	f >0° C to 6.0°C	Yes		No 🗌	NA 🗌	
6. Sample(s) in proper container(s)?		Yes	\checkmark	No 🗌		1
7. Sufficient sample volume for indicated test(s)?		Yes		No 🗌		
8. Are samples (except VOA and ONG) properly	preserved?	Yes [\checkmark	No 🗌		
9. Was preservative added to bottles?		Yes [No 🗹	NA 🗌	
10. VOA vials have zero headspace?		Yes [No 🗌	No VOA Vials 🗹	
11. Were any sample containers received broken?	?	Yes [No 🗹	44 of an and	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes	V	No 🗌	# of preserved bottles checked for pH:	or >12 unless noted)
13. Are matrices correctly identified on Chain of Cu	ustodv?	Yes 🛙		No 🗌	Adjusted?	,
14. Is it clear what analyses were requested?				No 🗌		
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🛛		No 🗌	Checked by:	
<u>Special Handling (if applicable)</u>						
16, Was client notified of all discrepancies with this	s order?	Yes		No 🗌	NA 🗹	
Person Notified:	Date					
By Whom:	Via:	eMail	Phone	Fax	In Person	
Regarding:						
Client Instructions:						

17. Additional remarks:

18. Cooler Information

Cooler No T	emp °C Cond	tion Seal Int	act Seal No	Seal Date	Signed By
1 2.4	Good	Yes			

С	hain-	of-Cus	tody Record		IIIIe.	SAME			B	F	łΔ	11	E	N	/тг	20	N	ME	NT	41												
Client:	BLAGG ENGR. / BP AMERICA			BLAGG ENGR. / BP AMERICA												and the second second			TO		(
				Project Name					-		ww	w.ha	allen	viro	nme	ental	.con	'n														
Mailing A	ddress:	P.O. BO)	(87	GCU # 124				4901 Hawkins NE - Albuquerque, NM 87109																								
		BLOOM	HELD, NM 87413	Project #:		Tel. 505-345-3975 Fax 505-345-4107																										
Phone #:	0	(505) 63	2-1199				Analysis Request																									
email or i	Fax#:			Project Mana	ger			-	71	-1	- 21			-				1)		1	Т											
QA/QC Pa			Level 4 (Full Validation)		NELSON VELEZ		5 (8021B)	TPH (Gas only)	THING				5										15)		04,504	PCB's			er - 300.1)		d	,
Accredita				Sampler:	NELSON VE	LEZ MV	The second	(Gas	DRO/	1	1)	8270SIMS)	1	1021	/ 8082			/ water		am												
	P	D Other_		On Ice:	Yes	EFNo		HdT	~	418.	504.	8270	10	03,N	3/5		(M)	C.00		5 53	1.4											
D EDD (Type)			Sample Temp	erature: Z	4 I	L	+	(GR(por	pou	or	etal	N'ID	cide	A)	It-VC	il - 3	4	osit	- N											
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +-MITE	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /	Grah camula	5 pt. composite sample	A1- 71-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-											
2/3/15	1320	SOIL	SPC - TB @ 5' (95)	4 oz 1	Cool	-001	٧		۷	٧					-			٧		V	_											
2/3/15	1330	SOIL	TH1 @ 8.5' (95)	4 oz 1	Cool	-002	V		٧	٧								٧	1	/	+											
						1					_		-								T											
					-11				_	-											\pm											
										-			1	-						-	+											
Date:)	Time:	Relinquish	ed by:	Received by:		Date Time	Ren	narks	5:		-			1		1					_											
2/3/15	1614	91	lon V/	Chart	Doct	2/3/15 1614	1.1.1																									
Date: 2/3/1<	Time:	Relinquishe	atu Walt	Received by:	E no la	Date Time 4/15/0830	1	TPea											HOI	BET	2											

-

If necessary, samples submitted to Hall Environmental may be subcontracted to other accrecited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report

bp

.



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

February 5, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 124 API #: 3004513076

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 9, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

9. Dulla

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

February 5, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 124 API 30-045-13076 (D) Section 35 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around February 9, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Sto Peace

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



