District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
12848 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:City of Farmington Com 1E
API Number:3004526734OCD Permit Number:
U/L or Qtr/QtrJ Section10 Township29N Range13W County:San Juan
Center of Proposed Design: Latitude36.74000 Longitude108.19054 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: Lx Wx D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)							
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,						
institution or church) ☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet							
☐ Alternate. Please specify							
6.							
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)							
Screen Netting Other							
Monthly inspections (If netting or screening is not physically feasible)							
7. Signs: Subsection C of 19.15.17.11 NMAC							
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers							
☐ Signed in compliance with 19.15.16.8 NMAC							
Variances and Exceptions:							
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:							
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.							
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
9.							
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce,	ntable source						
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	piuote source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No						
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)							
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No						
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	☐ Yes ☐ No						
from the ordinary high-water mark).	L Tes L No						
- Topographic map; Visual inspection (certification) of the proposed site							
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No					
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	MAC cuments are					
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.12 NMAC						
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:						
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents of the standard of	uments are					
attached. ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	15.17.9 NMAC					
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are							
<u>Proposed Closure:</u> 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.								
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit							
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC								
15.								
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.								
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site								
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Vithin incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance								

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality									
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No								
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No								
Within a 100-year floodplain FEMA map									
16.									
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC									
17. Operator Application Certification:									
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.								
Name (Print): Title:									
Signature: Date:									
e-mail address: Telephone:									
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/14 Title: OCD Permit Number:	12015								
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:2/7/2015									
Closure Method: Note: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)								
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.74000 Longitude -108.19054 NAD: 1927 19									

Operator Closure Certification:							
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.							
Name (Print):Jeff Peace	Title: Field Environmental Coordinator						
Signature: Joff Posee	Date:April 7, 2015						
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479						

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

City of Farmington Com 1E API No. 3004526734 Unit Letter J, Section 10, T29N, R13W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge) b.
 - Basin Disposal, Permit NM-01-0005 (Liquids) C.
 - Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and d. Sludge)
 - BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids) e.

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ase Notific	catio	n and Co	orrective A	ction				
						OPERATOR Initial Report Fin					Final Report	
Name of Company: BP						Contact: Jeff Peace						
		Court, Farmi					No.: 505-326-94					
Facility Nat	me: City o	f Farmington	Com 1E			Facility Typ	e: Natural gas v	well				
Surface Ow	Surface Owner: Private Mineral Owner					Private			API No	. 3004526	734	
				LOCA	ATIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the						an Juan	1	
J	10	29N	13W	2,203	South		1,653	East				
		Lati	tude36	5.74000		_ Longitud	e108.19054_					
				NAT	TURE	OF REL	EASE					
Type of Rele	ase: none						Release: N/A		Volume F	Recovered: 1	V/A	
Source of Re	lease: belov	w grade tank –	21 bbl			10	Iour of Occurrence	ce:	Date and	Hour of Dis	covery	: N/A
Was Immedia	ata Notice (Given?				N/A If YES, To	Whom?					
was minicula	ate Notice (Yes	No 🛛 Not R	equired		windin:					
By Whom?						Date and H	Iour					
Was a Water	course Read		Vac 🖂	No		If YES, Vo	olume Impacting	the Wate	rcourse.			
		Ц	Yes 🛚	NO								
If a Watercou	ırse was Im	pacted, Descri	be Fully.*									
							the BGT was do is results are attac		g removal	to ensure no	soil im	npacts from
				en.* BGT was rective well area.	emoved	and the area u	nderneath the BC	GT was sa	ampled. T	he area und	er the B	GT was
regulations all public health should their of or the environ	Il operators or the envi operations h nment. In a	are required to ronment. The nave failed to a	report an acceptance dequately CD accep	d/or file certain in e of a C-141 reprinted investigate and in	release nort by the remediate	notifications a ne NMOCD m te contaminati	knowledge and und perform correct arked as "Final R on that pose a thr e the operator of	ctive active active deport" de reat to gre	ons for releases not released ound water	eases which ieve the ope r, surface wa	may er rator of ater, hu	ndanger f liability man health
	A	^					OIL CON	SERV	ATION	DIVISIO	N	
Signature:	all	Peace										
310						Approved by	Environmental S	Specialist	:			
Printed Name	e: Jeff Peac	e			-							
Title: Field E	invironmen	tal Coordinato	r			Approval Da	te:	I	Expiration	Date:		
E-mail Addre	ess: peace.jo	effrey@bp.cor	n			Conditions o	f Approval:			Attached		
Date: April	7, 2015											

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG P.O. BOX 87	API #: 3004 TANK ID (if applicble):	526734 A						
FIELD REPORT:	FIELD REPORT: (circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:								
SITE INFORMATION	J: SITE NAME: CITY	OF FARMIN	GTON CO	OM #1E	DATE STARTED:	02/03/15			
QUAD/UNIT: J SEC: 10 TWP.	29N RNG: 13W	PM: NM CNT	ry: SJ	ST: NM	DATE FINISHED:				
1/4-1/4/FOOTAGE: 2,203'S / 1,	S53'E NW/SE LEA	ASE TYPE: FEDERA	L/STATE FE	EV INDIAN	ENVIRONMENTAL				
LEASE#: -	PROD. FORMATION: DK	CONTRACTOR: N	TRIKE IBF - B. SCI	HURMAN	SPECIALIST(S):				
REFERENCE POINT	WELL HEAD (W.H.)	GPS COORD.:	36.73986	X 108.19001	GL ELEV.	5,345'			
	GPS COORD.:								
2)					RING FROM W.H.:				
3)					RING FROM W.H.:				
4)				DISTANCE/BEAI	RING FROM W.H.:	OVM			
SAMPLING DATA:						READING (ppm)			
1) SAMPLE ID: 5PC - TB @ 2	(21) SAMPLE DATE: 02	2/03/15 SAMPLE TIME:	0910 LAB	ANALYSIS: 418	3.1/8021B/300.0 (C	I) NA			
2) SAMPLE ID:									
3) SAMPLE ID:									
4) SAMPLE ID:	SAMPLE DATE:								
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SA	ND SILT / SILTY CLAY / C	CLAY GRAVEL (OTHER					
SOIL COLOR: MODERA					OHESIVE / MEDIUM PLASTIC				
COHESION (ALL OTHERS): NON COHESIVE SLIGHT CONSISTENCY (NON COHESIVE SOILS): L				•	STIFF / VERY STIFF / HA	RD			
MOISTURE: DRY/SLIGHTLYMOIST MOIST V			ED: YES NO EXP	LANATION -					
SAMPLE TYPE: GRAB (COMPOSITE)	# OF PTS 5	-	YING WETNESS:	YES / NO EXPLAN	NATION - FROM RECE	NT			
DISCOLORATION/STAINING OBSERVED: YES	NO EXPLANATION -	PRECIPITATION	l.						
SITE OBSERVATION			ATION -						
APPARENT EVIDENCE OF A RELEASE OBSERV EQUIPMENT SET OVER RECLAIMED AREA:		EXPLANATION:							
OTHER: GRAVEL IMPORTED ROAD BA	SE. BOTTOM 2 FT. OF BGT	BURIED INTENTIONAL	LLY. SITE HAS	PERIMETER SE	CURITY FENCE.				
SOIL IMPACT DIMENSION ESTIMATION	: NA ft. X N	A ft. X NA	ft. E	VCAVATION EST	TIMATION (Cubic Yards	s): NA			
.1001		,000' NEAREST SURF			TIMATION (Cubic Yards	100 ppm			
SITE SKETCH	BGT Located: off on								
OTTE GRETOIT	BOT Located. Oil / Oil	Site PLOTP	LAIN circle.	VIVI	CALIB. READ. = NA	ppm RF =0.52			
1					CALIB. GAS = NA :: NA am/pm DATI	ppm D			
1		PBGTL		N TIME					
BERM →		x x x x T.B. ~ 2' B.G.			MISCELL. N				
1		B.G.			O: N1555326	12			
	A				EF #: P - 55 K: ZEVH01B	CT2			
	SEPARATO	R			J#: Z2-006Q0				
						6/14/10			
			ТО	0	CD Appr. date(s): 0	5/10/11			
			W.H.	Tar ID	nk OVM = Organic Va				
				A	BGT Sidewalls Visible	2: Y /N			
			Χ -	S.P.D.	BGT Sidewalls Visible				
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVAT				= WELL HEAD;	BGT Sidewalls Visible				
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE APPLICABLE OR NOT AVAILABLE; SW - SING				L, NA-NOI	lagnetic declination	1: 10 E			
NOTES: GOOGLE EARTH IMAG	ERY DATE: 2015.	ONSITE	<u>02/03/15</u>						

Analytical Report

Lab Order 1502117

Date Reported: 2/5/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 2' (21)

Project: City of Farmington COM #1E

Collection Date: 2/3/2015 9:10:00 AM

Lab ID: 1502117-001

Matrix: SOIL

Received Date: 2/4/2015 8:30:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	: LGT
Chloride	ND	30	mg/Kg	20	2/4/2015 12:38:18 PM	17559
EPA METHOD 8260B: VOLATILES S	SHORT LIST				Analyst	DJF
Benzene	ND	0.038	mg/Kg	1	2/4/2015 11:22:36 AM	17508
Toluene	ND	0.038	mg/Kg	1	2/4/2015 11:22:36 AM	17508
Ethylbenzene	ND	0.038	mg/Kg	1	2/4/2015 11:22:36 AM	17508
Xylenes, Total	ND	0.076	mg/Kg	1	2/4/2015 11:22:36 AM	17508
Surr: 1,2-Dichloroethane-d4	84.3	70-130	%REC	1	2/4/2015 11:22:36 AM	17508
Surr: 4-Bromofluorobenzene	100	70-130	%REC	1	2/4/2015 11:22:36 AM	17508
Surr: Dibromofluoromethane	88.7	70-130	%REC	1	2/4/2015 11:22:36 AM	17508
Surr: Toluene-d8	89.3	70-130	%REC	1	2/4/2015 11:22:36 AM	17508
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	2/4/2015 12:00:00 PM	17511

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 4

- P Sample pH greater than 2.
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502117

05-Feb-15

Client:

Blagg Engineering

Project:

City of Farmington COM #1E

Sample ID MB-17559

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 17559

PQL

RunNo: 24117

Prep Date: 2/4/2015 Analysis Date: 2/4/2015

SeqNo: 710960

Units: mg/Kg

Analyte

Result

SPK value SPK Ref Val %REC LowLimit HighLimit

%RPD

RPDLimit

Qual

Chloride

ND 1.5

Sample ID LCS-17559

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Batch ID: 17559

RunNo: 24117

Prep Date: 2/4/2015 Analysis Date: 2/4/2015

SeqNo: 710961

Units: mg/Kg HighLimit

Qual

Analyte

PQL

SPK value SPK Ref Val %REC 15.00

92.3

90

Chloride

1.5

%RPD **RPDLimit**

Result 14

110

Qualifiers:

E

- Value exceeds Maximum Contaminant Level.
- J Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0

Value above quantitation range

- R RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- Reporting Detection Limit

Page 2 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502117

05-Feb-15

Client:

Blagg Engineering

Project:

City of Farmington COM #1E

Sample ID MB-17511

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 17511

RunNo: 24075

Prep Date:

2/2/2015

Analysis Date: 2/4/2015

SeqNo: 710256

%REC LowLimit

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Analyte Petroleum Hydrocarbons, TR Result PQL ND 20

Sample ID LCS-17511

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID:

LCSS

Batch ID: 17511

RunNo: 24075

Prep Date: 2/2/2015

Analysis Date: 2/4/2015

SeqNo: 710257

Units: mg/Kg

Analyte Petroleum Hydrocarbons, TR Result PQL 97

SPK value SPK Ref Val %REC 100.0

SPK value SPK Ref Val

96.6

LowLimit 86.7

HighLimit

Qual

Qual

20

126

RPDLimit

20

Sample ID LCSD-17511

SampType: LCSD

RunNo: 24075

TestCode: EPA Method 418.1: TPH

Client ID: LCSS02 Prep Date: 2/2/2015

Batch ID: 17511

Analysis Date: 2/4/2015

SeqNo: 710258

Units: mg/Kg

%RPD **RPDLimit** HighLimit

2.77

%RPD

Result PQL %REC Analyte SPK value SPK Ref Val LowLimit Petroleum Hydrocarbons, TR 99 20 100.0 99.3 86.7 126

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range
- Analyte detected below quantitation limits RSD is greater than RSDlimit 0
- R RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- Reporting Detection Limit

Page 3 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1502117

05-Feb-15

Client:

Blagg Engineering

Project:

City of Farmington COM #1E

Sample ID mb-17508	SampType: MBLK TestCode: EPA Method 8260B: Volatiles SI						tiles Short	List		
Client ID: PBS	Batc	h ID: 17	508	F	RunNo: 24088					
Prep Date: 2/2/2015	Analysis [Date: 2/	4/2015	5	SeqNo: 7	11224	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 1,2-Dichloroethane-d4	0.42		0.5000		83.3	70	130			
Surr: 4-Bromofluorobenzene	0.44		0.5000		87.2	70	130			
Surr: Dibromofluoromethane	0.45		0.5000		90.7	70	130			
Surr: Toluene-d8	0.44		0.5000		87.9	70	130			
Sample ID Ics-17508	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8260B: Volat	iles Short	List	
Client ID: LCSS	Batc	h ID: 17	508	F	RunNo: 2	4088				
Prep Date: 2/2/2015	Analysis [Date: 2/	4/2015	5	SeqNo: 7	11225	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	109	70	130			
oluene	0.97	0.050	1.000	0	97.0	70	130			
Surr: 1,2-Dichloroethane-d4	0.45		0.5000		89.7	70	130			
Surr: 4-Bromofluorobenzene	0.43		0.5000		85.2	70	130			
Surr: Dibromofluoromethane	0.46		0.5000		92.1	70	130			
Surr: Toluene-d8	0.44		0.5000		87.2	70	130			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 4



4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Num	ber: 1502117		RcptNo:	1
Received by/date:	n 02/04/15				
Logged By: Anne Thor	ne 2/4/2015 8:30:00 A	M	anne Am		
Completed By: Anne Thor	ne 2/4/2015		anne Am	_	
Reviewed By:	2164115/		Olivia Di ana		
Chain of Custody					
1. Custody seals intact on sa	ample bottles?	Yes	No 🗌	Not Present	
2. Is Chain of Custody comp	lete?	Yes 🗸	No 🗌	Not Present	
3. How was the sample deliv	ered?	Courier			
Log In					
4. Was an attempt made to	cool the samples?	Yes 🗸	No 🗌	NA 🗌	
5. Were all samples received	at a temperature of >0° C to 6.0°C	Yes 🗸	No 🗌	NA 🗆	
6. Sample(s) in proper conta	iner(s)?	Yes 🗸	No 🗌		
7. Sufficient sample volume f	for indicated test(s)?	Yes 🗸	No 🗌		
8. Are samples (except VOA	and ONG) properly preserved?	Yes 🗸	No 🗌		
9. Was preservative added to	bottles?	Yes 🗌	No 🗸	NA 🗌	
10.VOA vials have zero heads	space?	Yes	No 🗆	No VOA Vials	
11. Were any sample contained	ers received broken?	Yes	No 🗸	# of preserved	
				bottles checked	
Does paperwork match both (Note discrepancies on charter)		Yes 🗸	No 🗌	for pH: (<2 or	>12 unless noted)
13. Are matrices correctly iden		Yes 🗸	No 🗌	Adjusted?	
14. Is it clear what analyses we		Yes 🗸	No 🗌		
15. Were all holding times able		Yes 🗸	No 🗌	Checked by:	
(If no, notify customer for a	autionzation.)				
Special Handling (if app	licable)				
16. Was client notified of all dis	screpancies with this order?	Yes	No 🗌	NA 🗸	
Person Notified:	Date				
By Whom:	Via:	eMail P	hone Fax	In Person	
Regarding:					
Client Instructions:					
17. Additional remarks:					
18. Cooler Information Gooler No. Temp 9C. 1 2.4	Good Yes Seal No.	Seal Date	Signed By		

Chain-of-Custody Record			Turr-Around	IIIIe.	SAME				Н	A	LL	E	NV	/TE	20	NI	MEN	ATL	L		
Client:	BLAGG ENGR. / BP AMERICA			☐ Standard	✓ Rush _	DAY												RA			r
				Project Name																	
Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413			CITY OF FARMINGTON COM TILE				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109														
			Project #:				Tel. 505-345-3975 Fax 505-345-4107														
			-				Analysis Request														
Phone #: (505) 632-1199 email or Fax#:			Project Manager:												uco						
QA/QC Package:							2	-	•		1			504	PCB's			300.1)			
		Level 4 (Full Validation)		NELSON VELEZ			5 (8021B)	+ TPH (Gas only)	(MINO)			(S)		PO4,	2 PC			1		е	
Accreditation:			Sampler: NELSON VELEZ				(Gas	DRO,	크	1.	8270SIMS)		102,	8082			/ water		sample		
		On Ice: Yes No			1	TPH	-	418.1)	504.1)	827	S	03,1	-		JA)	-300.0 /		e se	1		
□ EDD (1	□ EDD (Type)			Sample Temp	erature: 7	\mathcal{U}	ţ	3E +	(GR	por		or	etal	CI,N	cide	(A)	i-V(e e	osit	1
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +-NH	BTEX + MTBE	TPH 8015B (GRO	TPH (Method	EDB (Method	PAH (8310	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	Grab sample	5 pt. composite	
22/03/15	0910	SOIL	SPC-TBE Z' (ZI)	4021	COOL	-00	1			/								/		1	Γ
										\exists									1		-
																					-
			RUN TPH 8015B IF TPH																		
			418.1 > 100 mg/Kg																		
																					Γ
																					Γ
Date:	Time:	Relinquished by:		Received by: Date Time				Remarks:													
02/03/15	15/16/4 Man Vf			(Aristellact 2/3/15 1614				BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401													
Date:	Time: Relinquished by:		Received by Date Time														1401 1472 Z	SUL	310	Y.	
43/15	1747	1 h	istuliante	A	02/	04/15 0830			OR							-		-			1
,	If necess	aty, samples s	submitted to Hall Environmental may be s	ubcontracted to other	accredited laboratorie	es. This serves as notice o	f this p	ossibil	ity. An	y sub-	-contra	acted o	data w	vill be	clearly	notati	ed on f	the analyt	ical repo	ort.	



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

February 2, 2015

City of Farmington Julie Baird 800 Municipal Drive Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: CITY OF FARMINGTON COM 001E API #: 3004526734

Dear Mrs. Baird,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 2, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at (505)-326-9214.

Sincerely,

Jerry Van Riper

9 Ducker

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

January 29, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

CITY OF FARMINGTON COM 001E API 30-045-26734 (J)Section 10 – T29N – R13W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around February 2, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



