

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP


3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit F (SENW), 1960' FNL & 660' FWL, Section 18, T32N, R8W, NMPM

2005 OCT 12 PM 1 30

RECEIVED  
070 FARMINGTON NM



5. Lease Number  
NMNM-33055
6. If Indian, All. or  
Tribe Name
7. Unit Agreement Name
8. Well Name & Number  
Trail Canyon 103S
9. API Well No.  
30-045-33097
10. Field and Pool  
Basin Fruitland Coal
11. County and State  
San Juan Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection

☒ Other - Completion Detail

**13. Describe Proposed or Completed Operations**

9/14/05 MIRU Aztec #560. NU BOP, PT-OK. PT 7" casing & blind rams to 1500 psi/30 min. Good test. RIH w/6-1/4" bit & tagged top of float collar @ 3293'. D/O collar, hard cement & shoe then ahead to 3739' (TD). TD reached 9/16/04. Circ. hole. RIH w/9-1/2" underreamer & underreamed from 3345' - 3739'. Circ. hole. Started natural surges. Then used natural and energized surges for 5 days. Underreamed periodically during cleanout. UR & Surged C/O fill till 10/5/05. 10/5/05 RIH w/5-1/2", 20#, K-55 pre-perf'd liner (13 jts) and set liner @ 3739' w/TOL @ 3320'. Perfs from 3655' - 3635', 3619' - 3556', 3495' - 3432'; 3410' - 3367' = 189' = 189 holes (.32"). 10/6/05 RIH w/mill & milled out perf plugs. Milled out fill to PBTD. Used air & mist to circ. out. Blow well for 4 days. RIH w/ 2-3/8", 4.7# J-55 tbg and set @ 3719' w/SN @ 3688'. 10/10/04 RIH w/pump & rods. Spaced out. Load tbg & PT to 500 psi - good test. RD & released rig @ 1800 hrs 10/10/05.

**14. I hereby certify that the foregoing is true and correct.**

Signed Patsy Clugston Patsy Clugston Title Sr. Regulatory Specialist Date 10/13/05

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

**ACCEPTED FOR RECORD**Date OCT 14 2005**FARMINGTON FIELD OFFICE**

NM000 916