

Casing 1; 0.00 in; 0.0 ftKB

Conductor; 9 5/8 in; J-55; 14.0-75.0 ftKB
Surface; 12 1/4; 527.0

Surface Casing Cement; 0.0-527.0; Cement
Surface; 9 5/8 in; J-55; 14.0-527.0 ftKB

Pinion Unit D14-2410 02H
API: 30-045-35530

Intermediate; 8 3/4; 5,905.0

Intermediate 1; 7 in; J-55; 14.0-5,905.0 ftKB

Intermediate 1 Casing Cement; 0.0-5,974.0; Cement

Perforated; 6,164.0-6,407.0; 12/13/2014

Perforated; 6,494.0-6,754.0; 12/13/2014

Perforated; 6,841.0-7,101.0; 12/12/2014

Perforated; 7,188.0-7,455.0; 12/12/2014

Perforated; 7,541.0-7,788.0; 12/12/2014

Perforated; 7,874.0-8,141.0; 12/11/2014

Perforated; 8,228.0-8,488.0; 12/11/2014

Production; 6 1/8; 11,288.0

Perforated; 8,575.0-8,835.0; 12/11/2014

Perforated; 8,922.0-9,188.0; 12/11/2014

Perforated; 9,278.0-9,522.0; 12/11/2014

Perforated; 9,613.0-9,876.0; 12/10/2014

Perforated; 9,962.0-10,222.0; 12/10/2014

Perforated; 10,309.0-10,569.0; 12/10/2014

Perforated; 10,656.0-10,916.0; 12/09/2014

Perforated; 11,003.0-11,254.0; 12/05/2014

Production Liner Casing Cement; 5,797.0-11,285.0; Cement

TD - Original Hole; 11,288.0

Production Liner; 4 1/2 in; S-80; 5,800.2-11,288.0 ftKB

OIL CONS. DIV DIST. 3

APR 08 2015

AV