

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1. a. TYPE OF WELL:

OIL
WELL ☐GAS
WELL ☒DRY ☐

b. TYPE OF COMPLETION:

NEW
Well ☒WORK
OVER ☐DEEP-
EN ☐PLUG
BACK ☐DIFF.
CENTR. ☐

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface 2295' FNL & 805' FEL (SE/4 NE/4)

At top prod. interval reported below

same

At total depth

same

15. DATE SPUNDED

8/19/2005

16. DATE T.D. REACHED

8/24/2005

17. DATE COMPL.

(Ready to prod.)

10/5/2005

20. TOTAL DEPTH, MD & TVD

1595'

21. PLUG BACK T.D., MD & TVD

1539'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

6731' GL

TD

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*

1377'-1398' (Fruitland Coal)

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR-CNL-CCL

25. WAS DIRECTIONAL SURVEY MADE

no

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" J-55	24#	127'	12-1/4"	100 sx Class "B" neat w/2% CaCl2 w/1/4# celloflake/sx	
5-1/2" J-55	15.5#	1584'	7"	110 sx 2% Lodense w/1/4# celloflake/sx. Tail w/60 sx Class "B" neat w/1/4# celloflake/sx.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SBT (MD)
					2-3/8"	1455'	N/A

31. PERFORATION RECORD (Interval, size and number)

1377'-1398' w/4 spf (total 88 holes, XP 312-221T charges)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1377'-1398'	400 gals 15% HCL; 102,940# 20/40 Brady sand;
	53,052 gals AquaSafe gel

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump)					WELL STATUS (Producing or shut in)	
N/A		Pumping					Shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL - BBL.	GAS - MCF.	WATER - BBL.	GAS - OIL RATIO	
10/21/2005	24	n/a	→	0	14	240		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24 - HOUR RATE	OIL - BBL.	GAS - MCF.	WATER - BBL.	OIL GRAVITY - API (CORR.)		
25 psig	25 psig	→	0	14	240	ACCEPTED FOR RECORD		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented - to be sold

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Darrin Steed

Title

Petroleum Engineer

Date

NOV 01 2005
FARMINGTON FIELD OFFICE
BY 10/24/2005

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof: cored intervals; and all drill-stem, tests, including depth interval tested on used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Ojo Alamo	500'	
				Kirtland	583'	
				Fruitland	1055'	
				Pictured Cliffs	1400'	
				TOTAL DEPTH	1595'	