

RECEIVED

FORM APPROVED
OMB NO. 1004-0136
Expires: November 30, 2000

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

5. Lease Serial No.
SF-078988

6. Indian, Allottee or Tribe Name
N/A

7. If Unit or CA Agreement, Name and No.
NORTHEAST BLANCO UNIT

8. Lease Name and Well No.
NEBU 61A

9. API Well No.
30045 3/272

10. Field and Pool, or Exploratory
Blanco Mesaverde Basin Dakota

11. Sec., T., R., M., or Blk. And Survey or Area
Sec. 19, T 31N, R 6W
H

12. County or Parish
San Juan

13. State
NM

1a. Type of Work ☒ DRILL ☐ REENTER

1b. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other ☐ Single Zone ☒ Multiple Zone

2. Name of Operator
Attn: Diane Busch Devon Energy Production Company, L.P.

3a. Address
20 N. Broadway Oklahoma City, OK 73102

3b. Phone No. (include area code)
(405) 228-4362

4. Location of well (Report location clearly and in accordance with any State requirements.)
At surface 2000' FNL & 75' FEL SE NE Unit H
At bottom hole Same
At proposed prod. zone Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*
Approximately 25.5 mles from Ignacio, Colorado

15. Distance from proposed* location to nearest property or lease line, ft.
(Also to nearest drlg unit line, if any)
75'

16. No. of Acres in lease
2560

17. Spacing Unit dedicated to this well
320 E/2

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.

19. Proposed Depth
8100'

20. BLM/ BIA Bond No. on file
CO-1104

21. Elevations (Show whether DF, RT, GR, etc.)
6386' GL

22. Approximate date work will start*
Upon Approval

23. Estimated Duration
20 Days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1 shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by existing bond on file (see item 20 above).
- Operator certification.
- Such other site specific information and/ or plans as may be required by the authorized officer.

25. Signature Diane Busch Name (Printed/ Typed) Diane Busch Date 11-22-02

Title Sr. Operations Technician

Approved By (Signature) /s/ David J. Mankiewicz Name (Printed/ Typed) _____ Date _____

Title _____ Office _____

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

NMOCD

This action is subject to technical and
procedural review pursuant to 43 CFR 3165.3
and appeal pursuant to 43 CFR 3165.4

District I
PO Box 1980, Hobbs NM 88241-1980
District II
PO Drawer KK, Artesia, NM 87211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994

Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-045-31272	² Pool Code 72319/71599	³ Pool Name Blanco Mesaverde / Basin Dakota
⁴ Property Code 19641	⁵ Property Name NEBU	⁶ Well Number # 61A
⁷ OGRID No. 6137	⁸ Operator Name Devon Energy Production Company, L.P.	⁹ Elevation 6386

¹⁰ Surface Location

UL or Lot No. H	Section 19	Township 31 N	Range 6 W	Lot Idn	Feet from the 2000	North/South line NORTH	Feet from the 75	East/West line EAST	County SAN JUAN
--------------------	---------------	------------------	--------------	---------	-----------------------	---------------------------	---------------------	------------------------	--------------------

¹¹ Bottom Hole Location If Different From Surface

¹² UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹³ Dedicated Acres MV - E/320 DK - E/320	¹⁴ Joint or Infill	¹⁵ Consolidation Code	¹⁶ Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16	5285(R)	17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. Signature Diane Busch Printed Name DIANE BUSCH Title SR. OPERATIONS TECH. Date 11-22-02
5280(R)	19	18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Date of Survey September 16, 2002 Signature and Seal of Professional Surveyor GARY D. VANN 7016 7016 Certificate Number
RECEIVED	5271(R)	

**NEBU 61A
Unit H 19-31N-6W
San Juan Co., NM**

DRILLING PLAN

1. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS & ANTICIPATED WATER, OIL, GAS OR MINERAL FORMATIONS:

Formation	Depth (ft)	Hydrocarbon/Water Bearing Zones
San Jose	Surface	
Ojo Alamo	2340	Aquifer
Kirtland	2460	
Fruitland	2905	Gas
Pictured Cliffs	3235	Gas
Lewis	3425	Gas
Intermediate TD	3575	
Huerfanito bentonite	4125	
Massive Cliff House	5325	Gas
Menefee	5370	Gas
Massive Point Lookout	5605	Gas
Mancos	5980	Gas
Gallup	6945	Gas
Greenhorn	7660	
Graneros	7710	
Dakota	7845	Gas
TD	8100	

All shows of fresh water and minerals will be adequately protected and reported.

2. PRESSURE CONTROL EQUIPMENT:

All well control equipment shall be in accordance with Onshore Order #2 for 2M systems.

The minimum specifications for pressure control equipment that will be provided are included on the attached schematic diagram which shows the size and pressure ratings.

2000# BOP With Pipe Rams
2000# BOP With Blind Rams

Auxiliary equipment to be used:

- Upper kelly cock with handle available.

The manifold includes appropriate valves and adjustable chokes. The kill line will have one check valve. Ram type preventers will be pressure tested to full working pressure (utilizing a test plug) or 70% of the internal yield pressure (without a test plug) at:

- Initial installation
- Whenever any seal subject to test pressure is broken
- Following related repairs
- At 30 day intervals

Pipe and blind rams shall be activated each trip.

A BOPE pit level drill will be conducted weekly for each drilling crew.

All tests and drills will be recorded in the drilling log.

The accumulator will have sufficient capacity to close all rams and retain 200 psi above pre-charge pressure without the use of closing unit pumps.

Master controls will be at the accumulator.

3. CASING & CEMENTING PROGRAM:

A. The proposed casing program will be as follows:

Depth	Hole Size	Size	Grade	Weight	Thread	Condition
0-250'	12-1/4"	9-5/8"	H-40	32#	STC	New
0-3575'	8-3/4"	7"	K-55	23#	LTC	New
0-TD	6-1/4"	4-1/2"	K-55	11.6 #	LTC	New

All casing strings below the conductor shall be pressure tested to 0.22 psi/ft. of casing string length or 1500 psi, whichever is greater, but not to exceed 70% minimum internal yield.

The bottom three joints of the surface casing will have a minimum of one centralizer per joint and one centralizer every fourth joint thereafter.

B. The proposed cementing program will be as follows:

Surface String: Cement will be circulated to surface.

Lead: 200 sks Class "B" with additives mixed at 15.6 ppg, 1.19 ft³/sks.

Intermediate String: Cement will be circulated to surface.

Lead: 575 sks 50/50 Poz with additives mixed at 13.0 ppg, 1.44 ft³/sks prior to foaming, 9 ppg, 2.18 ft³/sks after foaming.

Tail: 75 sks 50/50 Poz with additives mixed at 13.0 ppg, 1.44 ft³/sks.

If hole conditions dictate, an alternate, two stage cement design will be used. Stage 1: 85 sacks Class B 50/50 POZ, 3% Gel, 5# Gilsonite, 1/4# Flocele, 1/10% CFR 3, .2% Halad 344, Yield 1.47 ft³/sks. Stage 2: 450 sacks Class B 50/50 POZ, 3% Gel, 5# Gilsonite, 1/4# Flocele, .1% CFR 3, .2% Halad 344, Yield 1.47 ft³/sks. Cement designed to circulate to surface.

Production String: TOC designed to circulate to surface, cement will tie into the intermediate casing as a minimum. Volumes may vary with actual well characteristics.

Lead: 500 sks 50/50 Poz with additives mixed at 13.0 ppg, 1.47 ft³/sks.

Actual volumes will be calculated and adjusted with caliper log prior to cementing.

4. DRILLING FLUIDS PROGRAM:

Interval	Type	Weight (ppg)	Viscosity	pH	Water Loss	Remarks
0-3575'	Spud-foam	8.4-9.0	29-70	8.0	NC	FW gel, LSND or stiff foam
3575'-7710'	Air				NC	
7710'-TD	Mud	8.5-9.0*	30-50	8.0-10.0	8-10cc @ TD	Low solids – nondispersed. * Min Wt. to control formation pressure.

NC = No Control

Sufficient quantities of mud material will be maintained on site or be readily accessible for the purpose of assuring well control. SPR will be recorded on daily drilling report after mudding up. Visual mud monitoring will be conducted during operations.