

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil
Well

☒ Gas
Well

☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1470' FNL & 1780' FEL (SW/4 NE/4)
Unit G, Sec: 19, T24N, R9W

5. Lease Designation and Serial No.

NO-G-0103-1462

6. If Indian, Allotted or Tribe Name

Navajo Allotted

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Bitsili #1

9. API Well No.

30 045 33186

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION


- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other TD, production casing
- ☒ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill to TD @ 6490' on 12/23/05. Run 4 1/2" 10.5# J-55 csg. Land @ 6490', float collar @ 6445', stage tool @ 4367'. Cement 1st stage w/345 sx Premium Lite High Strength, 3#/sx CSE, 2% KCL & 3% PhenoSeal. Circ 10 bbls cement. Cement 2nd stage w/575 sx Premium Lite FM, 3% CaCl2, 1/4# celloflake, 8% gel, .4% sodium metasilicate & 3% PhenoSeal. Tail w/100 sx Type III cement. Circ 20 bbls cement.

AM 10 08
RECEIVED
BUREAU OF LAND MANAGEMENT
FARMINGTON NM



14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Vice-President

Date

12/29/2005

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

JAN 05 2006

FARMINGTON FIELD OFFICE

BY *JB*