(August 1999) DEPARTMEN BUREAU OF L SUNDRY NOTICES AND RE Do not use this form for proposals abandoned well. Use Form 3160-3 SUBMIT IN TRIPLICATE - Other in	s to drill or to re-enter an RECI (APD) for such proposals 70 FARM	FORM APPROVED 1 Sudget Bureau No. 1004-0135 Expires: November 30, 2000 5. Lease Serial No. NMSF 077710 6. If Indian, Allottee or Tribe Name INM 7. If Unit or CA/Agreement, Name and/or No. 8. Well Name and No. Hardie No. 62S 9. API Well No. 30-045-32503	
3a. Address PO Box 5940, Farmington, NM 87499	3b. Phone No. (include area code) (505) 325-6779	10. Field and Pool, or Exploratory Area Basin Fruitland Coal	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FSL, 760' FWL, Sec. 14, T29N-R12W		11. County or Parish, State San Juan, New Mexico	
		NOTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent ☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans	Fracture Treat New Construction Plug and Abandon	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon Water Shut-Off Well Integrity Other Spud & Drilling	
Final Abandonment Notice Convert to Injection 13. Describe Proposed or Completed Operation (clearly state all pertinent of the Convert to Injection)		Water Disposal	_
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which ine work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or new interval, A Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) O7/22/05: Spudded 8-3/4" hole @ 6:45 a.m. Drilled to 144'. TIH w/7" 20# J-55 8RD ST&C csg & set @ 135'. Cemented csg w/80 sx (94.4 cf) Cl "B" cmt w/ 2% Cacl2 and 1/4#/sx cellophane flakes. Circ 4.5 bbls cmt to pit. O7/28/05: Drilled 6-1/4" hole to 2000'. TIH w 4-1/2" 10.5# J-55 8RD ST&C csg & set @ 1935'. Cemented w/ 95 sx (195.7 cf) Cl "B" cmt w/ 2% sodium metasilicate & 1/4#/sx cellophane flakes. Followed w/ 32 sx (37.76 cf) Cl "B" cmt w/ 2% Cacl2 & 1/4#/sx Cellophane flakes. Pressure test csg to 900 psi/30min OK TCC ~ Surface. Cement was circulated on Y.5". par Angel a Jaranwillo Hylbb			
 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Angela Jaramillo 	Title	Production Technician	
	inc	1 requestor 1 certifician	
Signature Should Strong Signature	Date	12/05/05	
Approved by	SPACE FÖR FEDERAL GR SPATE	OFFICE USE WOCEP TED FOR RECO!	राः
Conditions of approval, if any, are attached. Approval of this notice does not warra certify that the applicant holds legal or equitable title to those rights in the subject I which would entitle the applicant to conduct operation thereon.		JAN 0 4 2006	
Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime fo States any false, fictitious or fraudulent statements or representations as to any materials.		epartment or agency of the United FARMINGTON FIELD OFFICE	1

4