District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Is pit or below-grade tar Type of action: Registration of a pit of	ak covered by a "general plan"? Yes 🔀 No or below-grade tank 🔲 Closure of a pit or below-gr	ade tank 🔀
Operator: BP America Production Company Telephon Address: 200 Energy Ct, Farmington, NM 87401	ne: <u>(505)326-9200</u> e-mail address:	
	5004523092_U/LorQu/Qur_U	Sec 31 T3IN RBW
County: <u>San Juan</u> Latitude	Longitude	NAD: 1927 🗌 1983 🗍
Surface Owner: Federal 🗌 State 🗋 Private 🛄 Indian 🔲		
Pit Type: Drilling Production 🕱 Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume: bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If new	_
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points) (0 points) (0 points) (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points) (0 points) (20 poi
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit' your are burying in place) onsite offsite If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excava	Yes I f yes, show depth below ground surface	description of remedial action taken including
Additional Comments:		
See Attached Documentation		
· · · · · · · · · · · · · · · · · · ·		
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline		
	ture Ally C. Sligg	,
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.	not relieve the operator of liability should the content the operator of its responsibility for compliance with	s of the pit or tank contaminate ground water or any other federal, state, or local laws and/or
Approval: CEPUTY OR & GAS INSPECTOR, DIST. 64 Printed Name/Title	Signature Demp Fut	DEC 1 4 2005
	<i>V</i>	

			300452	3092				
CLIENT: <u>BP</u>	F	BLAC P.O. BOX	87, BLO		, NM 874			0: <u>80910</u> 0: <u>8785</u>
FIELD R	EPORI	F: CLC	́	·)N pag	E No:	/ of _/
LOCATION: <u>NAME</u> QUAD/UNIT: <i>O</i>							STARTED:	11/6/01
QTR/FOOTAGE:						5 1 1 1	RONMENTAL	NV
EXCAVATION APP	ROX <i>L</i> f	_ FT. x _ A	A FT. x	_NA_ FT	DEEP. C	UBIC YA	RDAGE: _	NA
DISPOSAL FACE						ETHOD: _		
		BLM				FORMA		
FIELD NOTES &								1
NMDCD RANKING SCO		_						NE :
SOIL AND EX	CAVATION				RF = 0.52			
DESCRIPTION:		TIME:	/ <u>0:/5</u>	- <u>/000</u> ppr /pm_DATE:	116/01	STE	ERGLASS TA	ANK INSTALLED
SOIL TYPE: SAND		ND / SILT / MED, GRA		/ CLAY / C	GRAVEL / DT	HER <u>BED</u>	rock (sh	MOSTONE)
COHESION (ALL DTI CONSISTENCY (NON	HERS): NON	COHESIVE /	SLIGHTLY C			HIGHLY CO	HESIVE	
PLASTICITY (CLAYS	S>: NON PL	ASTIC / SLIGH	ITLY PLASTI	с / СОНЕЗІХ	/E / MEDIUM		/ HIGHLY :	PLASTIC
DENSITY (COHESIVE MOISTURE: DRY /							CLOS	ED
DISCOLORATION/ST HC ODOR DETECTED	AINING DBSE	RVED: (YES/	ND EXPL	ANATION -	SEE COLD	R ABDLE		
AC UDUR DETECTET SAMPLE TYPE: G ADDITIONAL COMME								
BEDROCK	NTS FRIA	BLE, VERY	HARD	STEEL TI	n-K Kenou	ED e Ti	me of 1	AZKIVAL .
Bottom					CALCULATION	10		
SCALE	SAMP. TIME	SAMPLE I.D.	1	1		- 	READING	CALC. ppm
	PERIME	TER AN			1	I PIT P	 ROFILI	<u> </u> F
				WM				
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	RES SAMPLE	ULTS FIELD HEADSPACE				
	6'	RETAINING	1 e 4	PID (ppm)				
			2 @ 3 @					
		A PPROVE Z'AGOUE GRADE	4 @ 5 @					
6	Ð	->						
	7.	Comar.				NOT AF	PRICABU	ーモ
APPROX. 4			CALL POLL					
BELOW GRADE	10	دلد		H (8015) 10-	20			
	1. 17	$_{A}D$	1) RT	×(8021) /				1
	4 40							
P.D. = PIT DEPRES: T.H. = TEST HOLE	унс SION; B.G. =	BELOW GRADE	Волн	ARSSED)				

,

## ENVIROTECH LABS

### EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010	
Sample ID:	1@4'	Date Reported:	11-07-01	
Laboratory Number:	21430	Date Sampled:	11-06-01	
Chain of Custody No:	8785	Date Received:	11-06-01	
Sample Matrix:	Soil	Date Extracted:	11-07-01	
Preservative:	Cool	Date Analyzed:	11-07-01	
Condition:	Cool and Intact	Analysis Requested:	8015 TPH	
		Concentration	Det. Limit	
Parameter		(mg/Kg)	(mg/Kg)	
Gasoline Range (C5 - C10)			0.2	
Gasoline Range (C5 -	C10)	1,360	0.2	
Gasoline Range (C5 - Diesel Range (C10 - (		1,360 31.3	0.2 0.1	

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Dawson LS #1A Compressor Pit Grab Sample.

_ e . C Analyst

Mustur on Libeten Review

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505 • 632 • 0615 • Fax 505 • 632 • 1865

# ENVIROTECH LABS

-----

### EPA METHÓD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94	034-010
Sample ID:	1 @ 4'	Date Reported:	11-	-07-01
Laboratory Number:	21430	Date Sampled:	11-	-06-01
Chain of Custody:	8785	Date Received:	11	-06-01
Sample Matrix:	Soil	Date Analyzed:	11	-07-01
Preservative:	Cool	Date Extracted:	11	-07-01
Condition:	Cool & Intact	Analysis Requested:	BT	ΈX
			Det.	
<b>_</b>	Concentration		Limit	
Parameter	(U	g/Kg)	(ug/Kg)	
Benzene	1,160		1.8	
Toluene	141		1.7	
Ethylbenzene	1,670		1.5	
p,m-Xylene	5,010		2.2	
o-Xylene	3,330		1.0	
		11,310		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries: Pa		Parameter	Percent Recovery
		Fluorobenzene	97 %
		1,4-difluorobenzene	97 %
		Bromochlorobenzene	97 %
References:	Method 5030 December 19	B, Purge-and-Trap, Test Methods for Evaluat 196.	ting Solid Waste, SW-846, USEPA,
	Method 8021	B, Aromatic Volatile Organics, Test Methods	for Evaluating Solid Waste, SW-846,

Comments: Dawson LS #1A Compressor Pit Grab Sample.

USEPA, December 1996.

. C. (

Mistri n Walters Review