District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

For drilling and production facilities, submit to appropriate NMOCD District Office.

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes X No .

Type of action: Registration of a pit or below-grade tank \(\subseteq\) Closure of a pit or below-grade tank \(\subseteq\) Telephone: (505)326-9200 e-mail address: Operator: BP America Production Company Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: Bolack #2 API#: 3004523267 U/L or Qtr/Qtr 6 Sec 19 T 28N Latitude _____ Longitude _____ NAD: 1927 🗌 1983 🗍 County: San Juan Surface Owner: Federal State Private Indian Below-grade tank Type: Drilling | Production | Disposal | Volume: ____bbl Type of fluid: _____ Workover ☐ Emergency ☐ Construction material: ___ Double-walled, with leak detection? Yes If not, explain why not. Lined Unlined Liner type: Synthetic Thickness ____mil Clay __ Pit Volume (20 points) Less than 50 feet Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more (0 points) (20 points) Yes Wellhead protection area: (Less than 200 feet from a private domestic No (0 points) water source, or less than 1000 feet from all other water sources.) (20 points) Less than 200 feet Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more (0 points) **Ranking Score (Total Points)** If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite I If offsite, name of facility . (3) Attach a general description of remedial action taken including (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit , or an (attached) alternative OCD-approved plan ... Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. DEC 14 2005 DEPUTY OR & GAS INSPECTOR, DIST. 40 Approval: Printed Name/Title

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87 (505) 632-1199	2413 LOCATION NO: <u>80904</u> C.O.C. NO: <u>9591</u>			
FIELD REPORT: CLOSURE VERIFICATION	ON PAGE NO: of			
QUAD/UNIT: G SEC: 19 TWP: 28N RNG: 8W PM:NM CNTY: SJ ST				
QTR/FOOTAGE:2430'N 1650'E SWINE CONTRACTOR: FLINT				
EXCAVATION APPROX. 18 FT. x 18 FT. x 4 FT. DEEP. CUBIC YARDAGE: O DISPOSAL FACILITY: NA REMEDIATION METHOD: CLUSE AS IS LAND USE: RANGE - B LEASE: NM - 03549 FORMATION: DR				
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 115				
DEPTH TO GROUNDWATER >100 NEAREST WATER SOURCE >1000 NEAREST				
NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM	CHECK ONE : Z PIT ABANDONED			
SOIL AND EXCAVATION DVM CALIB. GAS = 250 ppm RF = 0.5				
DESCRIPTION: TIME: 1515 am pm DATE: 10-15-01	FIBERGLASS TANK INSTALLED			
SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / D	THER			
COHESION (ALL OTHERS): NON COHESIVO / SLIGHTLY COHESIVE / COHESIVE /	HIGHLY COHESIVE			
CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM	PLASTIC / HIGHLY PLASTIC			
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / I	HARD			
MOISTURE: DRY / CLIGHTLY MOIST / WET / SATURATED / SUPER SATURDISCOLORATION/STAINING OBSERVED: YES / NO EXPLANATION -	URATED (LASTO)			
HC DDOR DETECTED: YES /ND EXPLANATION -				
SAMPLE TYPE: (GRAB) / COMPOSITE - # OF PTS BACKHUE TO DIE Test Hole -				
SAM FLE				
FIELD 418.1 CALCULATIONS				
CCALE	N DILUTION READING CALC. ppm			
O FT				
N PIT PERIMETER	PIT PROFILE			
SAMPLE FIELD HEADSPACE				
SAMPLE FIELD HEADSPACE PID (ppm) 1 @ 7 O O				
2 @				
3 <u>e</u> 4 <u>e</u>	_ AÎ			
5 e A				
A 18 4'				
The state of the s				
	3			
LAB SAMPLES SAMPLE ANALYSIS TIME	¥ <u></u>			
(19') ANALTSIS (IME				
TDAVEL NOTES:	4.4			
TRAVEL NOTES: CALLOUT: 10/15/01 0800 ONSITE: 10/19/	1 1415			

revised: 07/16/01



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Dehy C @ 7'	Date Reported:	10-16-01
Laboratory Number:	21255	Date Sampled:	10-15-01
Chain of Custody No:	9591	Date Received:	10-15-01
Sample Matrix:	Soil	Date Extracted:	10-16-01
Preservative:	Cool	Date Analyzed:	10-16-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Bolack #2.

Analyst C. Office

Review Maller